PRODUCT DESCRIPTION



Extruded profile in aluminium, champagne, white or black powder coated with opal polycarbonate protection. Available in several color temperatures, dimmable and non dimmable.

Different compositions can be made with different lengths and corners.

TECHNICAL DATA

Application	surface - suspended- wall
Dimensions	L x 40 x 60mm
IP rating	IP20
Power	230V
Lifetime L70/F10/65°C	>60000h
MacAdam ellipse	3
Guarantee	5 year



Color Temperature	Forward current	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2700K	400mA	135 lm/W	90+	D
3000K	400mA	142 lm/W	90+	D
4000K	400mA	148 lm/W	90+	D

ORDER REFERENCE

> PROFILE

PROFILE /m	ZUMI41EP	**+ W / B / A / C / BR**	U40 EMPTY profile /m
END CAP	ZUMI41EC	**+ W / B / A / C / BR**	U40 ENDCAP
PMMA /m	ZUMI41PMMA		U40 PMMA satin plexi profile/m

W (white) / B (black) / A (aluminium) / C (champagne) / BR (bronze)

> MODULES FOR PMMA - **PMMA NOT INCLUDED, TO BE ORDERED SEPARATELY!**

COLOR TEMP.	LENGTH MODULE	ORDER REFERENCE ! + DD (for dimmable)	WATTAGE	LUMEN (LED)
2700K	1685mm	ZUMI94SL2380119	31,4W	3672 lm
	1404mm	ZUMI94XL2380119	26,2W	3060 lm
	1123mm	ZUMI94L2380119	20,9W	2448 lm
	842mm	ZUMI94M2380119	15,7W	1836 lm
	562mm	ZUMI94S2380119	10,5W	1224 lm
3000K	1685mm	ZUMI94SL2390119	31,4W	3816 lm
	1404mm	ZUMI94XL2390119	26,2W	3180 lm
	1123mm	ZUMI94L2390119	20,9W	2544 lm
	842mm	ZUMI94M2390119	15,7W	1908 lm
	562mm	ZUMI94S2390119	10,5W	1272 lm
4000K	1685mm	ZUMI94SL2400119	31,4W	3960 lm
	1404mm	ZUMI94XL2400119	26,2W	3300 lm
	1123mm	ZUMI94L2400119	20,9W	2640 lm
	842mm	ZUMI94M2400119	15,7W	1980 lm
	562mm	ZUMI94S2400119	10,5W	1320 lm

> Z-DOT module excl.Driver

COLOR TEMP.	LENGTH MODULE	FOR-WARD CURRENT	ORDER REFERENCE + W / B / A / C / BR	WATTAGE	LUMEN (LED)
2700K	180mm	200 mA	ZUMI1742823005	9,6W	1104 lm
3000K	180mm	200 mA	ZUMI1742893005	9,6W	1164 lm

(W (white) / B (black) / A (aluminium) / C (champagne) / BR (bronze)

> OPTIONS

CORNER 90°		ZUMI41C90		U40 Corner 90°
CORNER 180°		ZUMI41C180		U40 Corner 180°
SQUARE BASE		ZUMIPD6060	**+ W / B / A**	Square base 60x60
ROUND BASE		ZUMIPD801	**+ W / B / A**	Round base ø80mm
WIRE 1,60m		ZUMI12WIRE160		WIRE 5x0,75 1M60
WIRE 6,00m		ZUMI12WIRE600		WIRE 5x0,75 6M00
SUSPENSION CABLE SINGLE		ZUMI12SUSPSU70160		U40 suspension cable single 1m60
		ZUMI12SUSPSU70600		U40 suspension cable single 6m00
COVERPROF.		ZUMI41CP	**+ W / B / A / C / BR**	U40 coverprofile /m
EMERGENCY KIT		on request		

> DRIVER

Included, if dimmable: DALI, pushDIM (for dimmable add DD to order reference!)

PRODUCT DESCRIPTION



Extruded profile in aluminium, champagne, white or black powder coated with opal polycarbonate protection. Available in several color temperatures, dimmable and non dimmable.

Different compositions can be made with different lengths and corners.

TECHNICAL DATA

Application	surface - suspended- wall
Dimensions	L x 40 x 60mm
IP rating	IP20
Power	230V
Lifetime L70/F10/65°C	>60000h
MacAdam ellipse	3
Guarantee	5 year



Color Temperature	Forward current	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2700K	275mA	136 lm/W	90+	D
3000K	400mA	146 lm/W	90+	D
4000K	400mA	153 lm/W	90+	D

ORDER REFERENCE

> PROFILE

PROFILE /m	ZUMI41EP	**+ W / B / A / C / BR**	U40 EMPTY profile /m
END CAP	ZUMI41EC	**+ W / B / A / C / BR**	U40 ENDCAP
PMMA /m	ZUMI41PMMA		U40 PMMA satin plexi profile/m

(W (white) / B (black) / A (aluminium) / C (champagne) / BR (bronze)

> MODULES FOR PMMA **- PMMA NOT INCLUDED, TO BE ORDERED SEPARATELY!**

COLOR TEMP.	LENGTH MODULE	ORDER REFERENCE ! + DD (for dimmable)	WATTAGE	LUMEN (LED)
2700K	1685mm	ZUMI94SL1880123	64,6W	7638 lm
	1404mm	ZUMI94XL1880123	53,8W	6365 lm
	1123mm	ZUMI94L1880123	43,1W	5092 lm
	842mm	ZUMI94M1880123	32,3W	3819 lm
	562mm	ZUMI94S1880123	21,6W	2546 lm
3000K	1685mm	ZUMI94SL1890119	61,7W	7836 lm
	1404mm	ZUMI94XL1890119	51,5W	6530 lm
	1123mm	ZUMI94L1890119	41,2W	5224 lm
	842mm	ZUMI94M1890119	30,9W	3918 lm
	562mm	ZUMI94S1890119	20,6W	2612 lm
4000K	1685mm	ZUMI94SL1900119	61,7W	8220 lm
	1404mm	ZUMI94XL1900119	51,5W	6850 lm
	1123mm	ZUMI94L1900119	41,2W	5480 lm
	842mm	ZUMI94M1900119	30,9W	4110 lm
	562mm	ZUMI94S1900119	20,6W	2740 lm

> Z-DOT module excl.Driver

COLOR TEMP.	LENGTH MODULE	FOR-WARD CURRENT	ORDER REFERENCE + W / B / A / C / BR	WATTAGE	LUMEN (LED)
2700K	180mm	200 mA	ZUMI1742823005	9,6W	1104 lm
3000K	180mm	200 mA	ZUMI1742893005	9,6W	1164 lm

(W (white) / B (black) / A (aluminium) / C (champagne) / BR (bronze)

> OPTIONS

CORNER 90°		ZUMI41C90		U40 Corner 90°
CORNER 180°		ZUMI41C180		U40 Corner 180°
SQUARE BASE		ZUMIPD6060	**+ W / B / A**	Square base 60x60
ROUND BASE		ZUMIPD801	**+ W / B / A**	Round base ø80mm
WIRE 1,60m		ZUMI12WIRE160		WIRE 5x0,75 1M60
WIRE 6,00m		ZUMI12WIRE600		WIRE 5x0,75 6M00
SUSPENSION CABLE SINGLE		ZUMI12SUSPSU70160		U40 suspension cable single 1m60
		ZUMI12SUSPSU70600		U40 suspension cable single 6m00
COVERPROF.		ZUMI41CP	**+ W / B / A / C / BR**	U40 coverprofile /m
EMERGENCY KIT		on request		

> DRIVER

Included, if dimmable: DALI, pushDIM (for dimmable add DD to order reference!)

PRODUCT DESCRIPTION



Extruded profile in aluminium, champagne, white or black powder coated with opal polycarbonate protection. The tunable white version goes from 2700K up to 6500K and is standard dimmable (DALI, DSI or switchDIM).

Different compositions can be made with different lengths and corners.

TECHNICAL DATA

Application	surface - suspended- wall wall - surface
Dimensions	L x 40 x 60mm
IP rating	IP20
Power	230V
Lifetime L70/F10/65°C	50000h
MacAdam ellipse	3
Guarantee	5 year



Color Temperature	Forward Current	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
WW	275mA	130 lm/W	90+	F
CW	275mA	145 lm/W	90+	F

ORDER REFERENCE

> PROFILE

PROFILE /m	ZUMI41EP	**+ W / B / A / C / BR**	U40 EMPTY profile /m
END CAP	ZUMI41EC	**+ W / B / A / C / BR**	U40 ENDCAP
PMMA /m	ZUMI41PMMA		U40 PMMA satin plexi profile/m

(W (white) / B (black) / A (aluminium) / C (champagne) / BR (bronze)

> MODULES FOR PMMA **PMMA NOT INCLUDED, TO BE ORDERED SEPARATELY!**

COLOR TEMP.	LENGTH MODULE	ORDER REFERENCE ! + DD (for dimmable)	WATTAGE	LUMEN (LED)
2700K - 6500K	1404mm	ZUMI94XL2720114	68,7 W	7500 lm
	1123mm	ZUMI94L2320114	55,3 W	6000 lm
	842mm	ZUMI94M2310114	44,4 W	4500 lm

> Z-DOT module excl.Driver

COLOR TEMP.	LENGTH MODULE	FOR-WARD CURRENT	ORDER REFERENCE + W / B / A / C / BR	WATTAGE	LUMEN (LED)
2700K	180mm	200 mA	ZUMI1742823005	9,6W	1104 lm
3000K	180mm	200 mA	ZUMI1742893005	9,6W	1164 lm

(W (white) / B (black) / A (aluminium) / C (champagne) / BR (bronze)

> OPTIONS

CORNER 90°	ZUMI41C90		U40 Corner 90°
CORNER 180°	ZUMI41C180		U40 Corner 180°
SQUARE BASE	ZUMIPD6060	**+ W / B / A**	Square base 60x60
ROUND BASE	ZUMIPD801	**+ W / B / A**	Round base ø80mm
WIRE 1,60m	ZUMI12WIRE160		WIRE 5x0,75 1M60
WIRE 6,00m	ZUMI12WIRE600		WIRE 5x0,75 6M00

> OPTIONS

SUSPENSION CABLE SINGLE		ZUMI12SUSPSU70160 ZUMI12SUSPSU70600		U40 suspension cable single 1m60 U40 suspension cable single 6m00
COVERPROF.		ZUMI41CP	**+ W / B / A / C / BR**	U40 coverprofile /m

> DRIVER

Included, standard dimmable DALI (only Device Type 8), DSI, switchDIM