


**PRODUCT DESCRIPTION**

The TUBB M10 is a rotatable spot with M10 connector for general or accent lighting.  
Aluminium Luminaire in several colors and color temperatures with several possible reflectors.

**TECHNICAL DATA**

Application	On profile
Dimensions	ø 80mm h 80mm
IP rating	IP20
Power	350mA / 500mA
Lifetime L70/F10/65°C	>55000h
MacAdam ellipse	3
Guarantee	5 year

(\*on components, only if ordered luminaire **+driver**)



Color Temperature	Wattage excl. driver	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2700K	11,8W	350mA	1558 lm	134 lm/W	90+	E
	16,9W	500mA	2225 lm	134 lm/W	90+	E
3000K	11,8W	350mA	1714 lm	147 lm/W	90+	E
	16,9W	500mA	2449 lm	147 lm/W	90+	E
3500K	11,8W	350mA	1732 lm	149 lm/W	90+	E
	16,9W	500mA	2474 lm	149 lm/W	90+	E
4000K	11,8W	350mA	1775 lm	152 lm/W	90+	E
	16,9W	500mA	2536 lm	152 lm/W	90+	E

**ORDER REFERENCE**

> LUMINAIRE

**! ORDER REFERENCE** + (1) **W** (white) / **B** (black) / **C** (champagne) / **F** (forest)  
+ (2) **G** (gold reflector) option only for 2700K or 3000K

**2700K**

14°	ZUMI672132317	Tubb M10 CRI90+ SLE G7 11,8/16,9W 350/500mA 1558/2225 lm 2700K 14° glass excl. driver
25°	ZUMI672132417	Tubb M10 CRI90+ SLE G7 11,8/16,9W 350/500mA 1558/2225 lm 2700K 25° glass excl. driver
39°	ZUMI672132517	Tubb M10 CRI90+ SLE G7 11,8/16,9W 350/500mA 1558/2225 lm 2700K 39° glass excl. driver
61°	ZUMI672132617	Tubb M10 CRI90+ SLE G7 11,8/16,9W 350/500mA 1558/2225 lm 2700K 61° glass excl. driver

**3000K**

14°	ZUMI672142317	Tubb M10 CRI90+ SLE G7 11,8/16,9W 350/500mA 1558/2225 lm 2700K 14° glass excl. driver
25°	ZUMI672142417	Tubb M10 CRI90+ SLE G7 11,8/16,9W 350/500mA 1714/2449 lm 3000K 25° glass excl. driver
39°	ZUMI672142617	Tubb M10 CRI90+ SLE G7 11,8/16,9W 350/500mA 1714/2449 lm 3000K 39° glass excl. driver
61°	ZUMI672142617	Tubb M10 CRI90+ SLE G7 11,8/16,9W 350/500mA 1714/2449 lm 3000K 61° glass excl. driver

**3500K**

14°	ZUMI672152317	Tubb M10 CRI90+ SLE G7 11,8/16,9W 350/500mA 1558/2225 lm 2700K 14° glass excl. driver
25°	ZUMI672152417	Tubb M10 CRI90+ SLE G7 11,8/16,9W 350/500mA 1732/2474 lm 3500K 25° glass excl. driver
39°	ZUMI672152517	Tubb M10 CRI90+ SLE G7 11,8/16,9W 350/500mA 1732/2474 lm 3500K 39° glass excl. driver
61°	ZUMI672152617	Tubb M10 CRI90+ SLE G7 11,8/16,9W 350/500mA 1732/2474 lm 3500K 61° glass excl. driver

**4000K**

14°	ZUMI672162317	Tubb M10 CRI90+ SLE G7 11,8/16,9W 350/500mA 1558/2225 lm 2700K 14° glass excl. driver
25°	ZUMI672162417	Tubb M10 CRI90+ SLE G7 11,8/16,9W 350/500mA 1775/2536 lm 4000K 25° glass excl. driver
39°	ZUMI672162517	Tubb M10 CRI90+ SLE G7 11,8/16,9W 350/500mA 1775/2536 lm 4000K 39° glass excl. driver
61°	ZUMI672162617	Tubb M10 CRI90+ SLE G7 11,8/16,9W 350/500mA 1775/2536 lm 4000K 61° glass excl. driver

> OPTIONS

**Honeycomb grid**

ZUMI25HC

Honeycomb grid

> DRIVER to be placed remoted

**PRODUCT DESCRIPTION**

The TUBB M10 is a rotatable spot with M10 connector for general or accent lighting equipped with a LED-module especially to enlighten several food products.

There's a choice between 'fish' to light up fish products, 'gold' for bakery goods and 'gold+' for rather crusty bakery goods such as croissants and baguettes.

The cannon 'meat+' provides a highly red color which is ideal for the presentation of meat.


Its 'fresh meat' is suitable to use for meat in the counter. Fruit is ideal for fruit and vegetables.

Aluminium Luminaire in several colors and color temperatures with several possible reflectors.

**TECHNICAL DATA**

Application	On profile
Dimensions	ø 80mm h 80mm
IP rating	IP20
Power	350mA / 500mA
Lifetime L70/F10/65°C	>55000h
MacAdam ellipse	3
Guarantee	5 year

(\*on components, only if ordered luminaire **+driver**)



Color Temperature	Wattage excl. driver	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
FISH	11,8W	350mA	1411 lm	121 lm/W	/	E
	16,9W	500mA	2015 lm	121 lm/W	/	E
GOLD 2700K	11,8W	350mA	1308 lm	112 lm/W	/	E
	16,9W	500mA	1868 lm	112 lm/W	/	E
GOLD+ 2400K	11,8W	350mA	826 lm	73 lm/W	/	F
	16,9W	500mA	1171 lm	70 lm/W	/	F
MEAT+	11,8W	350mA	879 lm	75 lm/W	/	n.a
	16,9W	500mA	1256 lm	75 lm/W	/	n.a
FRESH MEAT	11,8W	350mA	857 lm	74 lm/W	/	n.a
	16,9W	500mA	1224 lm	74 lm/W	/	n.a
FRUIT	11,8W	350mA	1224 lm	105 lm/W	/	F
	16,9W	500mA	1748 lm	105 lm/W	/	F

**ORDER REFERENCE**

> LUMINAIRE

**! ORDER REFERENCE** + (1) **W** (white) / **B** (black) / **G** (gold) / **F** (forest)  
+ (2) **G** (gold reflector) option only for Gold 2700K

**FISH**

14°	ZUMI672173117	Tubb M10 Fish SLE G7 11,8/16,9W 350/500mA 1411/2015 lm 14° PC excl. driver
25°	ZUMI672171917	Tubb M10 Fish SLE G7 11,8/16,9W 350/500mA 1411/2015 lm 25° PC excl. driver
39°	ZUMI672172017	Tubb M10 Fish SLE G7 11,8/16,9W 350/500mA 1411/2015 lm 39° PC excl. driver
61°	ZUMI672172117	Tubb M10 Fish SLE G7 11,8/16,9W 350/500mA 1411/2015 lm 61° PC excl. driver

**GOLD 2700K**

14°	ZUMI672183117	Tubb M10 Gold SLE G7 11,8/16,9W 350/500mA 1308/1868 lm 2700K14° PC excl. driver
25°	ZUMI672181917	Tubb M10 Gold SLE G7 11,8/16,9W 350/500mA 1308/1868 lm 2700K 25° PC excl. driver
39°	ZUMI672182017	Tubb M10 Gold SLE G7 11,8/16,9W 350/500mA 1308/1868 lm 2700K 39° PC excl. driver
61°	ZUMI672182117	Tubb M10 Gold SLE G7 11,8/16,9W 350/500mA 1308/1868 lm 2700K 61° PC excl. driver

**GOLD+ 2400K**

14°	ZUMI672083117	Tubb M10 Gold+ SLE G7 11,8/16,9W 350/500mA 826/1171 lm 2400K 14° PC excl. driver
25°	ZUMI672081917	Tubb M10 Gold+ SLE G7 11,8/16,9W 350/500mA 826/1171 lm 2400K 25° PC excl. driver
39°	ZUMI672082017	Tubb M10 Gold+ SLE G7 11,8/16,9W 350/500mA 826/1171 lm 2400K 39° PC excl. driver
61°	ZUMI672082117	Tubb M10 Gold+ SLE G7 11,8/16,9W 350/500mA 826/1171 lm 2400K 61° PC excl. driver

# ZUMI

---

## MEAT+

14°	ZUMI672193117	Tubb M10 Meat+ SLE G7 11,8/16,9W 350/500mA 879/1256 lm 14° PC excl. driver
25°	ZUMI672191917	Tubb M10 Meat+ SLE G7 11,8/16,9W 350/500mA 879/1256 lm 25° PC excl. driver
39°	ZUMI672192017	Tubb M10 Meat+ SLE G7 11,8/16,9W 350/500mA 879/1256 lm 39° PC excl. driver
61°	ZUMI672192117	Tubb M10 Meat+ SLE G7 11,8/16,9W 350/500mA 879/1256 lm 61° PC excl. driver

## FRESH MEAT

14°	ZUMI672203117	Tubb M10 Fresh Meat SLE G7 11,8/16,9W 350/500mA 857/1224 lm 14° PC excl. driver
25°	ZUMI672201917	Tubb M10 Fresh Meat SLE G7 11,8/16,9W 350/500mA 857/1224 lm 25° PC excl. driver
39°	ZUMI672202017	Tubb M10 Fresh Meat SLE G7 11,8/16,9W 350/500mA 857/1224 lm 39° PC excl. driver
61°	ZUMI672202117	Tubb M10 Fresh Meat SLE G7 11,8/16,9W 350/500mA 857/1224 lm 61° PC excl. driver

## FRUIT

14°	ZUMI672213117	Tubb M10 Fruit SLE G7 11,8/16,9W 350/500mA 1224/1748 lm 14° PC excl. driver
25°	ZUMI672211917	Tubb M10 Fruit SLE G7 11,8/16,9W 350/500mA 1224/1748 lm 25° PC excl. driver
39°	ZUMI672212017	Tubb M10 Fruit SLE G7 11,8/16,9W 350/500mA 1224/1748 lm 39° PC excl. driver
61°	ZUMI672212117	Tubb M10 Fruit SLE G7 11,8/16,9W 350/500mA 1224/1748 lm 61° PC excl. driver

## > OPTIONS

### Honeycomb grid

ZUMI25HC

Honeycomb grid

> DRIVER to be placed remoted

**PRODUCT DESCRIPTION**

The TUBB M10 is a rotatable spot with M10 connector for general or accent lighting.  
Aluminium Luminaire in several colors and color temperatures with several possible reflectors.

**TECHNICAL DATA**

Application	On profile
Dimensions	ø 80mm h 80mm
IP rating	IP20
Power	350mA / 500mA
Lifetime L70/F10/65°C	>55000h
MacAdam ellipse	2
Guarantee	5 year
(*on components, only if ordered luminaire <b>+driver</b> )	

Color Temperature	Wattage excl. driver	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
3100K	11,8W	350mA	1210 lm	104 lm/W	98	F
	16,9W	500mA	1729 lm	104 lm/W	98	F

**ORDER REFERENCE**

> LUMINAIRE

**! ORDER REFERENCE** + (1) **W** (white) / **B** (black) / **G** (gold) / **F** (forest)  
+ (2) **G** (gold reflector)

<b>14°</b>	ZUMI672222317	Tubb M10 Art CRI97 SLE G7 11,8/16,9W 350/500mA 1210/1729lm 3100K 14° glass excl. driver
<b>25°</b>	ZUMI672222417	Tubb M10 Art CRI97 SLE G7 11,8/16,9W 350/500mA 1210/1729lm 3100K 25° glass excl. driver
<b>39°</b>	ZUMI672222517	Tubb M10 Art CRI97 SLE G7 11,8/16,9W 350/500mA 1210/1729lm 3100K 39° glass excl. driver
<b>61°</b>	ZUMI672222617	Tubb M10 Art CRI97 SLE G7 11,8/16,9W 350/500mA 1210/1729lm 3100K 61° glass excl. driver

> OPTIONS

**Honeycomb grid**

ZUMI25HC

Honeycomb grid

> DRIVER to be placed remoted

**PRODUCT DESCRIPTION**

The TUBB M10 is a rotatable spot with M10 connector for general or accent lighting.  
Aluminium Luminaire in several colors and color temperatures with several possible reflectors.

**TECHNICAL DATA**

Application	On profile
Dimensions	∅ 80mm h 80mm
IP rating	IP20
Power	350mA / 500mA
Lifetime L70/F10/65°C	>55000h
MacAdam ellipse	2
Guarantee	5 year
(*on components, only if ordered luminaire <b>+driver</b> )	

Color Temperature	Wattage excl. driver	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
3250K	11,8W	350mA	1313 lm	136 lm/W	95	F
	16,9W	500mA	1876 lm	136 lm/W	95	F

**ORDER REFERENCE**

> [LUMINAIRE](#)

**! ORDER REFERENCE + (1) W (white) / B (black) / G (gold) / F (forest)**

<b>14°</b>	ZUMI672232317	Tubb M10 Fashion CRI95 SLE G7 11,8/16,9W 350/500mA 1313/1876 lm 3250K 14° glass excl. driver
<b>25°</b>	ZUMI672232417	Tubb M10 Fashion CRI95 SLE G7 11,8/16,9W 350/500mA 1313/1876 lm 3250K 25° glass excl. driver
<b>39°</b>	ZUMI672232517	Tubb M10 Fashion CRI95 SLE G7 11,8/16,9W 350/500mA 1313/1876 lm 3250K 39° glass excl. driver
<b>61°</b>	ZUMI672232617	Tubb M10 Fashion CRI95 SLE G7 11,8/16,9W 350/500mA 1313/1876 lm 3250K 61° glass excl. driver

> [OPTIONS](#)

**Honeycomb grid**

ZUMI25HC

Honeycomb grid

> [DRIVER to be placed remotod](#)