

PRODUCT DESCRIPTION

The Floorline 2000 PLK is a floor lamp with 2 PLK spots mounted on a profile with indirect lighting. The tubes, with a diameter of about 40mm and a length of 138mm, are 359° rotatable and 80° inclinable.

Aluminium luminaire, white or black placed on a square base.
Inclusive wire (2,5m) & plug-in. Dimmable via push button.

TECHNICAL DATA

Application	Floorlamp
Dimensions	h: 2000mm base : L295mm x B295mm
IP rating	IP20
Power	230V
Lifetime L70/F10/65°C	>60000h
MacAdam ellipse	3
Guarantee	5 year

SPOTS

Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2700K	2x8W	200mA	2x840 lm	123 lm/W	90+	E
3000K	2x8W	200mA	2x895 lm	131 lm/W	90+	E

INDIRECT LIGHT

Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2700K	31W	200mA	2294 lm	123 lm/W	90+	E
3000K	31W	200mA	2442lm	79 lm/W	90+	E


ORDER REFERENCE

> [LUMINAIRE](#)

! **ORDER REFERENCE** + **W** (white) / **B** (black)

2700K ZUMI1932241201 FLOORLINE 2000 PLK 40° SLE G7 2x8W/840lm + 31W 2294lm 927 incl.driver dim
3000K ZUMI1932251201 FLOORLINE 2000 PLK 40° SLE G7 2x8W/895lm + 31W 2442lm 930 incl.driver dim.

> [Dimmable Driver included - Dim via push button](#)



PRODUCT DESCRIPTION

The Floorline 2400 PLK is a floor lamp with 3 PLK spots mounted on a profile with indirect lighting. The tubes, with a diameter of about 40mm and a length of 138mm, are 359° rotatable and 80° inclinable.

Aluminium luminaire, white or black placed on a square base. Inclusive wire (2,5m) & plug-in. Dimmable via push button.

TECHNICAL DATA

Application	Floorlamp
Dimensions	h: 2400mm base : L295mm x B295mm
IP rating	IP20
Power	230V
Lifetime L70/F10/65°C	>60000h
MacAdam ellipse	3
Guarantee	5 year

SPOTS

Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2700K	3x8W	200mA	3x840 lm	123 lm/W	90+	E
3000K	3x8W	200mA	3x895 lm	131 lm/W	90+	E

INDIRECT LIGHT

Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2700K	31W	200mA	2790 lm	123 lm/W	90+	E
3000K	32.4W	200mA	2970lm	79 lm/W	90+	E


ORDER REFERENCE

> [LUMINAIRE](#)

! **ORDER REFERENCE** + **W** (white) / **B** (black)

2700K ZUMI1812241201 FLOORLINE 2400 PLK 40° SLE G7 3x8W/840lm + 37W 2790lm 927 incl.driver dim
3000K ZUMI1812251201 FLOORLINE 2400 PLK 40° SLE G7 3x8W/895lm + 37W 2970lm 930 incl.driver dim.

> [Dimmable Driver](#) included - Dim via push button



PRODUCT DESCRIPTION

The Floorline 2000 TUBB is a floor lamp with 2 TUBB spots mounted on a profile with indirect lighting. The tubes, with a diameter of about 80mm and a length of 80mm, are 359° rotatable and 80° inclinable.

Aluminium luminaire, white or black placed on a square base.
Inclusive wire (2,5m) & plug-in. Dimmable via push button.

TECHNICAL DATA

Application	Floorlamp
Dimensions	h: 2000mm base : L295mm x B295mm
IP rating	IP20
Power	230V
Lifetime L70/F10/65°C	>60000h
MacAdam ellipse	3
Guarantee	5 year

SPOTS

Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2700K	2x19,4W	500mA	2x2225 lm	134 lm/W	90+	E
3000K	2x19,4W	500mA	2x2449 lm	147 lm/W	90+	E

INDIRECT LIGHT

Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2700K	31W	200mA	2294 lm	123 lm/W	90+	E
3000K	31W	200mA	2442lm	79 lm/W	90+	E

ORDER REFERENCE

> LUMINAIRE

! ORDER REFERENCE + W (white) / B (black)

2700K ZUMI1932132501 FLOORLINE 2000 TUBB SLE G7 2x19,4W/2225lm + 31W 2294lm 927 incl.driver dim
3000K ZUMI1932142501 FLOORLINE 2000 TUBB SLE G7 2x19,4W/2449lm + 31W 2442lm 930 incl.driver dim.

> Dimmable Driver included - Dim via push button

PRODUCT DESCRIPTION

The Floorline 2400 TUBB is a floor lamp with 3 TUBB spots mounted on a profile with indirect lighting. The tubes, with a diameter of about 80mm and a length of 80mm, are 359° rotatable and 80° inclinable.

Aluminium luminaire, white or black placed on a square base.
Inclusive wire (2,5m) & plug-in. Dimmable via push button.

TECHNICAL DATA

Application	Floorlamp
Dimensions	h: 2400mm base : L295mm x B295mm
IP rating	IP20
Power	230V
Lifetime L70/F10/65°C	>60000h
MacAdam ellipse	3
Guarantee	5 year

SPOTS

Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2700K	3x19,4W	500mA	3x2225 lm	134 lm/W	90+	E
3000K	3x19,4W	500mA	3x2449 lm	147 lm/W	90+	E

INDIRECT LIGHT

Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2700K	31W	200mA	2790 lm	123 lm/W	90+	E
3000K	32.4W	200mA	2970lm	79 lm/W	90+	E

ORDER REFERENCE

> LUMINAIRE

! ORDER REFERENCE + W (white) / B (black)

2700K ZUMI1812132501 FLOORLINE 2400 TUBB SLE G7 3x19,4W/2225lm + 37W 2790lm 927 incl.driver dim
3000K ZUMI1812142501 FLOORLINE 2400 TUBB SLE G7 3x19,4W/2449lm + 37W 2970lm 930 incl.driver dim.

> Dimmable Driver included - Dim via push button

