

PRODUCT DESCRIPTION

The mini version of the cannon. A recessed downlighter for general or accent lighting with a CRI of 90 for a better color accuracy.

Aluminium luminaire, white or black powder coated, available in several color temperatures, with several possible reflectors (25°, 39°, 61°).


Standard equipped with torsion springs.



TECHNICAL DATA

| | |
|-----------------------|------------------------|
| Application | recessed |
| Dimensions | cut out: ø107mm h110mm |
| IP rating | IP20 |
| Power | 500mA |
| Lifetime L70/F10/65°C | >60000h |
| MacAdam ellipse | 3 |
| Guarantee | 5 year |

(*on components, only if ordered luminaire + driver)



| Color Temperature | Wattage | Forward Current | Lumen (LED) (at tp = 65°C) | Lumen/Watt (LED) (at tp = 65°C) | CRI | Energy Label |
|-------------------|---------|-----------------|----------------------------|---------------------------------|-----|--------------|
| 2700K | 16,9W | 500mA | 2225 lm | 134 lm/W | 90+ | E |
| 3000K | 16,9W | 500mA | 2449 lm | 147 lm/W | 90+ | E |
| 3500K | 16,9W | 500mA | 2474 lm | 149 lm/W | 90+ | E |
| 4000K | 16,9W | 500mA | 2536 lm | 152 lm/W | 90+ | E |

ORDER REFERENCE

> LUMINAIRE

! ORDER REFERENCE + (1) **W** (white) / **B** (black)
+ (2) **G** (gold reflector) option only for 2700K or 3000K

2700K

| | | |
|-----|---------------|---|
| 25° | ZUMI262131507 | Cannon Mini Select SLE G7 2225lm 500mA 16,9W 2700K CRI90 25° glas-excl.driver |
| 39° | ZUMI262131607 | Cannon Mini Select SLE G7 2225lm 500mA 16,9W 2700K CRI90 39° glas-excl.driver |
| 61° | ZUMI262131707 | Cannon Mini Select SLE G7 2225lm 500mA 16,9W 2700K CRI90 61° glas-excl.driver |

3000K

| | | |
|-----|---------------|---|
| 25° | ZUMI262141507 | Cannon Mini Select SLE G7 2449lm 500mA 16,9W 3000K CRI90 25° glas-excl.driver |
| 39° | ZUMI262141607 | Cannon Mini Select SLE G7 2449lm 500mA 16,9W 3000K CRI90 39° glas-excl.driver |
| 61° | ZUMI262141707 | Cannon Mini Select SLE G7 2449lm 500mA 16,9W 3000K CRI90 61° glas-excl.driver |

3500K

| | | |
|-----|---------------|---|
| 25° | ZUMI262151507 | Cannon Mini Select SLE G7 2474lm 500mA 16,9W 3500K CRI90 25° glas-excl.driver |
| 39° | ZUMI262151607 | Cannon Mini Select SLE G7 2474lm 500mA 16,9W 3500K CRI90 39° glas-excl.driver |
| 61° | ZUMI262151707 | Cannon Mini Select SLE G7 2474lm 500mA 16,9W 3500K CRI90 61° glas-excl.driver |

4000K

| | | |
|-----|---------------|---|
| 25° | ZUMI262161507 | Cannon Mini Select SLE G7 2536lm 500mA 16,9W 4000K CRI90 25° glas-excl.driver |
| 39° | ZUMI262161607 | Cannon Mini Select SLE G7 2536lm 500mA 16,9W 4000K CRI90 39° glas-excl.driver |
| 61° | ZUMI262161707 | Cannon Mini Select SLE G7 2536lm 500mA 16,9W 4000K CRI90 61° glas-excl.driver |

> DRIVER

dimmable

| | |
|-----------------------------|---|
| TRID28000671 + TRID28001114 | LCA 25W 350-1050mA one4all SR PRE + PLUG 500mA (DALI, DSI, switchDIM) |
|-----------------------------|---|

non dimmable

| | |
|-----------------------------|---|
| TRID28000700 + TRID28001114 | LC 25W 350-1050mA flexC SR EXC + PLUG 500mA |
|-----------------------------|---|

> OPTIONS

PC-cover

| | |
|----------------|--------------------------------------|
| ZUMI2600000500 | PC-cover for food environment - Ø 71 |
|----------------|--------------------------------------|

Flat Springs

| | |
|--------|--------------|
| ZUMIFS | Flat Springs |
|--------|--------------|

Emergency kit

On request


PRODUCT DESCRIPTION

The mini version of the cannon, equipped with a LEDmodule especially to enlighten several food products. There's a choice between 'fish' to light up fish products, 'gold' for bakery goods and 'gold+' for rather crusty bakery goods such as croissants and baguettes.

The 'meat+' provides a highly red color which is ideal for the presentation of meat. Its 'fresh meat' is suitable to use for meat in the counter. Fruit is ideal for fruit and vegetables.

Aluminium luminaire, white or black powder coated, available in several color temperatures, with several possible reflectors (25°, 39°, 61°).

Standard equipped with PC-cover for food environment and torsion springs.



TECHNICAL DATA

| | |
|-----------------------|--------------------------|
| Application | recessed |
| Dimensions | cut out: Ø107mm h110mm |
| IP rating | IP20 |
| Power | 500mA |
| Lifetime L70/F10/65°C | >60000h |
| MacAdam ellipse | 3 (GOLD / FRESH MEAT: 4) |
| Guarantee | 5 year |

(*on components, only if ordered luminaire + driver)

| Color Temperature | Wattage | Forward Current | Lumen (LED) (at tp = 65°C) | Lumen/Watt (LED) (at tp = 65°C) | CRI | Energy Label |
|-------------------|---------|-----------------|----------------------------|---------------------------------|-----|--------------|
| FISH | 16,9W | 500mA | 2015 lm | 121 lm/W | / | E |
| GOLD 2700K | 16,9W | 500mA | 1868 lm | 112 lm/W | / | E |
| GOLD+ 2400K | 16,9W | 500mA | 1171 lm | 70 lm/W | / | G |
| MEAT+ | 16,9W | 500mA | 1256 lm | 75 lm/W | / | n.a |
| FRESH MEAT | 16,9W | 500mA | 1224 lm | 74 lm/W | / | n.a |
| FRUIT | 16,9W | 500mA | 1748 lm | 108 lm/W | / | F |

ORDER REFERENCE

> LUMINAIRE

! ORDER REFERENCE + (1) **W** (white) / **B** (black)
 (2) **G** (gold reflector) option only for GOLD and GOLD+

FISH

| | | |
|-----|---------------|---|
| 25° | ZUMI262171907 | Cannon Mini FISH SLE G7 2015lm 500mA 16,9W 25° PC-excl.driver |
| 39° | ZUMI262172007 | Cannon Mini FISH SLE G7 2015lm 500mA 16,9W 39° PC-excl.driver |
| 61° | ZUMI262172107 | Cannon Mini FISH SLE G7 2015lm 500mA 16,9W 61° PC-excl.driver |

GOLD 2700K

| | | |
|-----|---------------|---|
| 25° | ZUMI262181907 | Cannon Mini Gold SLE G7 1868lm 500mA 16,9W 2700K 25° PC-excl.driver |
| 39° | ZUMI262182007 | Cannon Mini Gold SLE G7 1868lm 500mA 16,9W 2700K 39° PC-excl.driver |
| 61° | ZUMI262182107 | Cannon Mini Gold SLE G7 1868lm 500mA 16,9W 2700K 61° PC-excl.driver |

GOLD+ 2400K

| | | |
|-----|---------------|--|
| 25° | ZUMI262081907 | Cannon Mini Gold+ SLE G7 1171lm 500mA 16,9W 2400K 25° PC-excl.driver |
| 39° | ZUMI262082007 | Cannon Mini Gold+ SLE G7 1171lm 500mA 16,9W 2400K 39° PC-excl.driver |
| 61° | ZUMI262082107 | Cannon Mini Gold+ SLE G7 1171lm 500mA 16,9W 2400K 61° PC-excl.driver |

MEAT+

| | | |
|-----|---------------|--|
| 25° | ZUMI262191907 | Cannon Mini Meat+ SLE G7 1256lm 500mA 16,9W 25° PC-excl.driver |
| 39° | ZUMI262192007 | Cannon Mini Meat+ SLE G7 1256lm 500mA 16,9W 39° PC-excl.driver |
| 61° | ZUMI262192107 | Cannon Mini Meat+ SLE G7 1256lm 500mA 16,9W 61° PC-excl.driver |

FRESH MEAT

| | | | |
|-----|---------------|--|--------------------|
| 25° | ZUMI262201907 | Cannon Mini Fresh meat SLE G7 1224lm 500mA 16,9W | 25° PC-excl.driver |
| 39° | ZUMI262202007 | Cannon Mini Fresh meat SLE G7 1224lm 500mA 16,9W | 39° PC-excl.driver |
| 61° | ZUMI262202107 | Cannon Mini Fresh meat SLE G7 1224lm 500mA 16,9W | 61° PC-excl.driver |

FRUIT

| | | | |
|-----|---------------|--|--------------------|
| 25° | ZUMI262211907 | Cannon Mini Fruit SLE G7 17mm 1748lm 500mA 16,9W | 25° PC-excl.driver |
| 39° | ZUMI262212007 | Cannon Mini Fruit SLE G7 17mm 1748lm 500mA 16,9W | 39° PC-excl.driver |
| 61° | ZUMI262212107 | Cannon Mini Fruit SLE G7 17mm 1748lm 500mA 16,9W | 61° PC-excl.driver |

> DRIVER**dimmable**

TRID28000671 + TRID28001114 LCA 25W 350-1050mA one4all SR PRE + PLUG 500mA (DALI, DSI, switchDIM)

non dimmable

TRID28000700 + TRID28001114 LC 25W 350-1050mA flexC SR EXC + PLUG 500mA

> OPTIONS**Flat Springs**

ZUMIFS Flat Springs

Emergency kit

On request

PRODUCT DESCRIPTION

The mini version of the cannon, a recessed downlighter for general or accent lighting. The art version is with its CRI 97 the perfect solution to enlighten art and musea.

Aluminium luminaire, white or black powder coated, available in several color temperatures, with several possible reflectors (25°, 39°, 61°).


Standard equipped with torsion springs.



TECHNICAL DATA

| | |
|-----------------------|------------------------|
| Application | recessed |
| Dimensions | cut out: ø107mm h110mm |
| IP rating | IP20 |
| Power | 500mA |
| Lifetime L70/F10/65°C | >60000h |
| MacAdam ellipse | 2 |
| Guarantee | 5 year |

(*on components, only if ordered luminaire + driver)



| Color Temperature | Wattage | Forward Current | Lumen (LED) (at tp = 65°C) | Lumen/Watt (LED) (at tp = 65°C) | CRI | Energy Label |
|-------------------|---------|-----------------|----------------------------|---------------------------------|-----|--------------|
| 3100K | 16,9W | 500mA | 1729 lm | 104 lm/W | 97 | F |

ORDER REFERENCE

> [LUMINAIRE](#)

! ORDER REFERENCE + (1) **W** (white) / **B** (black)
+ (2) **G** (gold reflector)

3100K

| | | |
|-----|---------------|--|
| 25° | ZUMI262221507 | Cannon Mini Art SLE G7 1729lm 500mA 16,9W 3100K CRI97 25° glas-excl.driver |
| 39° | ZUMI262221607 | Cannon Mini Art SLE G7 1729lm 500mA 16,9W 3100K CRI97 39° glas-excl.driver |
| 61° | ZUMI262221707 | Cannon Mini Art SLE G7 1729lm 500mA 16,9W 3100K CRI97 61° glas-excl.driver |

> [DRIVER](#)

dimmable

TRID28000671 + TRID28001114 LCA 25W 350-1050mA one4all SR PRE + PLUG 500mA (DALI, DSI, switchDIM)

non dimmable

TRID28000700 + TRID28001114 LC 25W 350-1050mA flexC SR EXC + PLUG 500mA

> [OPTIONS](#)

PC-cover

ZUMI2600000500 PC-cover for food environment - ø 71

Flat Springs

ZUMIFS Flat Springs

Emergency kit

On request

PRODUCT DESCRIPTION

The mini version of the cannon, a recessed downlighter for general or accent lighting. The fashion version has an optimized light spectrum with warm, lively colours combined with a pure, shiny white, which is ideal for the perfect fashion presentation.

Aluminium luminaire, white or black powder coated, available in several color temperatures, with several possible reflectors (25°, 39°, 61°).


Standard equipped with torsion springs.



TECHNICAL DATA

| | |
|-----------------------|------------------------|
| Application | recessed |
| Dimensions | cut out: Ø107mm h110mm |
| IP rating | IP20 |
| Power | 500mA |
| Lifetime L70/F10/65°C | >60000h |
| MacAdam ellipse | 3 |
| Guarantee | 5 year |

(*on components, only if ordered luminaire + driver)



| Color Temperature | Wattage | Forward Current | Lumen (LED) (at tp = 65°C) | Lumen/Watt (LED) (at tp = 65°C) | CRI | Energy Label |
|-------------------|---------|-----------------|----------------------------|---------------------------------|-----|--------------|
| 3250K | 16,9W | 500mA | 1876 lm | 113 lm/W | 95 | F |

ORDER REFERENCE

> LUMINAIRE

! ORDER REFERENCE + (1) **W** (white) / **B** (black)
+ (2) **G** (gold reflector)

3250K

| | | |
|------------|---------------|---|
| 25° | ZUMI262231507 | Cannon Mini Fashion SLE G7 1876lm 500mA 16,9W 3250K CRI90+ 25° glas-excl.driver |
| 39° | ZUMI262231607 | Cannon Mini Fashion SLE G7 1876lm 500mA 16,9W 3250K CRI90+ 39° glas-excl.driver |
| 61° | ZUMI262231707 | Cannon Mini Fashion SLE G7 1876lm 500mA 16,9W 3250K CRI90+ 61° glas-excl.driver |

> DRIVER

dimnable

TRID28000671 + TRID28001114 LCA 25W 350-1050mA one4all SR PRE + PLUG 500mA (DALI, DSI, switchDIM)

non dimnable

TRID28000700 + TRID28001114 LC 25W 350-1050mA flexC SR EXC + PLUG 500mA

> OPTIONS

| | | |
|----------------------|----------------|--------------------------------------|
| PC-cover | ZUMI2600000500 | PC-cover for food environment - Ø 71 |
| Flat Springs | ZUMIFS | Flat Springs |
| Emergency kit | On request | |

PRODUCT DESCRIPTION

The mini version of the cannon, a recessed downlighter for general or accent lighting. The tunable white version has a color temperature range from 2700K up to 6500K. Aluminium luminaire, white or black powder coated, with several possible reflectors (26°, 42°).


Standard equipped with torsion springs.



TECHNICAL DATA

| | |
|-----------------------|------------------------|
| Application | ceiling - recessed |
| Dimensions | cut out: Ø107mm h110mm |
| IP rating | IP20 |
| Power | 850mA |
| Lifetime L70/B10/65°C | 60000h |
| MacAdam ellipse | 3 |
| Guarantee | 5 year |

(*on components, only if ordered luminaire + driver)



| Color Temperature | Wattage | Forward Current | Lumen (LED) (at tp = 65°C) | Lumen/Watt (LED) (at tp = 65°C) | CRI | Energy Label |
|-------------------|---------|-----------------|----------------------------|---------------------------------|-----|--------------|
| WW | 27,6W | 850mA | 2812 lm | 102 lm/W | 90 | F |
| CW | 27,6W | 850mA | 2776 lm | 101lm/W | 90 | F |

ORDER REFERENCE

> LUMINAIRE

! ORDER REFERENCE + W (white) / B (black)

| | | |
|------------|---------------|---|
| TW | | |
| 26° | ZUMI012780325 | Cannon TW SLE3000 PRE2 2812/2776lm 27,6W 2700-6500K CRI90+ 26° glass excl. driver |
| 42° | ZUMI012780425 | Cannon TW SLE3000 PRE2 2812/2776lm 27,6W 2700-6500K CRI90+ 42° glass excl. driver |

> DRIVER - REQUIRED!

dimmable DALI DT8 (only Device Type 8), switchDIM

| | |
|--------------|---|
| TRID28002202 | LCA 38W 350-1050mA DT8 SR PRE |
| TRID28001121 | I-SELECT 2 PLUG 850MA BL (DALI DT8 (only Device Type 8), switchDIM) +colourswitch by push button |

Control via switchDIM:

A driverentional double pushbutton switch can be used for control via switchDIM. One of the pushbuttons is used to set the colour temperature, the other to set the dimming level.

For control via a switchDIM switch different settings can be made:

- Setting for the colour temperature via colourTEMPERATURE mode or colourSWITCH mode with 8 predefined values 2,700 K and 6,500 K.
- Stepless setting for the dimming level between 15 and 100 %.

> OPTIONS

PC-cover

| | |
|------------------|-------------------------------------|
| ZUMI010000000500 | PC-cover for food environment Ø 111 |
|------------------|-------------------------------------|

Flat Springs

| | |
|--------|--------------|
| ZUMIFS | Flat Springs |
|--------|--------------|