

PRODUCT DESCRIPTION

Recessed downlighter for general or accent lighting with a CRI of 90+ for a better color accuracy.

Aluminium luminaire, white or black powder coated, with several possible reflectors (16°, 26°, 42°)
Available in two different versions: the high efficiency (700mA) or the high output (1700mA) version.


Standard equipped with torsion springs.



TECHNICAL DATA

Application	recessed
Dimensions	cut out: Ø150mm h170mm
IP rating	IP20
Power	700mA / 1700mA
Lifetime L70/F10/65°C	>55000h
MacAdam ellipse	3
Guarantee	5 year

(*on components, only if ordered luminaire + driver)



Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2700K	23,6W	700mA	3125 lm	134 lm/W	90+	E
	61,3W	1700mA	6871 lm	112 lm/W	90+	E
3000K	23,6W	700mA	3441 lm	147 lm/W	90+	E
	61,3W	1700mA	7548lm	123 lm/W	90+	E
4000K	23,6W	700mA	3596 lm	154 lm/W	90+	E
	61,3W	1700mA	7898 lm	129 lm/W	90+	E

ORDER REFERENCE

> LUMINAIRE

! ORDER REFERENCE + (1) **W** (white) / **B** (black)
+ (2) **G** (gold reflector) option only for 2700K or 3000K

2700K

HE 700mA

16°	ZUMI011960208	Cannon Select SLE G7 HE 3125lm 700mA 23,6W 2700K CRI90 16° glas-excl.driver
26°	ZUMI011960308	Cannon Select SLE G7 HE 3125lm 700mA 23,6W 2700K CRI90 26° glas-excl.driver
42°	ZUMI011960408	Cannon Select SLE G7 HE 3125lm 700mA 23,6W 2700K CRI90 42° glas-excl.driver

HO 1700mA

16°	ZUMI011960210	Cannon Select SLE G7 HO 6871lm 1700mA 61,3W 2700K CRI90 16° glas-excl.driver
26°	ZUMI011960310	Cannon Select SLE G7 HO 6871lm 1700mA 61,3W 2700K CRI90 26° glass excl. driver
42°	ZUMI011960410	Cannon Select SLE G7 HO 6871lm 1700mA 61,3W 2700K CRI90 42° glass excl. driver

3000K

HE 700mA

16°	ZUMI011970208	Cannon Select SLE G7 HE 3441lm 700mA 23,6W 3000K CRI90 16° glas-excl.driver
26°	ZUMI011970308	Cannon Select SLE G7 HE 3441lm 700mA 23,6W 3000K CRI90 26° glas-excl.driver
42°	ZUMI011970408	Cannon Select SLE G7 HE 3441lm 700mA 23,6W 3000K CRI90 42° glas-excl.driver

HO 1700mA

16°	ZUMI011970210	Cannon Select SLE G7 HO 7548lm 1700mA 61,3W 3000K CRI90 16° glas-excl.driver
26°	ZUMI011970310	Cannon Select SLE G7 HO 7548lm 1700mA 61,3W 3000K CRI90 26° glas-excl.driver .
42°	ZUMI011970410	Cannon Select SLE G7 HO 7548lm 1700mA 61,3W 3000K CRI90 42° glas-excl.driver

4000K*HE 700mA*

16°	ZUMI011990208	Cannon Select SLE G7 HE 3596lm 700mA 23,6W 4000K CRI90 16° glas-excl.driver
26°	ZUMI011990308	Cannon Select SLE G7 HE 3596lm 700mA 23,6W 4000K CRI90 26° glas-excl.driver
42°	ZUMI011990408	Cannon Select SLE G7 HE 3596lm 700mA 23,6W 4000K CRI90 42° glas-excl.driver

HO 1700mA

16°	ZUMI011990210	Cannon Select SLE G7 HO 7898lm 1700mA 61,3W 4000K CRI90 16° glas-excl.driver
26°	ZUMI011990310	Cannon Select SLE G7 HO 7898lm 1700mA 61,3W 4000K CRI90 26° glas-excl.driver
42°	ZUMI011990410	Cannon Select SLE G7 HO 7898lm 1700mA 61,3W 4000K CRI90 42° glas-excl.driver

> DRIVER*HE 700mA***dimmable (DALI, switchDIM)**

TRID28000671 + TRID28001118 LCA 25W 350–1050mA one4all SR PRE + PLUG 700mA

non dimmable

TRID28000700 + TRID28001118 LC 25W 350–1050mA flexC SR EXC + PLUG 700mA

*HO 1700mA***dimmable (DALI, switchDIM)**

TRID28001571 + TRID28001135 LCA 100W 1100-2100mA one4all SR PRE + PLUG 1700mA

non dimmable

TRID28001573 + TRID28001135 LC 100W 1100-2100mA flexC SR EXC + PLUG 1700mA

> OPTIONS**PC-cover**

ZUMI010000000500 PC-cover for food environment Ø 111

Flat Springs

ZUMIFS Flat Springs

Emergency kit

On request


PRODUCT DESCRIPTION

Recessed downlighter equipped with a LEDmodule especially to enlighten several food products. There's a choice between 'fish' to light up fish products, 'gold' for bakery goods and 'gold+' for rather crusty bakery goods such as croissants and baguettes.

The cannon 'meat+' provides a highly red color which is ideal for the presentation of meat. Its 'fresh meat' is suitable to use for meat in the counter. Fruit is ideal for fruit and vegetables.

Aluminium luminaire, white or black powder coated, with several possible reflectors (16°, 26°, 42°)
Available in two different versions, the high efficiency (700mA) or the high output (1700mA) version.

Standard equipped with PC-cover for food environment and torsion springs.

**TECHNICAL DATA**

Application	recessed
Dimensions	cut out: ø150mm h170mm
IP rating	IP20
Power	700mA / 1700mA
Lifetime L70/F10/65°C	>55000h
MacAdam ellipse	3
Guarantee	5 year

(*on components, only if ordered luminaire + driver)

Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
FISH	23,6W	700mA	2847 lm	122 lm/W	/	E
	61,3W	1700mA	6362 lm	104lm/W	/	E
GOLD 2700K	23,6W	700mA	2671 lm	115 lm/W	/	E
	61,3W	1700mA	5970 lm	98 lm/W	/	E
GOLD+ 2400K	23,6W	700mA	1653 lm	71 lm/W	/	F
	61,3W	1700mA	3691 lm	61 lm/W	/	F
MEAT+	23,6W	700mA	1753 lm	76 lm/W	/	n.a
	61,3W	1700mA	3922 lm	64/W	/	n.a
FRESH MEAT	23,6W	700mA	1749 lm	75 lm/W	/	n.a
	61,3W	1700mA	3910 lm	64 lm/W	/	n.a
FRUIT	23,6W	700mA	2451 lm	106 lm/W	/	F
	61,3W	1700mA	5478 lm	90 lm/W	/	F

ORDER REFERENCE

> [LUMINAIRE](#)

! ORDER REFERENCE + (1) W (white) / B (black)

(2) **G** (gold reflector) option only for GOLD and GOLD+

FISH

HE 700mA

16°	ZUMI012000508	Cannon Fish SLE G7 HE 2847lm 700mA 23,6W 16° PC excl.driver
26°	ZUMI012000608	Cannon Fish SLE G7 HE 2847lm 700mA 23,6W 26° PC excl.driver
42°	ZUMI012000708	Cannon Fish SLE G7 HE 2847lm 700mA 23,6W 42° PC excl.driver

HO 1700mA

16°	ZUMI012000510	Cannon Fish SLE G7 HO 6362lm 1700mA 61,3W 16° PC excl.driver
26°	ZUMI012000610	Cannon Fish SLE G7 HO 6362lm 1700mA 61,3W 26° PC excl.driver
42°	ZUMI012000710	Cannon Fish SLE G7 HO 6362lm 1700mA 61,3W 42° PC excl.driver

GOLD 2700K

HE 700mA

16°	ZUMI012010508	Cannon Gold SLE G7 HE 2671lm 700mA 23,6W 2700K CRI90+ 16° PC excl.driver
26°	ZUMI012010608	Cannon Gold SLE G7 HE 2671lm 700mA 23,6W 2700K CRI90+ 26° PC excl.driver
42°	ZUMI012010708	Cannon Gold SLE G7 HE 2671lm 700mA 23,6W 2700K CRI90+ 42° PC excl.driver

HO 1700mA

16°	ZUMI012010510	Cannon Gold SLE G7 HO 5970lm 1700mA 61,3W 2700K CRI90+ 16° PC excl.driver
26°	ZUMI012010610	Cannon Gold SLE G7 HO 5970lm 1700mA 61,3W 2700K CRI90+ 26° PC excl.driver
42°	ZUMI012010710	Cannon Gold SLE G7 HO 5970lm 1700mA 61,3W 2700K CRI90+ 42° PC excl.driver

GOLD+ 2400K*HE 700mA*

16°	ZUMI011910508	Cannon Gold+ SLE G7 HE 1653lm 700mA 23,6W 2400K CRI90+ 16° PC excl.driver
26°	ZUMI011910608	Cannon Gold+ SLE G7 HE 1653lm 700mA 23,6W 2400K CRI90+ 26° PC excl.driver
42°	ZUMI011910708	Cannon Gold+ SLE G7 HE 1653lm 700mA 23,6W 2400K CRI90+ 42° PC excl.driver

HO 1700mA

16°	ZUMI011910510	Cannon Gold+ SLE G7 HO 3691lm 1700mA 61,3W 2400K CRI90+ 16° PC excl.driver
26°	ZUMI011910610	Cannon Gold+ SLE G7 HO 3691lm 1700mA 61,3W 2400K CRI90+ 26° PC excl.driver
42°	ZUMI011910710	Cannon Gold+ SLE G7 HO 3691lm 1700mA 61,3W 2400K CRI90+ 42° PC excl.driver

MEAT+*HE 700mA*

16°	ZUMI012020508	Cannon Meat+ SLE G7 HE 1753lm 700mA 23,6W 16° PC excl.driver
26°	ZUMI012020608	Cannon Meat+ SLE G7 HE 1753lm 700mA 23,6W 26° PC excl.driver
42°	ZUMI012020708	Cannon Meat+ SLE G7 HE 1753lm 700mA 23,6W 42° PC excl.driver

HO 1700mA

16°	ZUMI012020510	Cannon Meat+ SLE G7 HO 3922lm 1700mA 61,3W 16° PC excl.driver
26°	ZUMI012020610	Cannon Meat+ SLE G7 HO 3922lm 1700mA 61,3W 26° PC excl.driver
42°	ZUMI012020710	Cannon Meat+ SLE G7 HO 3922lm 1700mA 61,3W 42° PC excl.driver

FRESH MEAT*HE 700mA*

16°	ZUMI012030508	Cannon Fresh Meat SLE G7 HE 1749lm 700mA 23,6W 16° PC excl.driver
26°	ZUMI012030608	Cannon Fresh Meat SLE G7 HE 1749lm 700mA 23,6W 26° PC excl.driver
42°	ZUMI012030708	Cannon Fresh Meat SLE G7 HE 1749lm 700mA 23,6W 42° PC excl.driver

HO 1700mA

16°	ZUMI012030510	Cannon Fresh Meat SLE G7 HO 3910lm 1700mA 61,3W 16° PC excl.driver
26°	ZUMI012030610	Cannon Fresh Meat SLE G7 HO 3910lm 1700mA 61,3W 26° PC excl.driver
42°	ZUMI012030710	Cannon Fresh Meat SLE G7 HO 3910lm 1700mA 61,3W 42° PC excl.driver

FRUIT*HE 700mA*

16°	ZUMI012040508	Cannon Fruit SLE G7 HE 2451lm 700mA 23,6W 16° PC excl.driver
26°	ZUMI012040608	Cannon Fruit SLE G7 HE 2451lm 700mA 23,6W 26° PC excl.driver
42°	ZUMI012040708	Cannon Fruit SLE G7 HE 2451lm 700mA 23,6W 42° PC excl.driver

HO 1700mA

16°	ZUMI012040510	Cannon Fruit SLE G7 HO 5478lm 1700mA 61,3W 16° PC excl.driver
26°	ZUMI012040610	Cannon Fruit SLE G7 HO 5478lm 1700mA 61,3W 26° PC excl.driver
42°	ZUMI012040710	Cannon Fruit SLE G7 HO 5478lm 1700mA 61,3W 42° PC excl.driver

> DRIVER*HE 700mA***dimmable (DALI, switchDIM)**

TRID28000671 + TRID28001118 LCA 25W 350–1050mA one4all SR PRE + PLUG 700mA

non dimmable

TRID28000700 + TRID28001118 LC 25W 350–1050mA flexC SR EXC + PLUG 700mA

*HO 1700mA***dimmable (DALI, switchDIM)**

TRID28001571 + TRID28001135 LCA 100W 1100-2100mA one4all SR PRE + PLUG 1700mA

non dimmable

TRID28001573 + TRID28001135 LC 100W 1100-2100mA flexC SR EXC + PLUG 1700mA

> OPTIONS

Flat Springs	ZUMIFS	Flat Springs
Emergency kit	On request	

PRODUCT DESCRIPTION

Recessed downlighter for general or accent lighting. The art version is with its CRI 98 the perfect solution to enlighten art and musea.

Aluminium luminaire, white or black powder coated, with several possible reflectors (16°, 26°, 42°) Available in two different versions: the high efficiency (700mA) or the high output (1700mA) version.


Standard equipped with torsion springs.



TECHNICAL DATA

Application	recessed
Dimensions	cut out: ø150mm h170mm
IP rating	IP20
Power	700mA / 1700mA
Lifetime L70/F10/65°C	>55000h
MacAdam ellipse	2
Guarantee	5 year

(*on components, only if ordered luminaire + driver)



Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
3100K	23,6W	700mA	2420 lm	104 lm/W	97	F
	61,3W	1700mA	5400 lm	89 lm/W	97	F

ORDER REFERENCE

> LUMINAIRE

! ORDER REFERENCE + W (white) / B (black)

3100K

HE 700mA

16°	ZUMI012050208	Cannon Art SLE G7 HE 2420lm 700mA 23,6W 3100K CRI97 16° glas-excl.driver
26°	ZUMI012050308	Cannon Art SLE G7 HE 2420lm 700mA 23,6W 3100K CRI97 26° glas-excl.driver
42°	ZUMI012050408	Cannon Art SLE G7 HE 2420lm 700mA 23,6W 3100K CRI97 42° glas-excl.driver

HO 1700mA

16°	ZUMI012050210	Cannon Art SLE G7 HO 5400lm 1700mA 61,3W 3100K CRI97 16° glas-excl.driver
26°	ZUMI012050310	Cannon Art SLE G7 HO 5400lm 1700mA 61,3W 3100K CRI97 26° glas-excl.driver
42°	ZUMI012050410	Cannon Art SLE G7 HO 5400lm 1700mA 61,3W 3100K CRI97 42° glas-excl.driver

> DRIVER

HE 700mA

dimmable (DALI, switchDIM)

TRID28000671 + TRID28001118	LCA 25W 350–1050mA one4all SR PRE + PLUG 700mA
-----------------------------	--

non dimmable

TRID28000700 + TRID28001118	LC 25W 350–1050mA flexC SR EXC + PLUG 700mA
-----------------------------	---

HO 1700mA

dimmable (DALI, switchDIM)

TRID28001571 + TRID28001135	LCA 100W 1100-2100mA one4all SR PRE + PLUG 1700mA
-----------------------------	---

non dimmable

TRID28001573 + TRID28001135	LC 100W 1100-2100mA flexC SR EXC + PLUG 1700mA
-----------------------------	--

> OPTIONS

PC-cover	ZUMI010000000500	PC-cover for food environment Ø 111
Flat Springs	ZUMIFS	Flat Springs
Emergency kit	On request	

PRODUCT DESCRIPTION

Recessed downlighter for general or accent lighting. The fashion version has an optimized light spectrum with warm, lively colours combined with a pure, shiny white, which is ideal for the perfect fashion presentation.


Aluminium luminaire, white or black powder coated, with several possible reflectors (16°, 26°, 42°)
Available in two different versions: the high efficiency (700mA) or the high output (1700mA) version.

Standard equipped with torsion springs.

**TECHNICAL DATA**

Application	recessed
Dimensions	cut out: Ø150mm h170mm
IP rating	IP20
Power	700mA / 1700mA
Lifetime L70/F10/65°C	>55000h
MacAdam ellipse	3
Guarantee	5 year

(*on components, only if ordered luminaire + **driver**)



Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
3250K	23,6W	700mA	2656 lm	114 lm/W	95	F
	61,3W	1700mA	5936 lm	98 lm/W	95	F

ORDER REFERENCE

> [LUMINAIRE](#)

! ORDER REFERENCE + W (white) / B (black)

3250K

HE 700mA

16°	ZUMI012060208	Cannon Fashion SLE G7 HE 2656lm 700mA 23,6W 3250K CRI95 16° glas-excl.driver
26°	ZUMI012060308	Cannon Fashion SLE G7 HE 2656lm 700mA 23,6W 3250K CRI95 26° glas-excl.driver
42°	ZUMI012060408	Cannon Fashion SLE G7 HE 2656lm 700mA 23,6W 3250K CRI95 42° glas-excl.driver

HO 1700mA

16°	ZUMI012060210	Cannon Fashion SLE G7 HO 5936lm 1700mA 61,3W 3250K CRI95 16° glas-excl.driver
26°	ZUMI012060310	Cannon Fashion SLE G7 HO 5936lm 1700mA 61,3W 3250K CRI95 26° glas-excl.driver
42°	ZUMI012060410	Cannon Fashion SLE G7 HO 5936lm 1700mA 61,3W 3250K CRI95 42° glas-excl.driver

> [DRIVER](#)

HE 700mA

dimnable (DALI, switchDIM)

TRID28000671 + TRID28001118 LCA 25W 350–1050mA one4all SR PRE + PLUG 700mA

non dimmable

TRID28000700 + TRID28001118 LC 25W 350–1050mA flexC SR EXC + PLUG 700mA

HO 1700mA

dimnable (DALI, switchDIM)

TRID28001571 + TRID28001135 LCA 100W 1100–2100mA one4all SR PRE + PLUG 1700mA

non dimmable

TRID28001573 + TRID28001135 LC 100W 1100–2100mA flexC SR EXC + PLUG 1700mA

> [OPTIONS](#)

PC-cover	ZUMI010000000500	PC-cover for food environment Ø 111
Flat Springs	ZUMIFS	Flat Springs
Emergency kit	On request	

PRODUCT DESCRIPTION

Recessed downlighter for general or accent lighting.
Aluminium luminaire, white or black powder coated, with several possible reflectors (16°, 26°, 42°).

The PI-LED-version makes it possible to change color from 1800K to 16000K but also to create all additional RGB-colors. This way any atmosphere can be created. Available in 3 different versions: the low output (375mA) or the high output (500mA) and super high output (750mA) version.


Standard equipped with torsion springs.



TECHNICAL DATA

Application	recessed
Dimensions	cut out: Ø150mm h170mm
IP rating	IP20
Power	48V DC
Lifetime L70/F10/65°C	50000h
MacAdam ellipse	3
Guarantee	5 year

(*on components, only if ordered luminaire + driver)



Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
1800K-16000K RGB LO	22W	375mA	2300 lm	105 lm/W	90+	F
1800K-16000K RGB HO	31W	500mA	3000 lm	97 lm/W	90+	F
1800K-16000K RGB SHO	50W	750mA	4000 lm	80 lm/W	90+	F

ORDER REFERENCE

> LUMINAIRE

! ORDER REFERENCE + W (white) / B (black)

LO 22W

16°	ZUMI011310206	Cannon PI-LED LO 22W 48V DC 2300 lm CRI90+ 16° glass excl. driver dim DALI (Only DT8)
26°	ZUMI011310306	Cannon PI-LED LO 22W 48V DC 2300 lm CRI90+ 26° glass excl. driver dim DALI (Only DT8)
42°	ZUMI011310406	Cannon PI-LED LO 22W 48V DC 2300 lm CRI90+ 42° glass excl. driver dim DALI (Only DT8)

HO 31W

16°	ZUMI011330207	Cannon PI-LED HO 31W 48V DC 3000 lm CRI90+ 16° glass excl. driver dim DALI (Only DT8)
26°	ZUMI011330307	Cannon PI-LED HO 31W 48V DC 3000 lm CRI90+ 26° glass excl. driver dim DALI (Only DT8)
42°	ZUMI011330407	Cannon PI-LED HO 31W 48V DC 3000 lm CRI90+ 42° glass excl. driver dim DALI (Only DT8)

SHO 50W

16°	ZUMI012770224	Cannon PI-LED SHO 50W 48V DC 4000 lm CRI90+ 16° glass excl. driver dim DALI (Only DT8)
26°	ZUMI012770324	Cannon PI-LED SHO 50W 48V DC 4000 lm CRI90+ 26° glass excl. driver dim DALI (Only DT8)
42°	ZUMI012770424	Cannon PI-LED SHO 50W 48V DC 4000 lm CRI90+ 42° glass excl. driver dim DALI (Only DT8)

> DRIVER - REQUIRED!

375/500mA - 48V	LUMILTP1067	LED Driver for PI-LED Systems 60W/48V
------------------------	-------------	---------------------------------------

> OPTIONS

PC-cover	ZUMI01000000500	PC-cover for food environment Ø 111
-----------------	-----------------	-------------------------------------

Flat Springs	ZUMIFS	Flat Springs
---------------------	--------	--------------

PRODUCT DESCRIPTION

Recessed downlighter for general or accent lighting. The tunable white version has a color temperature range from 2700K up to 6500K.
Aluminium luminaire, white or black powder coated, with several possible reflectors (26°, 42°).


Standard equipped with torsion springs.



TECHNICAL DATA

Application	ceiling - recessed
Dimensions	cut out: Ø150mm h170mm
IP rating	IP20
Power	850mA
Lifetime L70/B10/65°C	60000h
MacAdam ellipse	3
Guarantee	5 year

(*on components, only if ordered luminaire + **driver**)



Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
WW	27,6W	850mA	2812 lm	102 lm/W	90	F
CW	27,6W	850mA	2776 lm	101lm/W	90	F

ORDER REFERENCE

> [LUMINAIRE](#)

! ORDER REFERENCE + W (white) / B (black)

TW

26°	ZUMI012780325	Cannon TW SLE3000 PRE2 2812/2776lm 27,6W 2700-6500K CRI90+ 26° glass excl. driver
42°	ZUMI012780425	Cannon TW SLE3000 PRE2 2812/2776lm 27,6W 2700-6500K CRI90+ 42° glass excl. driver

> [DRIVER - REQUIRED!](#)

dimnable DALI DT8 (only Device Type 8), switchDIM
 TRID28002202 LCA 38W 350-1050mA DT8 SR PRE
 TRID28001121 I-SELECT 2 PLUG 850MA BL
 (DALI DT8 (only Device Type 8), switchDIM) +colourswitch by push button

Control via switchDIM:

A driverentional double pushbutton switch can be used for control via switchDIM.
One of the pushbuttons is used to set the colour temperature, the other to set the dimming level.

For control via a switchDIM switch different settings can be made:

- Setting for the colour temperature via colourTEMPERATURE mode or colourSWITCH mode with 8 predefined values 2,700 K and 6,500 K.
- Stepless setting for the dimming level between 15 and 100 %.

> [OPTIONS](#)

PC-cover

ZUMI010000000500 PC-cover for food environment Ø 111

Flat Springs

ZUMIFS Flat Springs