

## CONO canto SMART



## CONO canto wireless

### The ideal speaker for lighting tracks

The CONO canto WiFi is an active wireless loudspeaker with integrated digital amplifier and special connection for use in all commercially available 3-phase power rails. The music is received through WiFi at a distance of up to 70 meters from the NewTec WiFi Sender or up to 120 meters from the newest NewTec SMARTplayer. Any number of speakers can be used. The volume of each individual loudspeaker can also be adjusted by remote control. The loudspeaker housing is made of carbon-fiber-reinforced plastic and can therefore be used directly next to large heat-generating light sources. The special coating ensures a noble and scratch-resistant surface structure. The soft sound of the CONO canto wireless creates a pleasant, soothing atmosphere from soft background music to precise playback in HiFi quality.

- ✓ Easy installation
- ✓ No speaker cable needed
- ✓ Any number of speakers can be used
- ✓ Volume of each individual speaker can be individually adjusted
- ✓ Compatible with all standard 3 phase lighting tracks
- ✓ Perfectly integrated into the look of the ceiling

### Plug & Play

# Technical Data

## CONO canto SMART

<b>Type</b>	Clip in on electric binaries (for lights)
<b>Principle</b>	one way WiFi speaker with integrated digital amplifier
<b>Dimensions DxH</b>	∅ 134mm x 150 mm (Total height)
<b>Weight</b>	1,45 kg (1,79 kg incl. Packaging)
<b>Enclosure</b>	ABS painted / Polycarbonat
<b>Material</b>	Formstable up to 220° (up to 170° long-term usage)
<b>Fireclass V-0</b>	UL94 self-extinguish
<b>Colours</b>	Silver - White - Black- all RAL colours on demand
<b>Equipment</b>	1 NewTec KA10 Speaker 50W 4 Ω
<b>Output</b>	40 Watt RMS
<b>Transmission rate Wireless</b>	1,9 Ghz n-DECT ( <a href="https://www.newtec-audio.com/en/wlan-vs-ndect/">https://www.newtec-audio.com/en/wlan-vs-ndect/</a> )
<b>Nominal Sensitivity</b>	85,5 dB (+6dB auf 360°)
<b>Maximum SPL</b>	103,5 dB
<b>Frequency response</b>	105 – 21.000 Hz ( +/- 3 dB)
<b>Connectors</b>	Multiadapter for 3 phase lightning track
<b>Compatibility</b>	Nordic Aluminium, Eutrac®, Global, Nuco, Staff, Ivela, Zumtobel, and many more
<b>Power Supply</b>	AC 100-240 V; 50/60 Hz; 0.5 A
<b>Transmitter</b>	NewTec SMARTplayer

### Example tracks

