

PRODUCT DESCRIPTION

The CRISSCROSS is a very elegant 3D printed suspension luminaire with a diameter of 63mm and a length of 375mm.

TECHNICAL DATA

Application	Suspension
Dimensions	Ø 63mm - 375mm
IP rating	IP20
Power	230V
Lifetime L70/B50/65°C	>50000h
MacAdam ellipse	3
Guarantee	5 year

Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2700K	9,5W	230V	710 lm	75 lm/W	90+	G
3000K	9,5W	230V	760 lm	80 lm/W	90+	G
4000K	9,5W	230V	810 lm	85 lm/W	90+	F

ORDER REFERENCE

> [LUMINAIRE](#)

! ORDER REFERENCE**2700K**

12°	ZUMI1802602701	Crisscross SLA AC G2 750lm 230V 9,5W 2700K CRI90+ 12°
24°	ZUMI1801742801	Crisscross SLA AC G2 710lm 230V 9,5W 2700K CRI90+ 24°
36°	ZUMI1801752901	Crisscross SLA AC G2 710lm 230V 9,5W 2700K CRI90+ 36°

3000K

12°	ZUMI1802612701	Crisscross SLA AC G2 780lm 230V 9,5W 3000K CRI90+ 12°
24°	ZUMI1801762801	Crisscross SLA AC G2 760lm 230V 9,5W 3000K CRI90+ 24°
36°	ZUMI1801772901	Crisscross SLA AC G2 760lm 230V 9,5W 3000K CRI90+ 36°

4000K

12°	ZUMI1802622701	Crisscross SLA AC G2 820lm 230V 9,5W 4000K CRI90+ 12°
24°	ZUMI1801782801	Crisscross SLA AC G2 810lm 230V 9,5W 4000K CRI90+ 24°
36°	ZUMI1801792901	Crisscross SLA AC G2 810lm 230V 9,5W 4000K CRI90+ 36°

> [no driver needed](#)

dimnable phase cut - see dimmerlist



PRODUCT DESCRIPTION

The CRISSCROSS is a very elegant 3D printed suspension luminaire with a diameter of 63mm and a length of 375mm.

TECHNICAL DATA

Application	Suspension
Dimensions	Ø 63mm - 375mm
IP rating	IP20
Power	250mA/350mA
Lifetime L70/B50/65°C	>50000h
MacAdam ellipse	3
Guarantee	5 year

(*on components, only if ordered luminaire + driver)

Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2700K	8,8W	250mA	770 lm	88 lm/W	90+	G
	12,2W	350mA	1140 lm	93 lm/W	90+	G
3000K	8,8W	250mA	840 lm	95 lm/W	90+	F
	12,2W	350mA	1170 lm	96 lm/W	90+	F
4000K	8,8W	250mA	890 lm	101 lm/W	90+	F
	12,2W	350mA	1270 lm	104 lm/W	90+	F

ORDER REFERENCE> LUMINAIRE**2700K**

700lm

24°	ZUMI1801682814	Crisscross SLA DC 8,8W 250mA 770 lm 2700K CRI90+ 24° excl. driver
36°	ZUMI1801692914	Crisscross SLA DC 8,8W 250mA 770 lm 2700K CRI90+ 36° excl. driver

1200lm

12°	ZUMI1802632706	Crisscross SLA DC 12,2W 350mA 1140 lm 2700K CRI90+ 12° excl. driver
24°	ZUMI1801622806	Crisscross SLA DC 12,2W 350mA 1140 lm 2700K CRI90+ 24° excl. driver
36°	ZUMI1801632906	Crisscross SLA DC 12,2W 350mA 1140 lm 2700K CRI90+ 36° excl. driver

3000K

700lm

24°	ZUMI1801702814	Crisscross SLA DC 8,8W 250mA 840 lm 3000K CRI90+ 24° excl. driver
36°	ZUMI1801712914	Crisscross SLA DC 8,8W 250mA 840 lm 3000K CRI90+ 36° excl. driver

1200lm

12°	ZUMI1802642706	Crisscross SLA DC 12,2W 350mA 1170 lm 3000K CRI90+ 12° excl. driver
24°	ZUMI1801642806	Crisscross SLA DC 12,2W 350mA 1170 lm 3000K CRI90+ 24° excl. driver
36°	ZUMI1801652906	Crisscross SLA DC 12,2W 350mA 1170 lm 3000K CRI90+ 36° excl. driver

4000K

700lm

24°	ZUMI1801722814	Crisscross SLA DC 8,8W 250mA 890 lm 4000K CRI90+ 24° excl. driver
36°	ZUMI1801732914	Crisscross SLA DC 8,8W 250mA 890 lm 4000K CRI90+ 36° excl. driver

1200lm

12°	ZUMI1802652706	Crisscross SLA DC 12,2W 350mA 1270 lm 4000K CRI90+ 12° excl. driver
24°	ZUMI1801662806	Crisscross SLA DC 12,2W 350mA 1270 lm 4000K CRI90+ 24° excl. driver
36°	ZUMI1801672906	Crisscross SLA DC 12,2W 350mA 1270 lm 4000K CRI90+ 36° excl. driver

> Driver- to be placed remotely

250mA	dimmable	TRID87500627	LCA 15W 180-350mA flexC PH-C SR ADV (phase cut)
	non dimmable	TCIL127710	MP 15 HPFU 15W 240mA
350mA	dimmable	TRID87500627	LCA 15W 180-350mA flexC PH-C SR ADV (phase cut)
	non dimmable	TCIL127710	MP 15 HPFU 15W 340mA

