


PRODUCT DESCRIPTION

Recessed downlighter for general lighting, no driver needed.
 Aluminium luminaire, white, black or aluminium powder coated, with glass cover, available in several color temperatures and reflectors.



TECHNICAL DATA

Application	recessed
Dimensions	cut out: ø100mm h95mm
IP rating	IP20
Power	230V
Lifetime L70/F10/65°C	49000h
MacAdam ellipse	4
Guarantee	3 year



Color Temperature	Reflector	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
3000K	none	10,2W	230V	980 lm	96 lm/W	80+	G
	60°	10,2W	230V	1060 lm	104 lm/W	80+	G
	90°	10,2W	230V	1060 lm	104 lm/W	80+	G
4000K	none	10,2W	230V	1030 lm	101 lm/W	80+	F
	60°	10,2W	230V	1110 lm	109 lm/W	80+	F
	90°	10,2W	230V	1110 lm	109 lm/W	80+	F

ORDER REFERENCE

> LUMINAIRE

! ORDER REFERENCE + (1) **W** (white) / **B** (black) / **A** (aluminium)
 + (2) **G** (gold reflector) option only for 3000K

3000K	60°	ZUMI242411301	Lobu Ready 1000-100 DLA G2 10,2W 230V 1060 lm 3000K CRI80 60°
	90°	ZUMI242411401	Lobu Ready 1000-100 DLA G2 10,2W 230V 1060 lm 3000K CRI80 90°
4000K	60°	ZUMI242421301	Lobu Ready 1000-100 DLA G2 10,2W 230V 1110 lm 4000K CRI80 60°
	90°	ZUMI242421401	Lobu Ready 1000-100 DLA G2 10,2W 230V 1110 lm 4000K CRI80 90°

> non dimmable

> DRIVER

No driver needed.


PRODUCT DESCRIPTION

Recessed downlighter for general lighting, no driver needed.
 Aluminium luminaire, white, black or aluminium powder coated, with glass cover, available in several color temperatures and reflectors.



TECHNICAL DATA

Application	recessed
Dimensions	cut out: ø140mm h125mm
IP rating	IP20
Power	230V
Lifetime L70/F10/65°C	49000h
MacAdam ellipse	4
Guarantee	3 year



Color Temperature	Reflector	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
3000K	none	10,1W	230V	1000 lm	99 lm/W	80+	G
	60°	10,1W	230V	1100 lm	109 lm/W	80+	G
	90°	10,1W	230V	1100 lm	109 lm/W	80+	G
4000K	none	10,1W	230V	1020 lm	101 lm/W	80+	F
	60°	10,1W	230V	1120 LM	111 lm/W	80+	F
	90°	10,1W	230V	1120 lm	111 lm/W	80+	F

ORDER REFERENCE

> LUMINAIRE

! ORDER REFERENCE + (1) **W** (white) / **B** (black) / **A** (aluminium)
 + (2) **G** (gold reflector) option only for 3000K

3000K	60°	ZUMI242431301	Lobu Ready 1000-150 DLA G2 10,1W 230V 1100 lm 3000K CRI80 60°
	90°	ZUMI242431401	Lobu Ready 1000-150 DLA G2 10,1W 230V 1100 lm 3000K CRI80 90°
4000K	60°	ZUMI242441301	Lobu Ready 1000-150 DLA G2 10,1W 230V 1120 lm 4000K CRI80 60°
	90°	ZUMI242441401	Lobu Ready 1000-150 DLA G2 10,1W 230V 1120 lm 4000K CRI80 90°

> non dimmable

> DRIVER

No driver needed.


PRODUCT DESCRIPTION

Recessed downlighter for general lighting, no driver needed.
 Aluminium luminaire, white, black or aluminium powder coated, with glass cover, available in several color temperatures and reflectors.



TECHNICAL DATA

Application: recessed
 Dimensions: cut out: ø140mm h125mm
 IP rating: IP20
 Power: 230V
 Lifetime L70/F10/65°C: 49000h
 MacAdam ellipse: 4
 Guarantee: 3 year



Color Temperature	Reflector	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
3000K	none	20,2W	230V	1970 lm	97 lm/W	80+	G
	60°	20,2W	230V	2130 lm	105 lm/W	80+	G
	90°	20,2W	230V	2130 lm	105 lm/W	80+	G
4000K	none	20,2W	230V	2050 lm	101 lm/W	80+	F
	60°	20,2W	230V	2210 lm	109 lm/W	80+	F
	90°	20,2W	230V	2210 lm	109 lm/W	80+	F

ORDER REFERENCE

> LUMINAIRE

! ORDER REFERENCE + (1) **W** (white) / **B** (black) / **A** (aluminium)
 + (2) **G** (gold reflector) option only for 3000K

3000K	60°	ZUMI2424321301	Lobu Ready 2000-150 DLA G2 20,2W 230V 2130 lm 3000K CRI80 60°
	90°	ZUMI2424321401	Lobu Ready 2000-150 DLA G2 20,2W 230V 2130 lm 3000K CRI80 90°
4000K	60°	ZUMI2424421301	Lobu Ready 2000-150 DLA G2 20,2W 230V 2210 lm 4000K CRI80 60°
	90°	ZUMI2424421401	Lobu Ready 2000-150 DLA G2 20,2W 230V 2210 lm 4000K CRI80 90°

> non dimmable

> DRIVER

No driver needed.