

PRODUCT DESCRIPTION


The PLK is a very small and elegant spot with multiple possibilities. The tube, with a diameter of about 40mm and a length of 138mm, is 359° rotatable and 80° inclinable.

In this recessed version the PLK is slightly sunken in the ceiling which gives it an extra dimension. Perfectly combinable with the Rori or Rova Deep spot.

Aluminium luminaire. Standard equipped with torsion springs.

**TECHNICAL DATA**

Application	semi - recessed
Dimensions	cut out: torsion springs: ø86mm h60mm flat springs: ø83mm h60mm
IP rating	IP20
Power	200mA
Lifetime L70/F10/65°C	>60000h
MacAdam ellipse	3
Guarantee	5 year
(*on components, only if ordered luminaire + driver)	



Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2700K	6,9W	200mA	840 lm	123 lm/W	90+	E
3000K	6,9W	200mA	895 lm	131 lm/W	90+	E

ORDER REFERENCE

> LUMINAIRE

! ORDER REFERENCE + W (white) / B (black) / G (gold) / T (titanium) / BR (bronze)

2700K 10°	ZUMI472243005	PLK R 10° SLE G7 6,9W 200mA 840lm 2700K CRI90+ ex.driver
2700K 40°	ZUMI472241205	PLK R 40° SLE G7 6,9W 200mA 840lm 2700K CRI90+ ex.driver
3000K 10°	ZUMI472253005	PLK R 10° SLE G7 6,9W 200mA 895lm 3000K CRI90+ ex.driver
3000K 40°	ZUMI472251205	PLK R 40° SLE G7 6,9W 200mA 895lm 3000K CRI90+ ex.driver

> DRIVER

dimnable (Dali, switchDIM)

TRID28000673 + TRID28001168 + TRID28001104

LCA 10W 150-400mA one4all SC PRE + Strain-relief + Plug 200mA

non dimmable

TRID28000704 + TRID28001168 + TRID28001104

LC 10W 150-400mA flexC SC EXC + Strain-relief + Plug 200mA

> OPTIONS

Flat Springs

ZUMIFS

Flat Springs