

PRODUCT DESCRIPTION

The PLK is a very small and elegant spot with multiple possibilities. The tube, with a diameter of about 40mm and a length of 138mm, is 359° rotatable and 80° inclinable. Two tubes are placed on a plate with a diameter of 147 mm, available with torsion and flat springs.


Aluminium luminaire. Standard equipped with torsion springs.



TECHNICAL DATA

| | |
|-----------------------|-----------------------|
| Application | semi - recessed |
| Dimensions | cut out: ø 80mm h60mm |
| IP rating | IP20 |
| Power | 200mA |
| Lifetime L70/F10/65°C | >60000h |
| MacAdam ellipse | 3 |
| Guarantee | 5 year |

(*on components, only if ordered luminaire + driver)



| Color Temperature | Wattage | Forward Current | Lumen (LED) (at tp = 65°C) | Lumen/Watt (LED) (at tp = 65°C) | CRI | Energy Label |
|-------------------|---------|-----------------|----------------------------|---------------------------------|-----|--------------|
| 2700K | 6,9W | 200mA | 840 lm | 123 lm/W | 90+ | E |
| 3000K | 6,9W | 200mA | 895 lm | 131 lm/W | 90+ | E |

ORDER REFERENCE

> LUMINAIRE

! ORDER REFERENCE + W (white) / B (black) / G (gold) / T (titanium) / BR (bronze)

| | | |
|------------------|---------------|---|
| 2700K 10° | ZUMI462243005 | PLK S 147 Double 10° SLE G7 2x6,9W 200mA 2x840lm 2700K CRI90+ ex.driver |
| 2700K 40° | ZUMI462241205 | PLK S 147 Double 40° SLE G7 2x6,9W 200mA 2x840lm 2700K CRI90+ ex.driver |
| 3000K 10° | ZUMI462253005 | PLK S 147 Double 10° SLE G7 2x6,9W 200mA 2x895lm 3000K CRI90+ ex.driver |
| 3000K 40° | ZUMI462251205 | PLK S 147 Double 40° SLE G7 2x6,9W 200mA 2x895lm 3000K CRI90+ ex.driver |

> DRIVER (parallel connection)

dimmable (Dali, switchDIM)

TRID28000674 + TRID28001168 + TRID28001112
 LCA 17W 250–700mA one4all SC PRE + Strain-relief + Plug 400mA

non dimmable

TRID28000705 + TRID28001168 + TRID28001112
 LC 17W 250-700mA flexC SC EXC + Strain-relief + Plug 400mA