

**PRODUCT DESCRIPTION**


The PLK is a very small and elegant spot with multiple possibilities. The tube, with a diameter of about 40mm and a length of 138mm, is 359° rotatable and 80° inclinable. It is asymmetricly placed on a plate with a diameter of 99 mm, available with torsion and flat springs.

Aluminium luminaire. Standard equipped with torsion springs.

**TECHNICAL DATA**

Application	semi - recessed
Dimensions	cut out: ø80mm h60mm
IP rating	IP20
Power	200mA
Lifetime L70/F10/65°C	>60000h
MacAdam ellipse	3
Guarantee	5 year

(\*on components, only if ordered luminaire + driver)



Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2700K	6,9W	200mA	840 lm	123 lm/W	90+	E
3000K	6,9W	200mA	895 lm	131 lm/W	90+	E

**ORDER REFERENCE**

> [LUMINAIRE](#)

**! ORDER REFERENCE + W (white) / B (black) / G (gold) / T (titanium) / BR (bronze)**

<b>2700K 10°</b>	ZUMI432243005	PLK S 99 Single 10° SLE G7 6,9W 200mA 840lm 2700K CRI90+ ex.driver
<b>2700K 40°</b>	ZUMI432241205	PLK S 99 Single 40° SLE G7 6,9W 200mA 840lm 2700K CRI90+ ex.driver
<b>3000K 10°</b>	ZUMI432253005	PLK S 99 Single 10° SLE G7 6,9W 200mA 895lm 3000K CRI90+ ex.driver
<b>3000K 40°</b>	ZUMI432251205	PLK S 99 Single 40° SLE G7 6,9W 200mA 895lm 3000K CRI90+ ex.driver

> [DRIVER](#)

**dimmable (Dali, switchDIM)**

TRID28000673 + TRID28001168 + TRID28001104  
LCA 10W 150-400mA one4all SC PRE + Strain-relief + Plug 200mA

**non dimmable**

TRID28000704 + TRID28001168 + TRID28001104  
LC 10W 150-400mA flexC SC EXC + Strain-relief + Plug 200mA

> [OPTIONS](#)

**Flat Springs**

ZUMIFS Flat Springs