

PRODUCT DESCRIPTION


Spot on track for general or accent lighting.

Aluminium luminaire in several colors and color temperatures with several possible reflectors.

Dimmable: only compatible with Global Trac PULSE from Nordic Aluminum and OneTrack from Stucchi.

TECHNICAL DATA

Application	3F track (If dimm. :Only Global or Stucchi track) (not dimm. Global, Stucchi or Eutrac)
Dimensions	ø 80mm h 80mm
IP rating	IP20
Power	230V
Lifetime L70/F10/65°C	>55000h
MacAdam ellipse	3
Guarantee	5 year



Color Temperature	Wattage incl. driver	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2700K	13,6W	350mA	1558 lm	134 lm/W	90+	E
	19,4W	500mA	2225 lm	134 lm/W	90+	E
3000K	13,6W	350mA	1714 lm	147 lm/W	90+	E
	19,4W	500mA	2449 lm	147 lm/W	90+	E
3500K	13,6W	350mA	1732 lm	149 lm/W	90+	E
	19,4W	500mA	2474 lm	149 lm/W	90+	E
4000K	13,6W	350mA	1775 lm	152 lm/W	90+	E
	19,4W	500mA	2536 lm	152 lm/W	90+	E

ORDER REFERENCE

> [LUMINAIRE](#)

! ORDER REFERENCE + (1) **W** (white) / **B** (black) / **G** (gold) / **F** (forest)
 + (2) **G** (gold reflector) option only for 2700K or 3000K
 + (3) **DD2** (Dali dim Global)

350mA**2700K**

14°	ZUMI662132306	Tubb 3F CRI90+ SLE G7 13,6W 350mA 1558 lm 2700K 14° glass incl. driver
25°	ZUMI662132406	Tubb 3F CRI90+ SLE G7 13,6W 350mA 1558 lm 2700K 25° glass incl. driver
39°	ZUMI662132506	Tubb 3F CRI90+ SLE G7 13,6W 350mA 1558 lm 2700K 39° glass incl. driver
61°	ZUMI662132606	Tubb 3F CRI90+ SLE G7 13,6W 350mA 1558 lm 2700K 61° glass incl. driver

3000K

14°	ZUMI662142306	Tubb 3F CRI90+ SLE G7 13,6W 350mA 1714 lm 3000K 14° glass incl. driver
25°	ZUMI662142406	Tubb 3F CRI90+ SLE G7 13,6W 350mA 1714 lm 3000K 25° glass incl. driver
39°	ZUMI662142506	Tubb 3F CRI90+ SLE G7 13,6W 350mA 1714 lm 3000K 39° glass incl. driver
61°	ZUMI662142606	Tubb 3F CRI90+ SLE G7 13,6W 350mA 1714 lm 3000K 61° glass incl. driver

3500K

14°	ZUMI662152306	Tubb 3F CRI90+ SLE G7 13,6W 350mA 1732 lm 3500K 14° glass incl. driver
25°	ZUMI662152406	Tubb 3F CRI90+ SLE G7 13,6W 350mA 1732 lm 3500K 25° glass incl. driver
39°	ZUMI662152506	Tubb 3F CRI90+ SLE G7 13,6W 350mA 1732 lm 3500K 39° glass incl. driver
61°	ZUMI662152606	Tubb 3F CRI90+ SLE G7 13,6W 350mA 1732 lm 3500K 61° glass incl. driver

4000K

14°	ZUMI662162306	Tubb 3F CRI90+ SLE G7 13,6W 350mA 1775 lm 4000K 14° glass incl. driver
25°	ZUMI662162406	Tubb 3F CRI90+ SLE G7 13,6W 350mA 1775 lm 4000K 25° glass incl. driver
39°	ZUMI662162506	Tubb 3F CRI90+ SLE G7 13,6W 350mA 1775 lm 4000K 39° glass incl. driver
61°	ZUMI662162606	Tubb 3F CRI90+ SLE G7 13,6W 350mA 1775 lm 4000K 61° glass incl. driver

500mA**2700K**

14°	ZUMI662132307	Tubb 3F CRI90+ SLE G7 19,4W 500mA 2225 lm 2700K 14° glass incl. driver
25°	ZUMI662132407	Tubb 3F CRI90+ SLE G7 19,4W 500mA 2225 lm 2700K 25° glass incl. driver
39°	ZUMI662132507	Tubb 3F CRI90+ SLE G7 19,4W 500mA 2225 lm 2700K 39° glass incl. driver
61°	ZUMI662132607	Tubb 3F CRI90+ SLE G7 19,4W 500mA 2225 lm 2700K 61° glass incl. driver

3000K

14°	ZUMI662142307	Tubb 3F CRI90+ SLE G7 19,4W 500mA 2449 lm 3000K 14° glass incl. driver
25°	ZUMI662142407	Tubb 3F CRI90+ SLE G7 19,4W 500mA 2449 lm 3000K 25° glass incl. driver
39°	ZUMI662142507	Tubb 3F CRI90+ SLE G7 19,4W 500mA 2449 lm 3000K 39° glass incl. driver
61°	ZUMI662142607	Tubb 3F CRI90+ SLE G7 19,4W 500mA 2449 lm 3000K 61° glass incl. driver

3500K

14°	ZUMI662152307	Tubb 3F CRI90+ SLE G7 19,4W 500mA 2474 lm 3500K 14° glass incl. conv
25°	ZUMI662152407	Tubb 3F CRI90+ SLE G7 19,4W 500mA 2474 lm 3500K 25° glass incl. driver
39°	ZUMI662152507	Tubb 3F CRI90+ SLE G7 19,4W 500mA 2474 lm 3500K 39° glass incl. driver
61°	ZUMI662152607	Tubb 3F CRI90+ SLE G7 19,4W 500mA 2474 lm 3500K 61° glass incl. driver

4000K

14°	ZUMI662162307	Tubb 3F CRI90+ SLE G7 19,4W 500mA 2536 lm 4000K 14° glass incl. driver
25°	ZUMI662162407	Tubb 3F CRI90+ SLE G7 19,4W 500mA 2536 lm 4000K 25° glass incl. driver
39°	ZUMI662162507	Tubb 3F CRI90+ SLE G7 19,4W 500mA 2536 lm 4000K 39° glass incl. driver
61°	ZUMI662162607	Tubb 3F CRI90+ SLE G7 19,4W 500mA 2536 lm 4000K 61° glass incl. driver

> OPTIONS**Honeycomb grid**

ZUMI25HC

Honeycomb grid

> DRIVER

Included : DALI


PRODUCT DESCRIPTION

Spot on track for general or accent lighting.
Aluminium luminaire in several colors and color temperatures with several possible reflectors.

Casambi dimmable.

TECHNICAL DATA

Application	3F track (Eutrac, Global or Stucchi track)
Dimensions	∅ 80mm h 80mm
IP rating	IP20
Power	230V
Lifetime L70/F10/65°C	>55000h
MacAdam ellipse	3
Guarantee	5 year



Color Temperature	Wattage incl. driver	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2700K	19,4W	500mA	2225 lm	134 lm/W	90+	E
3000K	19,4W	500mA	2449 lm	147 lm/W	90+	E
3500K	19,4W	500mA	2474 lm	149 lm/W	90+	E
4000K	19,4W	500mA	2536 lm	152 lm/W	90+	E

ORDER REFERENCE

> [LUMINAIRE](#)

! ORDER REFERENCE + (1) **W** (white) / **B** (black) / **G** (gold) / **F** (forest)
+ (2) **G** (gold reflector) option only for 2700K or 3000K

2700K

14°	ZUMI1702132307	Tubb 3F Wireless Casambi+ SLE G7 19,4W 500mA 2225 lm 2700K CRI90+ 14° incl. driver
25°	ZUMI1702132407	Tubb 3F Wireless Casambi+ SLE G7 19,4W 500mA 2225 lm 2700K CRI90+ 25° incl. driver
39°	ZUMI1702132507	Tubb 3F Wireless Casambi+ SLE G7 19,4W 500mA 2225 lm 2700K CRI90+ 39° incl. driver
61°	ZUMI1702132607	Tubb 3F Wireless Casambi+ SLE G7 19,4W 500mA 2225 lm 2700K CRI90+ 61° incl. driver

3000K

14°	ZUMI1702142307	Tubb 3F Wireless Casambi+ SLE G7 19,4W 500mA 2449 lm 3000K CRI90+ 14° incl. driver
25°	ZUMI1702142407	Tubb 3F Wireless Casambi+ SLE G7 19,4W 500mA 2449 lm 3000K CRI90+ 25° incl. driver
39°	ZUMI1702142507	Tubb 3F Wireless Casambi+ SLE G7 19,4W 500mA 2449 lm 3000K CRI90+ 39° incl. driver
61°	ZUMI1702142607	Tubb 3F Wireless Casambi+ SLE G7 19,4W 500mA 2449 lm 3000K CRI90+ 61° incl. driver

3500K

14°	ZUMI1702152307	Tubb 3F Wireless Casambi+ SLE G7 19,4W 500mA 2474 lm 3500K CRI90+ 14° incl. conv
25°	ZUMI1702152407	Tubb 3F Wireless Casambi+ SLE G7 19,4W 500mA 2474 lm 3500K CRI90+ 25° incl. driver
39°	ZUMI1702152507	Tubb 3F Wireless Casambi+ SLE G7 19,4W 500mA 2474 lm 3500K CRI90+ 39° incl. driver
61°	ZUMI1702152607	Tubb 3F Wireless Casambi+ SLE G7 19,4W 500mA 2474 lm 3500K CRI90+ 61° incl. driver

4000K

14°	ZUMI1702162307	Tubb 3F Wireless Casambi+ SLE G7 19,4W 500mA 2536 lm 4000K CRI90+ 14° incl. driver
25°	ZUMI1702162407	Tubb 3F Wireless Casambi+ SLE G7 19,4W 500mA 2536 lm 4000K CRI90+ 25° incl. driver
39°	ZUMI1702162507	Tubb 3F Wireless Casambi+ SLE G7 19,4W 500mA 2536 lm 4000K CRI90+ 39° incl. driver
61°	ZUMI1702162607	Tubb 3F Wireless Casambi+ SLE G7 19,4W 500mA 2536 lm 4000K CRI90+ 61° incl. driver

> [OPTIONS](#)

ZUMI25HC Honeycomb grid

> [DRIVER](#) Included

> [Recommended Wireless User Interface](#)

TRID28002213 basicDIM Wireless User Interface black
TRID28002420 basicDIM Wireless User Interface white

PRODUCT DESCRIPTION

Spot on track for general or accent lighting equipped with a LEDmodule especially to enlighten several food products.

There's a choice between 'fish' to light up fish products, 'gold' for bakery goods and 'gold+' for rather crusty bakery goods such as croissants and baguettes.

The cannon 'meat+' provides a highly red color which is ideal for the presentation of meat.


Its 'fresh meat' is suitable to use for meat in the counter. Fruit is ideal for fruit and vegetables.

Aluminium luminaire in several colors and color temperatures with several possible reflectors.

Dimmable: only compatible with Global Trac PULSE from Nordic Aluminum and OneTrack from Stucchi.

**TECHNICAL DATA**

Application	3F track (If dimm. :Only Global or Stucchi track) (not dimm. Global, Stucchi or Eutrac)
Dimensions	ø 80mm h 80mm
IP rating	IP20
Power	230V
Lifetime L70/F10/65°C	>55000h
MacAdam ellipse	3
Guarantee	5 year



Color Temperature	Wattage incl. driver	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
FISH	13,6W	350mA	1411 lm	121 lm/W	/	E
	19,4W	500mA	2015 lm	121 lm/W	/	E
GOLD 2700K	13,6W	350mA	1308 lm	112 lm/W	/	E
	19,4W	500mA	1868 lm	112 lm/W	/	E
GOLD+ 2400K	13,6W	350mA	826 lm	73 lm/W	/	F
	19,4W	500mA	1171 lm	70 lm/W	/	F
MEAT+	13,6W	350mA	879 lm	75 lm/W	/	n.a
	19,4W	500mA	1256 lm	75 lm/W	/	n.a
FRESH MEAT	13,6W	350mA	857 lm	74 lm/W	/	n.a
	19,4W	500mA	1224 lm	74 lm/W	/	n.a
FRUIT	13,6W	350mA	1224 lm	105 lm/W	/	F

ORDER REFERENCE

> LUMINAIRE

! **ORDER REFERENCE** + (1) **W** (white) / **B** (black) / **G** (gold) / **F** (forest)

+ (2) **G** (gold reflector) option only for Gold 2700K and Gold+ 2400K

+ (3) **DD2** (Dali dim Global)

350mA**FISH**

14°	ZUMI662173106	Tubb 3F Fish SLE G7 13,6W 350mA 1411 lm 14° PC incl. driver
25°	ZUMI662171906	Tubb 3F Fish SLE G7 13,6W 350mA 1411 lm 25° PC incl. driver
39°	ZUMI662172006	Tubb 3F Fish SLE G7 13,6W 350mA 1411 lm 39° PC incl. driver
61°	ZUMI662172106	Tubb 3F Fish SLE G7 13,6W 350mA 1411 lm 61° PC incl. driver

GOLD 2700K

14°	ZUMI662183106	Tubb 3F Gold SLE G7 13,6W 350mA 1308 lm 2700K 14° PC incl. driver
25°	ZUMI662181906	Tubb 3F Gold SLE G7 13,6W 350mA 1308 lm 2700K 25° PC incl. driver
39°	ZUMI662182006	Tubb 3F Gold SLE G7 13,6W 350mA 1308 lm 2700K 39° PC incl. driver
61°	ZUMI662182106	Tubb 3F Gold SLE G7 13,6W 350mA 1308 lm 2700K 61° PC incl. driver

GOLD+ 2400K

14°	ZUMI662083106	Tubb 3F Gold+ SLE G7 13,6W 350mA 826 lm 2400K 14° PC incl. driver
25°	ZUMI662081906	Tubb 3F Gold+ SLE G7 13,6W 350mA 826 lm 2400K 25° PC incl. driver
39°	ZUMI662082006	Tubb 3F Gold+ SLE G7 13,6W 350mA 826 lm 2400K 39° PC incl. driver
61°	ZUMI662082106	Tubb 3F Gold+ SLE G7 13,6W 350mA 826 lm 2400K 61° PC incl. driver

MEAT+

14°	ZUMI662193106	Tubb 3F Meat+ SLE G7 13,6W 350mA 879 lm 14° PC incl. driver
25°	ZUMI662191906	Tubb 3F Meat+ SLE G7 13,6W 350mA 879 lm 25° PC incl. driver
39°	ZUMI662192006	Tubb 3F Meat+ SLE G7 13,6W 350mA 879 lm 39° PC incl. driver
61°	ZUMI662192106	Tubb 3F Meat+ SLE G7 13,6W 350mA 879 lm 61° PC incl. driver

FRESH MEAT

14°	ZUMI662203106	Tubb 3F Fresh Meat SLE G7 13,6W 350mA 857 lm 14° PC incl. driver
25°	ZUMI662201906	Tubb 3F Fresh Meat SLE G7 13,6W 350mA 857 lm 25° PC incl. driver
39°	ZUMI662202006	Tubb 3F Fresh Meat SLE G7 13,6W 350mA 857 lm 39° PC incl. driver
61°	ZUMI662202106	Tubb 3F Fresh Meat SLE G7 13,6W 350mA 857 lm 61° PC incl. driver

FRUIT

14°	ZUMI662213106	Tubb 3F Fruit SLE G7 13,6W 350mA 1224 lm 14° PC incl. driver
25°	ZUMI662211906	Tubb 3F Fruit SLE G7 13,6W 350mA 1224 lm 25° PC incl. driver
39°	ZUMI662212006	Tubb 3F Fruit SLE G7 13,6W 350mA 1224 lm 39° PC incl. driver
61°	ZUMI662212106	Tubb 3F Fruit SLE G7 13,6W 350mA 1224 lm 61° PC incl. driver

500mA**FISH**

14°	ZUMI662173107	Tubb 3F Fish SLE G7 19,4W 500mA 2015 lm 14° PC incl. driver
25°	ZUMI662171907	Tubb 3F Fish SLE G7 19,4W 500mA 2015 lm 25° PC incl. driver
39°	ZUMI662172007	Tubb 3F Fish SLE G7 19,4W 500mA 2015 lm 39° PC incl. driver
61°	ZUMI662172107	Tubb 3F Fish SLE G7 19,4W 500mA 2015 lm 61° PC incl. driver

GOLD 2700K

14°	ZUMI662183107	Tubb 3F Gold SLE G7 19,4W 500mA 1868 lm 2700K 14° PC incl. driver
25°	ZUMI662181907	Tubb 3F Gold SLE G7 19,4W 500mA 1868 lm 2700K 25° PC incl. driver
39°	ZUMI662182007	Tubb 3F Gold SLE G7 19,4W 500mA 1868 lm 2700K 39° PC incl. driver
61°	ZUMI662182107	Tubb 3F Gold SLE G7 19,4W 500mA 1868 lm 2700K 61° PC incl. driver

GOLD+ 2400K

14°	ZUMI662083107	Tubb 3F Gold+ SLE G7 19,4W 500mA 1171 lm 2400K 14° PC incl. driver
25°	ZUMI662081907	Tubb 3F Gold+ SLE G7 19,4W 500mA 1171 lm 2400K 25° PC incl. driver
39°	ZUMI662082007	Tubb 3F Gold+ SLE G7 19,4W 500mA 1171 lm 2400K 39° PC incl. driver
61°	ZUMI662082107	Tubb 3F Gold+ SLE G7 19,4W 500mA 1171 lm 2400K 61° PC incl. driver

MEAT+

14°	ZUMI662193107	Tubb 3F Meat+ SLE G7 19,4W 500mA 1256 lm 14° PC incl. driver
25°	ZUMI662191907	Tubb 3F Meat+ SLE G7 19,4W 500mA 1256 lm 25° PC incl. driver
39°	ZUMI662192007	Tubb 3F Meat+ SLE G7 19,4W 500mA 1256 lm 39° PC incl. driver
61°	ZUMI662192107	Tubb 3F Meat+ SLE G7 19,4W 500mA 1256 lm 61° PC incl. driver

FRESH MEAT

14°	ZUMI662203107	Tubb 3F Fresh Meat SLE G7 19,4W 500mA 1224 lm 14° PC incl. driver
25°	ZUMI662201907	Tubb 3F Fresh Meat SLE G7 19,4W 500mA 1224 lm 25° PC incl. driver
39°	ZUMI662202007	Tubb 3F Fresh Meat SLE G7 19,4W 500mA 1224 lm 39° PC incl. driver
61°	ZUMI662202107	Tubb 3F Fresh Meat SLE G7 19,4W 500mA 1224 lm 61° PC incl. driver

FRUIT

14°	ZUMI662213107	Tubb 3F Fruit SLE G7 19,4W 500mA 1748 lm 14° PC incl. driver
25°	ZUMI662211907	Tubb 3F Fruit SLE G7 19,4W 500mA 1748 lm 25° PC incl. driver
39°	ZUMI662212007	Tubb 3F Fruit SLE G7 19,4W 500mA 1748 lm 39° PC incl. driver
61°	ZUMI662212107	Tubb 3F Fruit SLE G7 19,4W 500mA 1748 lm 61° PC incl. driver

> OPTIONS**Honeycomb grid**

ZUMI25HC

Honeycomb grid

> DRIVER

Included : DALI

PRODUCT DESCRIPTION


Spot on track for general or accent lighting.

Aluminium luminaire in several colors and color temperatures with several possible reflectors.

Dimmable: only compatible with Global Trac PULSE from Nordic Aluminum and OneTrack from Stucchi.

TECHNICAL DATA

Application	3F track (If dimm. :Only Global or Stucchi track) (not dimm. Global, Stucchi or Eutrac)
Dimensions	ø 80mm h 80mm
IP rating	IP20
Power	230V
Lifetime L70/F10/65°C	>55000h
MacAdam ellipse	2
Guarantee	5 year



Color Temperature	Wattage incl. driver	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
3100K	13,6W	350mA	1210 lm	104 lm/W	98	F
	19,4W	500mA	1729 lm	104 lm/W	98	F

ORDER REFERENCE

> LUMINAIRE

! ORDER REFERENCE + (1) **W** (white) / **B** (black) / **G** (gold) / **F** (forest)
 + (2) **G** (gold reflector)
 + (3) **DD2** (Dali dim Global)

350mA

14°	ZUMI662222306	Tubb 3F Art CRI97 SLE G7 13,6W 350mA 1210 lm 3100K 14° glass incl. driver
25°	ZUMI662222406	Tubb 3F Art CRI97 SLE G7 13,6W 350mA 1210 lm 3100K 25° glass incl. driver
39°	ZUMI662222506	Tubb 3F Art CRI97 SLE G7 13,6W 350mA 1210 lm 3100K 39° glass incl. driver
61°	ZUMI662222606	Tubb 3F Art CRI97 SLE G7 13,6W 350mA 1210 lm 3100K 61° glass incl. driver

500mA

14°	ZUMI662222307	Tubb 3F Art CRI97 SLE G7 19,4W 500mA 1729 lm 3100K 14° glass incl. driver
25°	ZUMI662222407	Tubb 3F Art CRI97 SLE G7 19,4W 500mA 1729 lm 3100K 25° glass incl. driver
39°	ZUMI662222507	Tubb 3F Art CRI97 SLE G7 19,4W 500mA 1729 lm 3100K 39° glass incl. driver
61°	ZUMI662222607	Tubb 3F Art CRI97 SLE G7 19,4W 500mA 1729 lm 3100K 61° glass incl. driver

> OPTIONS

Honeycomb grid

ZUMI25HC

Honeycomb grid

> DRIVER

Included : DALI

PRODUCT DESCRIPTION


Spot on track for general or accent lighting.

Aluminium luminaire in several colors and color temperatures with several possible reflectors.

Dimmable: only compatible with Global Trac PULSE from Nordic Aluminum and OneTrack from Stucchi.

TECHNICAL DATA

Application	3F track (If dimm. :Only Global or Stucchi track) (not dimm. Global, Stucchi or Eutrac)
Dimensions	ø 80mm h 80mm
IP rating	IP20
Power	230V
Lifetime L70/F10/65°C	>55000h
MacAdam ellipse	2
Guarantee	5 year



Color Temperature	Wattage incl. driver	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
3250K	13,6W	350mA	1313 lm	136 lm/W	95	F
	19,4W	500mA	1876 lm	136 lm/W	95	F

ORDER REFERENCE

> [LUMINAIRE](#)

! ORDER REFERENCE + (1) **W** (white) / **B** (black) / **G** (gold) / **F** (forest)
+ (2) **DD2** (Dali dim Global)

350mA

14°	ZUMI662232306	Tubb 3F Fashion CRI95 SLE G7 13,6W 350mA 1313 lm 3250K 14° glass incl. driver
25°	ZUMI662232406	Tubb 3F Fashion CRI95 SLE G7 13,6W 350mA 1313 lm 3250K 25° glass incl. driver
39°	ZUMI662232506	Tubb 3F Fashion CRI95 SLE G7 13,6W 350mA 1313 lm 3250K 39° glass incl. driver
61°	ZUMI662232606	Tubb 3F Fashion CRI95 SLE G7 13,6W 350mA 1313 lm 3250K 61° glass incl. driver

500mA

14°	ZUMI662232307	Tubb 3F Fashion CRI95 SLE G7 19,4W 500mA 1876 lm 3250K 14° glass incl. driver
25°	ZUMI662232407	Tubb 3F Fashion CRI95 SLE G7 19,4W 500mA 1876 lm 3250K 25° glass incl. driver
39°	ZUMI662232507	Tubb 3F Fashion CRI95 SLE G7 19,4W 500mA 1876 lm 3250K 39° glass incl. driver
61°	ZUMI662232607	Tubb 3F Fashion CRI95 SLE G7 19,4W 500mA 1876 lm 3250K 61° glass incl. driver

> [OPTIONS](#)

Honeycomb grid

ZUMI25HC

Honeycomb grid

> [DRIVER](#)

Included : DALI