

PRODUCT DESCRIPTION

The Xininx collection: a concept of invisible integration of plaster-imitated lighting fixtures.
Wall luminaire with an opal polycarbonate cover to be used as orientation luminaire.

**TECHNICAL DATA**

| | |
|-----------------------|------------------|
| Application | wall - recessed |
| Dimensions | 100 x 100 x 90mm |
| IP rating | IP20 |
| Power | 100mA |
| Lifetime L70/F10/65°C | 58000h |
| MacAdam ellipse | 3 |
| Guarantee | 5 year |

| Color Temperature | Wattage | Forward current | Lumen (LED) (at tp = 65°C) | Lumen/Watt (LED) (at tp = 65°C) | CRI | Energy Label |
|-------------------|---------|-----------------|----------------------------|---------------------------------|-----|--------------|
| 3000K | 3,5W | 100mA | 448 lm | 110 lm/W | 90 | D |
| 4000K | 3,7W | 100mA | 480 lm | 121 lm/W | 90 | D |

ORDER REFERENCE> FIXTURE

| | | |
|--------------|---------------|--|
| 3000K | ZUMI152250118 | XINIX MINI SLE G7 3,5W 100mA 448lm 3000K CRI90 excl.driver |
| 4000K | ZUMI152280118 | XINIX MINI SLE G7 3,5W 100mA 480lm 4000K CRI90 excl.driver |

> CONVERTER

| | | |
|---------------------|----------------|---------------------------------|
| non dimmable | ZUMITCIL122360 | TCI MP15 Converter 15W 60-360mA |
|---------------------|----------------|---------------------------------|