

PRODUCT DESCRIPTION

AURYX is a acoustic light luminaire made from open-cell foam with a soft flocked finish in standard colors. It features three integrated light lines with Zhagacompliant, cradle-to-cradle certified LEDs. Available in Ø800 mm and Ø1080 mm, AURYX supports ON/OFF, DALI, or CASAMBI dimming, with an optional emergency kit. Mounting options include surface (ceiling/wall), suspension with steel wires, or a Swing Arm. AURYX is available with either monochromatic lighting or tunable white for adjustable light ambiance



Technical data

Application	ceiling / wall
Dimensions	Ø 1080mm - H 78mm
IP rating	IP20
Power	230V
Lifetime L80/B10	72000h - 102000h
MacAdam ellipse	3
Guarantee	5 year

Color Temperature	Wattage	Forward Current	Lumen (LED)	Lumen/Watt (LED)	Lifetime L80/F10	CRI	Energy Label
2700K	72W	400mA	8850lm	142lm/W	>72000h	>90	D
3000K	72W	400mA	9150lm	147lm/W	>102000h	>90	D
3500K	72W	400mA	9350lm	150lm/W	>72000h	>90	D
4000K	72W	400mA	9480lm	152lm/W	>102000h	>90	D

Color Temperature	Wattage	Forward Current	Lumen (LED)	Lumen/Watt (LED)	Lifetime L80/B10	CRI	Energy Label
TW 2700K-6500K	69W	250mA	8940lm	150lm/W	>72000h	>90	D

ORDER REFERENCE

> [LUMINAIRE](#)

! ORDER REFERENCE

- PW** (Pure white)
- B** (black)
- LG** (light grey)
- MG** (medium grey)
- BBL** (brilliant blue)
- PY** (post yellow)
- GREN** (grenata)
- MG** (moss green)
- BBE** (brown beige)

2700K	ZUMI2423193219	AURYX 1080 2700K 8850lm 72W CRI90+ incl. driver - non dim
2700K	ZUMI2423193219D	AURYX 1080 2700K 8850lm 72W CRI90+ incl. driver - DALI
2700K	ZUMI2423193229	AURYX 1080 2700K 8850lm 72W CRI90+ incl. driver - CASAMBI
3000K	ZUMI2423203219	AURYX 1080 3000K 9150lm 72W CRI90+ incl. driver - non dim
3000K	ZUMI2423203219D	AURYX 1080 3000K 9150lm 72W CRI90+ incl. driver - DALI
3000K	ZUMI2423203229	AURYX 1080 3000K 9150lm 72W CRI90+ incl. driver - CASAMBI
3500K	ZUMI2423213219	AURYX 1080 3500K 9350lm 72W CRI90+ incl. driver - non dim
3500K	ZUMI2423213219D	AURYX 1080 3500K 9350lm 72W CRI90+ incl. driver - DALI
3500K	ZUMI2423213229	AURYX 1080 3500K 9350lm 72W CRI90+ incl. driver - CASAMBI
4000K	ZUMI2423223219	AURYX 1080 4000K 9480lm 72W CRI90+ incl. driver - non dim
4000K	ZUMI2423223219D	AURYX 1080 4000K 9480lm 72W CRI90+ incl. driver - DALI
4000K	ZUMI2423223229	AURYX 1080 4000K 9480lm 72W CRI90+ incl. driver - CASAMBI
2700-6500K	ZUMI2423233214	AURYX 1080 2700-6500K 8940lm 69W CRI90+ incl. driver - DALI DT8
2700-6500K	ZUMI2423233230	AURYX 1080 2700-6500K 8940lm 69W CRI90+ incl. driver - CASAMBI

> [OPTIONS](#)

Emergency kit 3h On request

PRODUCT DESCRIPTION

AURYX is a acoustic light luminaire made from open-cell foam with a soft flocked finish in standard colors. It features three integrated light lines with Zhagacompliant, cradle-to-cradle certified LEDs. Available in Ø800 mm and Ø1080 mm, AURYX supports ON/OFF, DALI, or CASAMBI dimming, with an optional emergency kit. Mounting options include surface (ceiling/wall), suspension with steel wires, or a Swing Arm. AURYX is available with either monochromatic lighting or tunable white for adjustable light ambiance



Technical data

Application	suspended
Dimensions	Ø 1080mm - H 78mm
IP rating	IP20
Power	230V
Lifetime L80/B10	72000h - 102000h
MacAdam ellipse	3
Guarantee	5 year

Color Temperature	Wattage	Forward Current	Lumen (LED)	Lumen/Watt (LED)	Lifetime L80/B10	CRI	Energy Label
2700K	72W	400mA	8850lm	142lm/W	>72000h	>90	D
3000K	72W	400mA	9150lm	147lm/W	>102000h	>90	D
3500K	72W	400mA	9350lm	150lm/W	>72000h	>90	D
4000K	72W	400mA	9480lm	152lm/W	>102000h	>90	D

Color Temperature	Wattage	Forward Current	Lumen (LED)	Lumen/Watt (LED)	Lifetime L80/B10	CRI	Energy Label
TW 2700K-6500K	69W	250mA	8940lm	150lm/W	>72000h	>90	D

ORDER REFERENCE

> [LUMINAIRE](#)

! ORDER REFERENCE

- PW** (Pure white)
- MG** (medium grey)
- GREN** (grenata)
- B** (black)
- BBL** (brilliant blue)
- MG** (moss green)
- LG** (light grey)
- PY** (post yellow)
- BBE** (brown beige)

2700K	ZUMI 2433193219	AURYX 1080 susp. 2700K 8850lm 72W CRI90+ incl. driver - non dim
2700K	ZUMI2433193219D	AURYX 1080 susp. 2700K 8850lm 72W CRI90+ incl. driver - DALI
2700K	ZUMI2433193229	AURYX 1080 susp. 2700K 8850lm 72W CRI90+ incl. driver - CASAMBI
3000K	ZUMI2433203219	AURYX 1080 susp. 3000K 9150lm 72W CRI90+ incl. driver - non dim
3000K	ZUMI2433203219D	AURYX 1080 susp. 3000K 9150lm 72W CRI90+ incl. driver - DALI
3000K	ZUMI2433203229	AURYX 1080 susp. 3000K 9150lm 72W CRI90+ incl. driver - CASAMBI
3500K	ZUMI2433213219	AURYX 1080 susp. 3500K 9350lm 72W CRI90+ incl. driver - non dim
3500K	ZUMI2433213219D	AURYX 1080 susp. 3500K 9350lm 72W CRI90+ incl. driver - DALI
3500K	ZUMI2433213229	AURYX 1080 susp. 3500K 9350lm 72W CRI90+ incl. driver - CASAMBI
4000K	ZUMI2433223219	AURYX 1080 susp. 4000K 9480lm 72W CRI90+ incl. driver - non dim
4000K	ZUMI2433223219D	AURYX 1080 susp. 4000K 9480lm 72W CRI90+ incl. driver - DALI
4000K	ZUMI2433223229	AURYX 1080 susp. 4000K 9480lm 72W CRI90+ incl. driver - CASAMBI
2700-6500K	ZUMI2433233214	AURYX 1080 susp. 2700-6500K 8940lm 69W CRI90+ incl. driver - DALI DT8
2700-6500K	ZUMI2433233230	AURYX 1080 susp. 2700-6500K 8940lm 69W CRI90+ incl. driver - CASAMBI

> [OPTIONS](#)

Emergency kit 3h On request

PRODUCT DESCRIPTION

AURYX is a acoustic light luminaire made from open-cell foam with a soft flocked finish in standard colors. It features three integrated light lines with Zhagacompliant, cradle-to-cradle certified LEDs. Available in Ø800 mm and Ø1080 mm, AURYX supports ON/OFF, DALI, or CASAMBI dimming, with an optional emergency kit. Mounting options include surface (ceiling/wall), suspension with steel wires, or a Swing Arm. AURYX is available with either monochromatic lighting or tunable white for adjustable light ambiance



Technical data

Application	ceiling
Dimensions	Ø 1080mm - H 78mm
IP rating	IP20
Power	230V
Lifetime L80/B10	72000h - 102000h
MacAdam ellipse	3
Guarantee	5 year

Color Temperature	Wattage	Forward Current	Lumen (LED)	Lumen/Watt (LED)	Lifetime L80/B10	CRI	Energy Label
2700K	72W	400mA	8850lm	142lm/W	>72000h	>90	D
3000K	72W	400mA	9150lm	147lm/W	>102000h	>90	D
3500K	72W	400mA	9350lm	150lm/W	>72000h	>90	D
4000K	72W	400mA	9480lm	152lm/W	>102000h	>90	D

Color Temperature	Wattage	Forward Current	Lumen (LED)	Lumen/Watt (LED)	Lifetime L80/B10	CRI	Energy Label
TW 2700K-6500K	69W	250mA	8940lm	150lm/W	>72000h	>90	D

ORDER REFERENCE

> [LUMINAIRE](#)

! ORDER REFERENCE

- PW** (Pure white)
- MG** (medium grey)
- GREN** (grenata)
- B** (black)
- BBL** (brilliant blue)
- MG** (moss green)
- LG** (light grey)
- PY** (post yellow)
- BBE** (brown beige)

2700K	ZUMI2443193219	AURYX 1080 arm 2700K 8850lm 72W CRI90+ incl. driver - non dim
2700K	ZUMI2443193219D	AURYX 1080 arm 2700K 8850lm 72W CRI90+ incl. driver - DALI
2700K	ZUMI2443193229	AURYX 1080 arm 2700K 8850lm 72W CRI90+ incl. driver - CASAMBI
3000K	ZUMI2443203219	AURYX 1080 arm 3000K 9150lm 72W CRI90+ incl. driver - non dim
3000K	ZUMI2443203219D	AURYX 1080 arm 3000K 9150lm 72W CRI90+ incl. driver - DALI
3000K	ZUMI 2443203229	AURYX 1080 arm 3000K 9150lm 72W CRI90+ incl. driver - CASAMBI
3500K	ZUMI2443213219	AURYX 1080 arm 3500K 9350lm 72W CRI90+ incl. driver - non dim
3500K	ZUMI2443213219D	AURYX 1080 arm 3500K 9350lm 72W CRI90+ incl. driver - DALI
3500K	ZUMI2443213229	AURYX 1080 arm 3500K 9350lm 72W CRI90+ incl. driver - CASAMBI
4000K	ZUMI2443223219	AURYX 1080 arm 4000K 9480lm 72W CRI90+ incl. driver - non dim
4000K	ZUMI2443223219D	AURYX 1080 arm 4000K 9480lm 72W CRI90+ incl. driver - DALI
4000K	ZUMI2443223229	AURYX 1080 arm 4000K 9480lm 72W CRI90+ incl. driver - CASAMBI
2700-6500K	ZUMI2443233214	AURYX 1080 arm 2700-6500K 8940lm 69W CRI90+ incl. driver - DALI DT8
2700-6500K	ZUMI2443233230	AURYX 1080 arm 2700-6500K 8940lm 69W CRI90+ incl. driver - CASAMBI

> [OPTIONS](#)

Emergency kit 3h On request