PRODUCT DESCRIPTION



The FLUUT M10 is a very small and elegant spot with M10 connector with multiple possibilities. The tube, with a diameter of about 55mm and a length of 120mm, is 359° rotable and 80° inclinable.

Aluminium luminaire.

TECHNICAL DATA

Application	On profile
Dimensions	Ø 55mm L 120mm
IP rating	IP20
Power	230V
Lifetime L70/B50/65°C	>50000h
MacAdam ellipse	3
Guarantee	5 year



Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2700K	9,5W	230V	710 lm	75 lm/W	90+	G
3000K	9,5W	230V	760 lm	80 lm/W	90+	G
4000K	9,5W	230V	810 lm	85 lm/W	90+	F

ORDER REFERENCE

> LUMINAIRE

! ORDER REFERENCE + **W** (white) / **B** (black / **C** (champagne) / **T** (titanium) / **BR** (bronze)

2700K

12°	ZUMI1052602701	Fluut M10 SLA AC G2 750lm 230V 9,5W 2700K CRI90+ 12°
24°	ZUMI1051742801	Fluut M10 SLA AC G2 710lm 230V 9,5W 2700K CRI90+ 24°
36°	ZUMI1051752901	Fluut M10 SLA AC G2 710lm 230V 9,5W 2700K CRI90+ 36°

3000K

12°	ZUMI1052612701	Fluut M10 SLA AC G2 780lm 230V 9,5W 3000K CRI90+ 12°
24°	ZUMI1051762801	Fluut M10 SLA AC G2 760lm 230V 9,5W 3000K CRI90+ 24°
36°	ZUMI1051772901	Fluut M10 SLA AC G2 760lm 230V 9,5W 3000K CRI90+ 36°

4000K

12°	ZUMI1052622701	Fluut M10 SLA AC G2 820lm 230V 9,5W 4000K CRI90+ 12°
24°	ZUMI1051782801	Fluut M10 SLA AC G2 810lm 230V 9,5W 4000K CRI90+ 24°
36°	ZUMI1051792901	Fluut M10 SLA AC G2 810lm 230V 9,5W 4000K CRI90+ 36°

> no driver needed

dimmable phase cut - see dimmerlist

PRODUCT DESCRIPTION



The FLUUT M10 is a very small and elegant spot with M10 connector with multiple possibilities. The tube, with a diameter of about 55mm and a length of 120mm, is 359° rotable and 80° inclinable.

Aluminium luminaire.

TECHNICAL DATA

Application	On profile
Dimensions	Ø 55mm L 120mm
IP rating	IP20
Power	250mA/350mA
Lifetime L70/B50/65°C	>50000h
MacAdam ellipse	3
Guarantee	5 year

(*on components, only if ordered luminaire **+ driver**)



Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2700K	8,8W	250mA	770 lm	88 lm/W	90+	G
	12,2W	350mA	1140 lm	93 lm/W	90+	G
3000K	8,8W	250mA	840 lm	95 lm/W	90+	F
	12,2W	350mA	1170 lm	96 lm/W	90+	F
4000K	8,8W	250mA	890 lm	101 lm/W	90+	F
	12,2W	350mA	1270 lm	104 lm/W	90+	F

ORDER REFERENCE

> LUMINAIRE

! ORDER REFERENCE + **W** (white) / **B** (black / **C** (champagne) / **T** (titanium) / **BR** (bronze)

2700K

700lm

24°	ZUMI1051682814	Fluut M10 SLA DC 8,8W 250mA 770 lm 2700K CRI90+ 24° excl. driver
36°	ZUMI1051692914	Fluut M10 SLA DC 8,8W 250mA 770 lm 2700K CRI90+ 36° excl. driver

1200lm

12°	ZUMI1052632706	Fluut M10 SLA DC 12,2W 350mA 1140 lm 2700K CRI90+ 12° excl. driver
24°	ZUMI1051622806	Fluut M10 SLA DC 12,2W 350mA 1140 lm 2700K CRI90+ 24° excl. driver
36°	ZUMI1051632906	Fluut M10 SLA DC 12,2W 350mA 1140 lm 2700K CRI90+ 36° excl. driver

3000K

700lm

24°	ZUMI1051702814	Fluut M10 SLA DC 8,8W 250mA 840 lm 3000K CRI90+ 24° excl. driver
36°	ZUMI1051712914	Fluut M10 SLA DC 8,8W 250mA 840 lm 3000K CRI90+ 36° excl. driver

1200lm

12°	ZUMI1052642706	Fluut M10 SLA DC 12,2W 350mA 1170 lm 3000K CRI90+ 12° excl. driver
24°	ZUMI1051642806	Fluut M10 SLA DC 12,2W 350mA 1170 lm 3000K CRI90+ 24° excl. driver
36°	ZUMI1051652906	Fluut M10 SLA DC 12,2W 350mA 1170 lm 3000K CRI90+ 36° excl. driver

4000K

700lm

24°	ZUMI1051722814	Fluut M10 SLA DC 8,8W 250mA 890 lm 4000K CRI90+ 24° excl. driver
36°	ZUMI1051732914	Fluut M10 SLA DC 8,8W 250mA 890 lm 4000K CRI90+ 36° excl. driver

1200lm

12°	ZUMI1052652706	Fluut M10 SLA DC 12,2W 350mA 1270 lm 4000K CRI90+ 12° excl. driver
24°	ZUMI1051662806	Fluut M10 SLA DC 12,2W 350mA 1270 lm 4000K CRI90+ 24° excl. driver
36°	ZUMI1051672906	Fluut M10 SLA DC 12,2W 350mA 1270 lm 4000K CRI90+ 36° excl. driver

> Driver

250mA

dimmable (to be placed remoted)

TRID87500627	LCA 15W 180-350mA flexC PH-C SR ADV (phase cut)

non dimmable

TCIL127710	MP 15 HPFU 15W 240mA

350mA

dimmable (to be placed remoted)

TRID87500627	LCA 15W 180-350mA flexC PH-C SR ADV (phase cut)

non dimmable

TCIL127710	MP 15 HPFU 15W 340mA