

PRODUCT DESCRIPTION

The PLK is a very small and elegant spot with multiple possibilities. The tube, with a diameter of about 40mm and a length of 138mm, is 359° rotatable and 80° inclinable.


This recessed wall version is perfect to be used as a bedlight.

Aluminium luminaire.



TECHNICAL DATA

Application semi - recessed
 Dimensions cut out: ø68mm (standard junction box)
 IP rating IP20
 Power 200mA
 Lifetime L70/F10/65°C >60000h
 MacAdam ellipse 3
 Guarantee 5 year
 (*on components, only if ordered luminaire + driver)



Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2700K	7,15W	200mA	864 lm	121 lm/W	90+	E
3000K	7,15W	200mA	930 lm	130 lm/W	90+	E

ORDER REFERENCE

> LUMINAIRE

! ORDER REFERENCE + W (white) / B (black) / G (gold) / T (titanium) / BR (bronze)

2700K 10°	ZUMI612243005	PLK Bed 10° SLE G7 7,15W 200mA 864lm 2700K CRI90+ ex.driver
2700K 40°	ZUMI612241205	PLK Bed 40° SLE G7 7,15W 200mA 864lm 2700K CRI90+ ex.driver
3000K 10°	ZUMI612253005	PLK Bed 10° SLE G7 7,15W 200mA 930lm 3000K CRI90+ ex.driver
3000K 40°	ZUMI612251205	PLK Bed 40° SLE G7 7,15W 200mA 930lm 3000K CRI90+ ex.driver

> DRIVER (to be placed remoted)