

PRODUCT DESCRIPTION

PLK COUPE M6 is a very small and elegant spot based on the design of the PLK but with a flat end. The tube, with a diameter of about 40mm and a length of 138mm, is 359° rotatable and 80° inclinable.


This version is perfect to be used on profiles.

Aluminium luminaire.

**TECHNICAL DATA**

Application	On profile
IP rating	IP20
Power	200mA
Lifetime L70/B50/65°C	>60000h
MacAdam ellipse	3
Guarantee	5 year

(*on components, only if ordered luminaire + driver)



Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2700K	7,15W	200mA	864lm	121 lm/W	90+	E
3000K	7,15W	200mA	930lm	130 lm/W	90+	E

ORDER REFERENCE

> LUMINAIRE

! ORDER REFERENCE + W (white) / B (black) / G (gold) / T (titanium) / BR (bronze)

2700K 10° ZUMI1472243005 PLK COUPE M6 10° SLE G7 7,15W 200mA 864lm 2700K CRI90+ ex.driver
2700K 40° ZUMI1472241205 PLK COUPE M6 40° SLE G7 7,15W 200mA 864lm 2700K CRI90+ ex.driver

3000K 10° ZUMI1472253005 PLK COUPE M6 10° SLE G7 7,15W 200mA 930lm 3000K CRI90+ ex.driver
3000K 40° ZUMI1472251205 PLK COUPE M6 40° SLE G7 7,15W 200mA 930lm 3000K CRI90+ ex.driver

> DRIVER (to be placed remoted)