PRODUCT DESCRIPTION

The PLK COUPE is a very small and elegant spot, based on the design of the PLK but with a flat end.
The tube, with a diameter of about 40mm and a length of 138mm, is 359° rotable and 80° inclinable.
It is placed on a small plate with a diameter of 50 mm. Standard equipped with tosion springs.

Aluminium luminaire available in different colors.

TECHNICAL DATA

Application	semi recessed
Dimensions	cut out: ø40mm h60mm
IP rating	IP20
Power	200mA
Lifetime L70/F10/65°C	>60000h
MacAdam ellipse	3
Guarantee	5 year

(*on components, only if ordered luminaire **+ driver**)



Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2700K	7,15W	200mA	864 lm	121 lm/W	90+	E
3000K	7,15W	200mA	930 lm	130 lm/W	90+	E

ORDER REFERENCE

> LUMINAIRE

! ORDER REFERENCE + **W** (white) / **B** (black) / **G** (gold) / **T** (titanium) / **BR** (bronze)

2700K 10°	ZUMI1482243005	PLK COUPE S 50 10° SLE G7 7,15W 200mA 864lm 2700K CRI90+ ex.driver
2700K 40°	ZUMI1482241205	PLK COUPE S 50 40° SLE G7 7,15W 200mA 864lm 2700K CRI90+ ex.driver
3000K 10°	ZUMI1482253005	PLK COUPE S 50 10° SLE G7 7,15W 200mA 930lm 3000K CRI90+ ex.driver
3000K 40°	ZUMI1482251205	PLK COUPE S 50 40° SLE G7 7,15W 200mA 930lm 3000K CRI90+ ex.driver

> DRIVER (to be placed remotely)

> OPTIONS

Flat springs	ZUMIFS	Flat springs