

PRODUCT DESCRIPTION

PLK Recessed is a very small downlighter for general or accent lighting.
The central tube with a diameter of about 40mm is placed in a ring of about 72mm.
Available in different colors and color temperatures with a lens of 10° or 40°.

Aluminium luminaire.

TECHNICAL DATA

Application	Recessed
Dimensions	cut out Ø 68mm - H 110mm
IP rating	IP20
Power	200mA
Lifetime L70/B50/65°C	>60000h
MacAdam ellipse	3
Guarantee	5 year

(*on components, only if ordered luminaire + driver)

Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2700K	7,15W	200mA	864 lm	121 lm/W	90+	E
3000K	7,15W	200mA	930 lm	130 lm/W	90+	E

ORDER REFERENCE

> LUMINAIRE

! **ORDER REFERENCE** + **W** (white) / **B** (black) / **G** (gold) / **T** (titanium) / **BR** (bronze)

2700K 10°	ZUMI1942243005	PLK Recessed 10° SLE G7 7,15W 200mA 864lm 2700K CRI90+ ex.driver
2700K 40°	ZUMI1942241205	PLK Recessed 40° SLE G7 7,15W 200mA 864lm 2700K CRI90+ ex.driver
3000K 10°	ZUMI1942253005	PLK Recessed 10° SLE G7 7,15W 200mA 930lm 3000K CRI90+ ex.driver
3000K 40°	ZUMI1942251205	PLK Recessed 40° SLE G7 7,15W 200mA 930lm 3000K CRI90+ ex.driver

> DRIVER (to be placed remoted)