PRODUCT DESCRIPTION

PLK JACK is a very small and elegant spot for general or accent lighting to be used with the ZUMI POINT.
The tube, with a diameter of about 40mm and a length of 138mm, is 359° rotable and 80° inclinable.

Aluminium luminaire.

TECHNICAL DATA

Application	Jack
IP rating	IP20
Power	200mA
Lifetime L70/B50/65°C	>60000h
MacAdam ellipse	3
Guarantee	5 year

(*on components, only if ordered luminaire **+ driver**)



Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2700K	7,15W	200mA	864 lm	121 lm/W	90+	E
3000K	7,15W	200mA	930 lm	130 lm/W	90+	E

ORDER REFERENCE

> LUMINAIRE

! ORDER REFERENCE + **W** (white) / **B** (black) / / **G** (gold) / **T** (titanium) / **BR** (bronze)

2700K 10°	ZUMI1692243005	PLK Jack 10° SLE G7 7,15W 200mA 864lm 2700K CRI90+ ex.driver
2700K 40°	ZUMI1692241205	PLK Jack 40° SLE G7 7,15W 200mA 864lm 2700K CRI90+ ex.driver
3000K 10°	ZUMI1692253005	PLK Jack 10° SLE G7 7,15W 200mA 930lm 3000K CRI90+ ex.driver
3000K 40°	ZUMI1692251205	PLK Jack 40° SLE G7 7,15W 200mA 930lm 3000K CRI90+ ex.driver

> REQUIREMENTS

ZUMIZPB	Zumipoint black cut out Ø 25mm
ZUMIZPTFCB	Zumipoint black trimless falls ceiling cut out Ø 51mm
ZUMIZPTSCB	Zumipoint black trimless strech ceiling cut out Ø

> DRIVER (to be placed remoted)