

PRODUCT DESCRIPTION

The PLK mini recessed is one of the smallest downlighters in the world for general or accent lighting. The tube has a diameter of about 35mm. Available in different colors and color temperatures with a lens of 10° or 40°.

Aluminium luminaire.

**TECHNICAL DATA**

Application	Recessed
Dimensions	cut out Ø 32mm - H 75mm
IP rating	IP20
Power	350mA
Lifetime L70/B50/65°C	>60000h
MacAdam ellipse	3
Guarantee	5 year

(*on components, only if ordered luminaire + **driver**)

Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2700K	2,8W	350 mA	322lm	115 lm/W	90+	E
3000K	2,8W	350 mA	339lm	121 lm/W	90+	E

ORDER REFERENCE

> [LUMINAIRE](#)

! ORDER REFERENCE + (1) W (white) / B (black) // G (gold) / T (titanium) / BR (bronze)

2700K 10°	ZUMI2062823006	PLK Mini recessed 10° 2,8W 350mA 322lm 2700K CRI90+ ex.driver
2700K 40°	ZUMI2062821206	PLK Mini recessed 40° 2,8W 350mA 322lm 2700K CRI90+ ex.driver
3000K 10°	ZUMI2062893006	PLK Mini recessed 10° 2,8W 350mA 339lm 3000K CRI90+ ex.driver
3000K 40°	ZUMI2062891206	PLK Mini recessed 40° 2,8W 350mA 339lm 3000K CRI90+ ex.driver

> [DRIVER \(to be placed remotely\)](#)