PRODUCT DESCRIPTION

The PLK is a very small and elegant spot with multiple possibilities. The tube, with a diameter of about 40mm and a length of 138mm, is 359° rotable and 80° inclinable.

In this recessed version the PLK is slightly sunken in the ceiling which gives it an extra dimension. Perfectly combinable with the Rori or Rova Deep spot.

Aluminium luminaire. Standard equipped with torsion springs.

TECHNICAL DATA

Application	semi - recessed
Dimensions	cut out: **torsion** springs: ø86mm h60mm **flat** springs: ø83mm h60mm
IP rating	IP20
Power	200mA
Lifetime L70/F10/65°C	>60000h
MacAdam ellipse	3
Guarantee	5 year

(*on components, only if ordered luminaire **+ driver**)



Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2700K	7,15W	200mA	864 lm	121 lm/W	90+	E
3000K	7,15W	200mA	930 lm	130 lm/W	90+	E

ORDER REFERENCE

> LUMINAIRE

! ORDER REFERENCE + **W** (white) / **B** (black) / **G** (gold) / **T** (titanium) / **BR** (bronze)

2700K 10°	ZUMI472243005	PLK R 10° SLE G7 7,15W 200mA 864lm 2700K CRI90+ ex.driver
2700K 40°	ZUMI472241205	PLK R 40° SLE G7 7,15W 200mA 864lm 2700K CRI90+ ex.driver
3000K 10°	ZUMI472253005	PLK R 10° SLE G7 7,15W 200mA 930lm 3000K CRI90+ ex.driver
3000K 40°	ZUMI472251205	PLK R 40° SLE G7 7,15W 200mA 930lm 3000K CRI90+ ex.driver

> DRIVER

dimmable (Dali, switchDIM)
TRID28000673 + TRID28001168 + TRID28001104
LCA 10W 150–400mA one4all SC PRE + Strain-relief + Plug 200mA

non dimmable
TRID28000704 + TRID28001168 + TRID28001104
LC 10W 150-400mA flexC SC EXC + Strain-relief + Plug 200mA

> OPTIONS

Flat Springs
ZUMIFS Flat Springs