PRODUCT DESCRIPTION

The PLK is a very small and elegant spot with multiple possibilities. The tube, with a diameter of about 40mm and a length of 138mm, is 359° rotable and 80° inclinable.
It is asymmetricly placed on a plate with a diameter of 147 mm, available with torsion and flat springs.

Aluminium luminaire. Standard equipped with torsion springs.

TECHNICAL DATA

Application	semi - recessed
Dimensions	cut out: ø 80mm h60mm
IP rating	IP20
Power	200mA
Lifetime L70/F10/65°C	>60000h
MacAdam ellipse	3
Guarantee	5 year

(*on components, only if ordered luminaire **+ driver**)



Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2700K	7,15W	200mA	864 lm	121 lm/W	90+	E
3000K	7,15W	200mA	930 lm	130 lm/W	90+	E

ORDER REFERENCE

> LUMINAIRE

! ORDER REFERENCE + **W** (white) / **B** (black) / **G** (gold) / **T** (titanium) / **BR** (bronze)

2700K 10°	ZUMI452243005	PLK S 147 Single 10° SLE G7 7,15W 200mA 864lm 2700K CRI90+ ex.driver
2700K 40°	ZUMI452241205	PLK S 147 Single 40° SLE G7 7,15W 200mA 864lm 2700K CRI90+ ex.driver
3000K 10°	ZUMI452253005	PLK S 147 Single 10° SLE G7 7,15W 200mA 930lm 3000K CRI90+ ex.driver
3000K 40°	ZUMI452251205	PLK S 147 Single 40° SLE G7 7,15W 200mA 930lm 3000K CRI90+ ex.driver

> DRIVER

dimmable (Dali, switchDIM)
TRID28000673 + TRID28001168 + TRID28001104
LCA 10W 150–400mA one4all SC PRE + Strain-relief + Plug 200mA

non dimmable
TRID28000704 + TRID28001168 + TRID28001104
LC 10W 150-400mA flexC SC EXC + Strain-relief + Plug 200mA

> OPTIONS

Flat Springs
ZUMIFS Flat Springs