

PRODUCT DESCRIPTION

PLK Recessed telescopic is a very small downlighter for general or accent lighting. The central tube with a diameter of about 40mm is placed in a ring of about 72mm. The Tube is extendable and 359° orientable. Available in different colors and color temperatures with a lens of 10° or 40°.

Aluminium luminaire.

TECHNICAL DATA

Application	Recessed
Dimensions	cut out Ø 68mm - H 125mm
IP rating	IP20
Power	200mA
Lifetime L70/B50/65°C	>60000h
MacAdam ellipse	3
Guarantee	5 year

(*on components, only if ordered luminaire **± driver**)

Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2700K	7,15W	200mA	864 lm	121 lm/W	90+	E
3000K	7,15W	200mA	930 lm	130 lm/W	90+	E

ORDER REFERENCE

> LUMINAIRE

! ORDER REFERENCE + W (white) / B (black) / G (gold) / T (titanium) / BR (bronze)

2700K 10°	ZUMI1952243005	PLK Recessed Telescopic 10° SLE G7 7,15W 200mA 864lm 2700K CRI90+ ex.driver
2700K 40°	ZUMI1952241205	PLK Recessed Telescopic 40° SLE G7 7,15W 200mA 864lm 2700K CRI90+ ex.driver
3000K 10°	ZUMI1952253005	PLK Recessed Telescopic 10° SLE G7 7,15W 200mA 930lm 3000K CRI90+ ex.driver
3000K 40°	ZUMI1952251205	PLK Recessed Telescopic 40° SLE G7 7,15W 200mA 930lm 3000K CRI90+ ex.driver

> DRIVER (to be placed remoted)