



**PRODUCT DESCRIPTION**

Fixed recessed downlighter for general or accent lighting.  
Aluminium luminaire, provided with a LEDmodule which replaces the MR16 halogen.  
Available in 2700, 3000 & 4000K, in low output (250mA) or high output (350mA).

**TECHNICAL DATA**

Application	recessed
Dimensions	cut out: <b>torsion</b> springs: ø86mm h100mm <b>flat</b> springs: ø83mm h100mm
IP rating	IP20
Power	250/350mA
Lifetime L70/B50/65°C	>50000h
MacAdam ellipse	3
Guarantee	5 year

(\*on components, only if ordered luminaire + **driver**)



Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2700K	8,8W	250mA	770 lm	88 lm/W	90+	G
	12,2W	350mA	1140 lm	93 lm/W	90+	G
3000K	8,8W	250mA	840 lm	95 lm/W	90+	F
	12,2W	350mA	1170 lm	96 lm/W	90+	F
4000K	8,8W	250mA	890 lm	101 lm/W	90+	F
	12,2W	350mA	1270 lm	104 lm/W	90+	F

**ORDER REFERENCE**

> [LUMINAIRE](#)

**ORDER REFERENCE + W (white) / B (black)**

**2700K**

700lm

<b>24°</b>	ZUMI371682814	Rova 700 DC 8,8W 250mA 770 lm 2700K CRI90 24° excl. driver
<b>36°</b>	ZUMI371692914	Rova 700 DC 8,8W 250mA 770 lm 2700K CRI90 36° excl. driver

1200lm

<b>12°</b>	ZUMI372632706	Rova 1200 DC 12,2W 350mA 970 lm 2700K CRI90 12° excl. driver
<b>24°</b>	ZUMI371622806	Rova 1200 DC 12,2W 350mA 1140 lm 2700K CRI90 24° excl. driver
<b>36°</b>	ZUMI371632906	Rova 1200 DC 12,2W 350mA 1140 lm 2700K CRI90 36° excl. driver

**3000K**

700lm

<b>24°</b>	ZUMI371702814	Rova 700 DC 8,8W 250mA 840 lm 3000K CRI90 24° excl. driver
<b>36°</b>	ZUMI371712914	Rova 700 DC 8,8W 250mA 840 lm 3000K CRI90 36° excl. driver

1200lm

<b>12°</b>	ZUMI372642706	Rova 1200 DC 12,2W 350mA 1040 lm 3000K CRI90 12° excl. driver
<b>24°</b>	ZUMI371642806	Rova 1200 DC 12,2W 350mA 1170 lm 3000K CRI90 24° excl. driver
<b>36°</b>	ZUMI371652906	Rova 1200 DC 12,2W 350mA 1170 lm 3000K CRI90 36° excl. driver

**4000K**

700lm

<b>24°</b>	ZUMI371722814	Rova 700 DC 8,8W 250mA 890 lm 4000K CRI90 24° excl. driver
<b>36°</b>	ZUMI371732914	Rova 700 DC 8,8W 250mA 890 lm 4000K CRI90 36° excl. driver

1200lm

<b>12°</b>	ZUMI372652706	Rova 1200 DC 12,2W 350mA 1130 lm 4000K CRI90 12° excl. driver
<b>24°</b>	ZUMI371662806	Rova 1200 DC 12,2W 350mA 1270 lm 4000K CRI90 24° excl. driver
<b>36°</b>	ZUMI371672906	Rova 1200 DC 12,2W 350mA 1270 lm 4000K CRI90 36° excl. driver

> DRIVER*250mA***dimmable**

TRID87500627

LCA 15W 180-350mA flexC PH-C SR ADV (phase cut)

*or* TRID28000669 + PLUG TRID28001106

LCA 10W 150-400mA one4all SR PRE (DALI, pushDIM)

**non dimmable**

TRID87500580

LC 10W 250mA fixC SR SNC

*350mA***dimmable**

TRID87500627

LCA 15W 180-350mA flexC PH-C SR ADV (phase cut)

*or* TRID28000670 + PLUG TRID28001110

LCA 17W 250-700mA one4all SR PRE (DALI, pushDIM)

**non dimmable**

TRID28000699

LC 17W 250-700mA flexC SR EX

> OPTIONS**Flat Springs**

ZUMIFS

Flat Springs

**PRODUCT DESCRIPTION**



Adjustable recessed downlighter for general or accent lighting.  
 Aluminium luminaire, provided with a LEDmodule which replaces the MR16 halogen spotlight.  
 Available in 2700, 3000 & 4000K, in low output (250mA) or high output (350mA).



**TECHNICAL DATA**

Application	recessed
Dimensions	cut out: <b>torsion</b> springs: ø86mm h100mm <b>flat</b> springs: ø83mm h100mm
IP rating	IP20
Power	250/350mA
Lifetime L70/B50/65°C	>50000h
MacAdam ellipse	3
Guarantee	5 year

(\*on components, only if ordered luminaire + **driver**)



Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2700K	8,8W	250mA	770 lm	88 lm/W	90+	G
	12,2W	350mA	1140 lm	93 lm/W	90+	G
3000K	8,8W	250mA	840 lm	95 lm/W	90+	F
	12,2W	350mA	1170 lm	96 lm/W	90+	F
4000K	8,8W	250mA	890 lm	101 lm/W	90+	F
	12,2W	350mA	1270 lm	104 lm/W	90+	F

**ORDER REFERENCE**

> LUMINAIRE

**ORDER REFERENCE + W (white) / B (black)**

**2700K**

700lm

**24°** ZUMI381682814 Rori 700 DC 8,8W 250mA 770 lm 2700K CRI90 24° excl. driver  
**36°** ZUMI381692914 Rori 700 DC 8,8W 250mA 770 lm 2700K CRI90 36° excl. driver

1200lm

**12°** ZUMI382632706 Rori 1200 DC 12,2W 350mA 970 lm 2700K CRI90 12° excl. driver  
**24°** ZUMI381622806 Rori 1200 DC 12,2W 350mA 1140 lm 2700K CRI90 24° excl. driver  
**36°** ZUMI381632906 Rori 1200 DC 12,2W 350mA 1140 lm 2700K CRI90 36° excl. driver

**3000K**

700lm

**24°** ZUMI381702814 Rori 700 DC 8,8W 250mA 840 lm 3000K CRI90 24° excl. driver  
**36°** ZUMI381712914 Rori 700 DC 8,8W 250mA 840 lm 3000K CRI90 36° excl. driver

1200lm

**12°** ZUMI382642706 Rori 1200 DC 12,2W 350mA 1040 lm 3000K CRI90 12° excl. driver  
**24°** ZUMI381642806 Rori 1200 DC 12,2W 350mA 1170 lm 3000K CRI90 24° excl. driver  
**36°** ZUMI381652906 Rori 1200 DC 12,2W 350mA 1170 lm 3000K CRI90 36° excl. driver

**4000K**

700lm

**24°** ZUMI381722814 Rori 700 DC 8,8W 250mA 890 lm 4000K CRI90 24° excl. driver  
**36°** ZUMI381732914 Rori 700 DC 8,8W 250mA 890 lm 4000K CRI90 36° excl. driver

1200lm

**12°** ZUMI382652706 Rori 1200 DC 12,2W 350mA 1130 lm 4000K CRI90 12° excl. driver  
**24°** ZUMI381662806 Rori 1200 DC 12,2W 350mA 1270 lm 4000K CRI90 24° excl. driver  
**36°** ZUMI381672906 Rori 1200 DC 12,2W 350mA 1270 lm 4000K CRI90 36° excl. driver

> DRIVER

250mA

**dimmable**

TRID87500627

LCA 15W 180-350mA flexC PH-C SR ADV (phase cut)

or TRID28000669 + PLUG TRID28001106

LCA 10W 150-400mA one4all SR PRE (DALI, pushDIM)

**non dimmable**

TRID87500580

LC 10W 250mA fixC SR SNC

350mA

**dimmable**

TRID87500627

LCA 15W 180-350mA flexC PH-C SR ADV (phase cut)

or TRID28000670 + PLUG TRID28001110

LCA 17W 250-700mA one4all SR PRE (DALI, pushDIM)

**non dimmable**

TRID28000699

LC 17W 250-700mA flexC SR EX

> OPTIONS**Flat Springs**

ZUMIFS


Flat Springs

**PRODUCT DESCRIPTION**

Fixed recessed downlighter for general or accent lighting.  
Aluminium luminaire, provided with a LEDmodule which replaces the GU10 halogen spotlight.  
Available in 2700, 3000 and 4000K.

**TECHNICAL DATA**

Application	recessed
Dimensions	cut out: <b>torsion</b> springs: ø86mm h110mm <b>flat</b> springs: ø83mm h110mm
IP rating	IP20
Power	230V
Lifetime L70/B50/75°C	>50000h
MacAdam ellipse	3
Guarantee	5 year



Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2700K	9,5W	230V	710 lm	75 lm/W	90+	G
3000K	9,5W	230V	760 lm	80 lm/W	90+	G
4000K	9,5W	230V	810 lm	85 lm/W	90+	F

**ORDER REFERENCE**

> [LUMINAIRE](#)

**ORDER REFERENCE + W (white) / B (black)**

**2700K**

<b>12°</b>	ZUMI372602701	Rova AC 9,5W 230V 710lm 2700K CRI90 12°
<b>24°</b>	ZUMI371742801	Rova AC 9,5W 230V 710lm 2700K CRI90 24°
<b>36°</b>	ZUMI371752901	Rova AC 9,5W 230V 710lm 2700K CRI90 36°

**3000K**

<b>12°</b>	ZUMI372612701	Rova AC 9,5W 230V 760lm 3000K CRI90 12°
<b>24°</b>	ZUMI371762801	Rova AC 9,5W 230V 760lm 3000K CRI90 24°
<b>36°</b>	ZUMI371772901	Rova AC 9,5W 230V 760lm 3000K CRI90 36°

**4000K**

<b>12°</b>	ZUMI372622701	Rova AC 9,5W 230V 810lm 4000K CRI90 12°
<b>24°</b>	ZUMI371782801	Rova AC 9,5W 230V 810lm 4000K CRI90 24°
<b>36°</b>	ZUMI371792901	Rova AC 9,5W 230V 810lm 4000K CRI90 36°

> [no driver needed](#)


dimnable phase cut- see dimmerlist

**PRODUCT DESCRIPTION**

Adjustable recessed downlighter for general or accent lighting.  
Aluminium luminaire, provided with a LEDmodule which replaces the GU10 halogen spotlight.  
Available in 2700, 3000 and 4000K.

**TECHNICAL DATA**

Application	recessed
Dimensions	cut out: <b>torsion</b> springs: ø86mm h110mm <b>flat</b> springs: ø83mm h110mm
IP rating	IP20
Power	230V
Lifetime L70/B50/75°C	>50000h
MacAdam ellipse	3
Guarantee	5 year



Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2700K	9,5W	230V	710 lm	75 lm/W	90+	G
3000K	9,5W	230V	760 lm	80 lm/W	90+	G
4000K	9,5W	230V	810 lm	85 lm/W	90+	F

**ORDER REFERENCE**

> [LUMINAIRE](#)

**ORDER REFERENCE + W (white) / B (black)**

**G (gold) on request**

**2700K**

<b>12°</b>	ZUMI382602701	Rori AC 9,5W 230V 710 lm 2700K CRI90 12°
<b>24°</b>	ZUMI381742801	Rori AC 9,5W 230V 710 lm 2700K CRI90 24°
<b>36°</b>	ZUMI381752901	Rori AC 9,5W 230V 710 lm 2700K CRI90 36°

**3000K**

<b>12°</b>	ZUMI382612701	Rori AC 9,5W 230V 760 lm 3000K CRI90 12°
<b>24°</b>	ZUMI381762801	Rori AC 9,5W 230V 760 lm 3000K CRI90 24°
<b>36°</b>	ZUMI381772901	Rori AC 9,5W 230V 760 lm 3000K CRI90 36°

**4000K**

<b>12°</b>	ZUMI382622701	Rori AC 9,5W 230V 810 lm 4000K CRI90 12°
<b>24°</b>	ZUMI381782801	Rori AC 9,5W 230V 810 lm 4000K CRI90 24°
<b>36°</b>	ZUMI381792901	Rori AC 9,5W 230V 810 lm 4000K CRI90 36°

> [no driver needed](#)

dimnable phase cut- see dimmerlist

**PRODUCT DESCRIPTION**

Fixed recessed downlighter for general or accent lighting. Similar to the ROVA spot, but with a light-source that is placed 'deeper' into the fixture which makes it a more subtle downlighter.



Aluminium luminaire, provided with a LEDmodule which replaces the MR16 halogen spotlight. Available in 2700, 3000 & 4000K, in low output (250mA) or high output (350mA).



**TECHNICAL DATA**

Application	recessed
Dimensions	cut out: <b>torsion</b> springs: ø86mm h120mm <b>flat</b> springs: ø83mm h120mm
IP rating	IP20
Power	250/350mA
Lifetime L70/B50/65°C	>50000h
MacAdam ellipse	3
Guarantee	5 year

(\*on components, only if ordered luminaire + **driver**)



Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2700K	8,8W	250mA	770 lm	88 lm/W	90+	G
	12,2W	350mA	1140 lm	93 lm/W	90+	G
3000K	8,8W	250mA	840 lm	95 lm/W	90+	F
	12,2W	350mA	1170 lm	96 lm/W	90+	F
4000K	8,8W	250mA	890 lm	101 lm/W	90+	F
	12,2W	350mA	1270 lm	104 lm/W	90+	F

**ORDER REFERENCE**

> LUMINAIRE

**ORDER REFERENCE + W (white) / B (black)**

**2700K**

700lm

<b>24°</b>	ZUMI601682814	Rova Deep 700 DC 8,8W 250mA 770 lm 2700K CRI90 24° excl. driver
<b>36°</b>	ZUMI601692914	Rova Deep 700 DC 8,8W 250mA 770 lm 2700K CRI90 36° excl. driver

1200lm

<b>12°</b>	ZUMI602632706	Rova Deep 1200 DC 12,2W 350mA 970 lm 2700K CRI90 12° excl. driver
<b>24°</b>	ZUMI601622806	Rova Deep 1200 DC 12,2W 350mA 1140 lm 2700K CRI90 24° excl. driver
<b>36°</b>	ZUMI601632906	Rova Deep 1200 DC 12,2W 350mA 1140 lm 2700K CRI90 36° excl. driver

**3000K**

700lm

<b>24°</b>	ZUMI601702814	Rova Deep 700 DC 8,8W 250mA 770 lm 3000K CRI90 24° excl. driver
<b>36°</b>	ZUMI601712914	Rova Deep 700 DC 8,8W 250mA 770 lm 3000K CRI90 36° excl. driver

1200lm

<b>12°</b>	ZUMI602642706	Rova Deep 1200 DC 12,2W 350mA 1040 lm 3000K CRI90 12° excl. driver
<b>24°</b>	ZUMI601642806	Rova Deep 1200 DC 12,2W 350mA 1170 lm 3000K CRI90 24° excl. driver
<b>36°</b>	ZUMI601652906	Rova Deep 1200 DC 12,2W 350mA 1170 lm 3000K CRI90 36° excl. driver

**4000K**

700lm

<b>24°</b>	ZUMI601722814	Rova Deep 700 DC 8,8W 250mA 770 lm 4000K CRI90 24° excl. driver
<b>36°</b>	ZUMI601732914	Rova Deep 700 DC 8,8W 250mA 770 lm 4000K CRI90 36° excl. driver

1200lm

<b>12°</b>	ZUMI602652706	Rova Deep 1200 DC 12,2W 350mA 1130 lm 4000K CRI90 12° excl. driver
<b>24°</b>	ZUMI601662806	Rova Deep 1200 DC 12,2W 350mA 1270 lm 4000K CRI90 24° excl. driver
<b>36°</b>	ZUMI601672906	Rova Deep 1200 DC 12,2W 350mA 1270 lm 4000K CRI90 36° excl. driver

> DRIVER

250mA

**dimmable**

TRID87500627 LCA 15W 180-350mA flexC PH-C SR ADV (phase cut)  
or TRID28000669 + PLUG TRID28001106 LCA 10W 150-400mA one4all SR PRE (DALI, pushDIM)

**non dimmable**

TRID87500580 LC 10W 250mA fixC SR SNC

350mA

**dimmable**

TRID87500627 LCA 15W 180-350mA flexC PH-C SR ADV (phase cut)  
or TRID28000670 + PLUG TRID28001110 LCA 17W 250-700mA one4all SR PRE (DALI, pushDIM)

**non dimmable**

TRID28000699 LC 17W 250-700mA flexC SR EX

> OPTIONS**Flat Springs**

ZUMIFS Flat Springs

**PRODUCT DESCRIPTION**



Adjustable recessed downlighter for general or accent lighting. Similar to the RORI spot, but with a light source that is placed 'deeper' into the fixture which makes it a more subtle downlighter.

Aluminium luminaire, provided with a LEDmodule which replaces the MR16 halogen spotlight. Available in 2700, 3000 & 4000K, in low output (250mA) or high output (350mA).



**TECHNICAL DATA**

Application: recessed  
 Dimensions: cut out: **torsion** springs: ø86mm h120mm  
**flat** springs: ø83mm h120mm  
 IP rating: IP20  
 Power: 250/350mA  
 Lifetime L70/B50/65°C: >50000h  
 MacAdam ellipse: 3  
 Guarantee: 5 year  
 (\*on components, only if ordered luminaire + **driver**)



Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2700K	8,8W	250mA	770 lm	88 lm/W	90+	G
	12,2W	350mA	1140 lm	93 lm/W	90+	G
3000K	8,8W	250mA	840 lm	95 lm/W	90+	F
	12,2W	350mA	1170 lm	96 lm/W	90+	F
4000K	8,8W	250mA	890 lm	101 lm/W	90+	F
	12,2W	350mA	1270 lm	104 lm/W	90+	F

**ORDER REFERENCE**

> [LUMINAIRE](#)

**ORDER REFERENCE + W (white) / B (black)**

**2700K**

700lm

24° ZUMI591682814 Rori Deep 700 DC 8,8W 250mA 770 lm 2700K CRI90 24° excl. driver  
 36° ZUMI591692914 Rori Deep 700 DC 8,8W 250mA 770 lm 2700K CRI90 36° excl. driver

1200lm

12° ZUMI592632706 Rori Deep 1200 DC 12,2W 350mA 970 lm 2700K CRI90 12° excl. driver  
 24° ZUMI591622806 Rori Deep 1200 DC 12,2W 350mA 1140 lm 2700K CRI90 24° excl. driver  
 36° ZUMI591632906 Rori Deep 1200 DC 12,2W 350mA 1140 lm 2700K CRI90 36° excl. driver

**3000K**

700lm

24° ZUMI591702814 Rori Deep 700 DC 8,8W 250mA 840 lm 3000K CRI90 24° excl. driver  
 36° ZUMI591712914 Rori Deep 700 DC 8,8W 250mA 840 lm 3000K CRI90 36° excl. driver

1200lm

12° ZUMI592642706 Rori Deep 1200 DC 12,2W 350mA 1040 lm 3000K CRI90 12° excl. driver  
 24° ZUMI591642806 Rori Deep 1200 DC 12,2W 350mA 1170 lm 3000K CRI90 24° excl. driver  
 36° ZUMI591652906 Rori Deep 1200 DC 12,2W 350mA 1170 lm 3000K CRI90 36° excl. driver

**4000K**

700lm

24° ZUMI591722814 Rori Deep 700 DC 8,8W 250mA 890 lm 4000K CRI90 24° excl. driver  
 36° ZUMI591732914 Rori Deep 700 DC 8,8W 250mA 890 lm 4000K CRI90 36° excl. driver

1200lm

12° ZUMI592652706 Rori Deep 1200 DC 12,2W 350mA 1130 lm 4000K CRI90 12° excl. driver  
 24° ZUMI591662806 Rori Deep 1200 DC 12,2W 350mA 1270 lm 4000K CRI90 24° excl. driver  
 36° ZUMI591672906 Rori Deep 1200 DC 12,2W 350mA 1270 lm 4000K CRI90 36° excl. driver

> DRIVER

250mA

**dimmable**

TRID87500627

LCA 15W 180-350mA flexC PH-C SR ADV (phase cut)

or TRID28000669 + PLUG TRID28001106

LCA 10W 150-400mA one4all SR PRE (DALI, pushDIM)

**non dimmable**

TRID87500580

LC 10W 250mA fixC SR SNC

350mA

**dimmable**

TRID87500627

LCA 15W 180-350mA flexC PH-C SR ADV (phase cut)

or TRID28000670 + PLUG TRID28001110

LCA 17W 250-700mA one4all SR PRE (DALI, pushDIM)

**non dimmable**

TRID28000699

LC 17W 250-700mA flexC SR EX

> OPTIONS**Flat Springs**

ZUMIFS

Flat Springs


**PRODUCT DESCRIPTION**

Fixed recessed downlighter for general or accent lighting. Similar to the ROVA spot, but with a light-source that is placed 'deeper' into the fixture which makes it a more subtle downlighter.

Aluminium luminaire, provided with a LEDmodule which replaces the GU10 halogen spotlight. Available in 2700, 3000 and 4000K.

**TECHNICAL DATA**

Application	recessed
Dimensions	cut out: <b>torsion</b> springs: ø86mm h125mm <b>flat</b> springs: ø83mm h125mm
IP rating	IP20
Power	230V
Lifetime L70/B50/75°C	>50000h
MacAdam ellipse	3
Guarantee	5 year



Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2700K	9,5W	230V	710 lm	75 lm/W	90+	G
3000K	9,5W	230V	760 lm	80 lm/W	90+	G
4000K	9,5W	230V	810 lm	85 lm/W	90+	F

**ORDER REFERENCE**

> [LUMINAIRE](#)

**ORDER REFERENCE + W (white) / B (black)**

**G (gold) on request**

**2700K**

<b>12°</b>	ZUMI602602701	Rova Deep AC 9,5W 230V 710 lm 2700K CRI90 12°
<b>24°</b>	ZUMI601742801	Rova Deep AC 9,5W 230V 710 lm 2700K CRI90 24°
<b>36°</b>	ZUMI601752901	Rova Deep AC 9,5W 230V 710 lm 2700K CRI90 36°

**3000K**

<b>12°</b>	ZUMI602612701	Rova Deep AC 9,5W 230V 760 lm 3000K CRI90 12°
<b>24°</b>	ZUMI601762801	Rova Deep AC 9,5W 230V 760 lm 3000K CRI90 24°
<b>36°</b>	ZUMI601772901	Rova Deep AC 9,5W 230V 760 lm 3000K CRI90 36°

**4000K**

<b>12°</b>	ZUMI602622701	Rova Deep AC 9,5W 230V 810 lm 4000K CRI90 12°
<b>24°</b>	ZUMI601782801	Rova Deep AC 9,5W 230V 810 lm 4000K CRI90 24°
<b>36°</b>	ZUMI601792901	Rova Deep AC 9,5W 230V 810 lm 4000K CRI90 36°

> [no driver needed](#)

dimnable phase cut- see dimmerlist


**PRODUCT DESCRIPTION**

Adjustable recessed downlighter for general or accent lighting. Similar to the ROVA spot, but with a lightsource that is placed 'deeper' into the fixture which makes it a more subtle downlighter.

Aluminium luminaire, provided with a LEDmodule which replaces the GU10 halogen spotlight. Available in 2700, 3000 and 4000K.

**TECHNICAL DATA**

Application	recessed
Dimensions	cut out: <b>torsion</b> springs: ø86mm h125mm <b>flat</b> springs: ø83mm h125mm
IP rating	IP20
Power	230V
Lifetime L70/B50/75°C	>50000h
MacAdam ellipse	3
Guarantee	5 year



Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2700K	9,5W	230V	710 lm	75 lm/W	90+	G
3000K	9,5W	230V	760 lm	80 lm/W	90+	G
4000K	9,5W	230V	810 lm	85 lm/W	90+	F

**ORDER REFERENCE**

> [LUMINAIRE](#)

**ORDER REFERENCE + W (white) / B (black)**

**G (gold) on request**

**2700K**

<b>12°</b>	ZUMI592602701	Rori Deep AC 9,5W 230V 710 lm 2700K CRI90 12°
<b>24°</b>	ZUMI591742801	Rori Deep AC 9,5W 230V 710 lm 2700K CRI90 24°
<b>36°</b>	ZUMI591752901	Rori Deep AC 9,5W 230V 710 lm 2700K CRI90 36°

**3000K**

<b>12°</b>	ZUMI592612701	Rori Deep AC 9,5W 230V 760 lm 3000K CRI90 12°
<b>24°</b>	ZUMI591762801	Rori Deep AC 9,5W 230V 760 lm 3000K CRI90 24°
<b>36°</b>	ZUMI591772901	Rori Deep AC 9,5W 230V 760 lm 3000K CRI90 36°

**4000K**

<b>12°</b>	ZUMI592622701	Rori Deep AC 9,5W 230V 810 lm 4000K CRI90 12°
<b>24°</b>	ZUMI591782801	Rori Deep AC 9,5W 230V 810 lm 4000K CRI90 24°
<b>36°</b>	ZUMI591792901	Rori Deep AC 9,5W 230V 810 lm 4000K CRI90 36°

> [no driver needed](#)

dimnable phase cut- see dimmerlist