

**PRODUCT DESCRIPTION**


Trimless Single Downlighter for general or accent lighting. Available in a version for stretch ceiling and false ceiling.

Aluminium luminaire in several colors and color temperatures with several possible reflectors.

**TECHNICAL DATA**

Application	Recessed
Dimensions	visible dimensions: 154x154mm Tubb: ø80mm h80mm
IP rating	IP20
Power	350mA / 500mA
Lifetime L70/F10/65°C	>55000h
MacAdam ellipse	3
Guarantee	5 year

(\*on components, only if ordered luminaire **+driver**)



Color Temperature	Wattage excl. driver	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2700K	11,8W	350mA	1558 lm	134 lm/W	90+	E
	16,9W	500mA	2225 lm	134 lm/W	90+	E
3000K	11,8W	350mA	1714 lm	147 lm/W	90+	E
	16,9W	500mA	2449 lm	147 lm/W	90+	E
3500K	11,8W	350mA	1732 lm	149 lm/W	90+	E
	16,9W	500mA	2474 lm	149 lm/W	90+	E
4000K	11,8W	350mA	1775 lm	152 lm/W	90+	E
	16,9W	500mA	2536 lm	152 lm/W	90+	E

**ORDER REFERENCE**

> LUMINAIRE

**! ORDER REFERENCE** + (1) **W** (white) / **B** (black)  
+ (2) **G** (gold reflector) option only for 2700K or 3000K

**STRETCH CEILING****2700K**

14°	ZUMI732132317	Tubb Trimless Single SC CRI90+ SLE G7 11,8/16,9W 350/500mA 1558/2225 lm 2700K 14° glass excl. driver
25°	ZUMI732132417	Tubb Trimless Single SC CRI90+ SLE G7 11,8/16,9W 350/500mA 1558/2225 lm 2700K 25° glass excl. driver
39°	ZUMI732132517	Tubb Trimless Single SC CRI90+ SLE G7 11,8/16,9W 350/500mA 1558/2225 lm 2700K 39° glass excl. driver
61°	ZUMI732132617	Tubb Trimless Single SC CRI90+ SLE G7 11,8/16,9W 350/500mA 1558/2225 lm 2700K 61° glass excl. driver

**3000K**

14°	ZUMI732142317	Tubb Trimless Single SC CRI90+ SLE G7 11,8/16,9W 350/500mA 1714/2449 lm 3000K 14° glass excl. driver
25°	ZUMI732142417	Tubb Trimless Single SC CRI90+ SLE G7 11,8/16,9W 350/500mA 1714/2449 lm 3000K 25° glass excl. driver
39°	ZUMI732142517	Tubb Trimless Single SC CRI90+ SLE G7 11,8/16,9W 350/500mA 1714/2449 lm 3000K 39° glass excl. driver
61°	ZUMI732142617	Tubb Trimless Single SC CRI90+ SLE G7 11,8/16,9W 350/500mA 1714/2449 lm 3000K 61° glass excl. driver

**3500K**

14°	ZUMI732152317	Tubb Trimless Single SC CRI90+ SLE G7 11,8/16,9W 350/500mA 1732/2474 lm 3500K 14° glass excl. driver
25°	ZUMI732152417	Tubb Trimless Single SC CRI90+ SLE G7 11,8/16,9W 350/500mA 1732/2474 lm 3500K 25° glass excl. driver
39°	ZUMI732152517	Tubb Trimless Single SC CRI90+ SLE G7 11,8/16,9W 350/500mA 1732/2474 lm 3500K 39° glass excl. driver
61°	ZUMI732152617	Tubb Trimless Single SC CRI90+ SLE G7 11,8/16,9W 350/500mA 1732/2474 lm 3500K 61° glass excl. driver

**4000K**

14°	ZUMI732162317	Tubb Trimless Single SC CRI90+ SLE G7 11,8/16,9W 350/500mA 1775/2536 lm 4000K 14° glass excl. driver
25°	ZUMI732162417	Tubb Trimless Single SC CRI90+ SLE G7 11,8/16,9W 350/500mA 1775/2536 lm 4000K 25° glass excl. driver
39°	ZUMI732162517	Tubb Trimless Single SC CRI90+ SLE G7 11,8/16,9W 350/500mA 1775/2536 lm 4000K 39° glass excl. driver
61°	ZUMI732162617	Tubb Trimless Single SC CRI90+ SLE G7 11,8/16,9W 350/500mA 1775/2536 lm 4000K 61° glass excl. driver

*FALSE CEILING -recessed kit to be ordered separately !*

**2700K**

14°	ZUMI742132317	Tubb Trimless Single FC CRI90+ SLE G7 11,8/16,9W 350/500mA 1558/2225 lm 2700K 14° glass excl. driver
25°	ZUMI742132417	Tubb Trimless Single FC CRI90+ SLE G7 11,8/16,9W 350/500mA 1558/2225 lm 2700K 25° glass excl. driver
39°	ZUMI742132517	Tubb Trimless Single FC CRI90+ SLE G7 11,8/16,9W 350/500mA 1558/2225 lm 2700K 39° glass excl. driver
61°	ZUMI742132617	Tubb Trimless Single FC CRI90+ SLE G7 11,8/16,9W 350/500mA 1558/2225 lm 2700K 61° glass excl. driver

**3000K**

14°	ZUMI742142317	Tubb Trimless Single FC CRI90+ SLE G7 11,8/16,9W 350/500mA 1714/2449 lm 3000K 14° glass excl. driver
25°	ZUMI742142417	Tubb Trimless Single FC CRI90+ SLE G7 11,8/16,9W 350/500mA 1714/2449 lm 3000K 25° glass excl. driver
39°	ZUMI742142517	Tubb Trimless Single FC CRI90+ SLE G7 11,8/16,9W 350/500mA 1714/2449 lm 3000K 39° glass excl. driver
61°	ZUMI742142617	Tubb Trimless Single FC CRI90+ SLE G7 11,8/16,9W 350/500mA 1714/2449 lm 3000K 61° glass excl. driver

**3500K**

14°	ZUMI742152317	Tubb Trimless Single FC CRI90+ SLE G7 11,8/16,9W 350/500mA 1732/2474 lm 3500K 14° glass excl. driver
25°	ZUMI742152417	Tubb Trimless Single FC CRI90+ SLE G7 11,8/16,9W 350/500mA 1732/2474 lm 3500K 25° glass excl. driver
39°	ZUMI742152517	Tubb Trimless Single FC CRI90+ SLE G7 11,8/16,9W 350/500mA 1732/2474 lm 3500K 39° glass excl. driver
61°	ZUMI742152617	Tubb Trimless Single FC CRI90+ SLE G7 11,8/16,9W 350/500mA 1732/2474 lm 3500K 61° glass excl. driver

**4000K**

14°	ZUMI742162317	Tubb Trimless Single FC CRI90+ SLE G7 11,8/16,9W 350/500mA 1775/2536 lm 4000K 14° glass excl. driver
25°	ZUMI742162417	Tubb Trimless Single FC CRI90+ SLE G7 11,8/16,9W 350/500mA 1775/2536 lm 4000K 25° glass excl. driver
39°	ZUMI742162517	Tubb Trimless Single FC CRI90+ SLE G7 11,8/16,9W 350/500mA 1775/2536 lm 4000K 39° glass excl. driver
61°	ZUMI742162617	Tubb Trimless Single FC CRI90+ SLE G7 11,8/16,9W 350/500mA 1775/2536 lm 4000K 61° glass excl. driver

> REQUIREMENTS**False ceiling recessed kit**

ZUMIFB1	Tubb Trimless Single FC recessed kit
---------	--------------------------------------

> DRIVER**dimmable**

TRID28000671	LCA 25W 350-1050mA one4all SR PRE (DALI, DSI, switchDIM)
TRID28001110	PLUG 350mA
or	
TRID28001114	PLUG 500mA

**non dimmable**

TRID28000700	LC 25W 350-1050mA flexC SR EXC
TRID28001110	PLUG 350mA
or	
TRID28001114	PLUG 500mA

> OPTIONS**Honeycomb grid**

ZUMI25HC	Honeycomb grid
----------	----------------

**PRODUCT DESCRIPTION**

Trimless Single Downlighter for general or accent lighting equipped with a LEDmodule especially to enlighten several food products. There's a choice between 'fish' to light up fish products, 'gold' for bakery goods and 'gold+' for rather crusty bakery goods such as croissants and baguettes. The cannon 'meat+' provides a highly red color which is ideal for the presentation of meat.

Its 'fresh meat' is suitable to use for meat in the counter. Fruit is ideal for fruit and vegetables.


Available in a version for stretch ceiling and false ceiling.

Aluminium luminaire in several colors and color temperatures with several possible reflectors.

**TECHNICAL DATA**

Application	Recessed
Dimensions	visible dimensions: 154x154mm Tubb: ø80mm h80mm
IP rating	IP20
Power	350mA / 500mA
Lifetime L70/F10/65°C	>55000h
MacAdam ellipse	3
Guarantee	5 year

(\*on components, only if ordered luminaire **+driver**)



Color Temperature	Wattage excl. driver	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
FISH	11,8W	350mA	1411 lm	121 lm/W	/	E
	16,9W	500mA	2015 lm	121 lm/W	/	E
GOLD 2700K	11,8W	350mA	1308 lm	112 lm/W	/	E
	16,9W	500mA	1868 lm	112 lm/W	/	E
GOLD+ 2400K	11,8W	350mA	826 lm	73 lm/W	/	F
	16,9W	500mA	1171 lm	70 lm/W	/	F
MEAT+	11,8W	350mA	879 lm	75 lm/W	/	n.a
	16,9W	500mA	1256 lm	75 lm/W	/	n.a
FRESH MEAT	11,8W	350mA	857 lm	74 lm/W	/	n.a
	16,9W	500mA	1224 lm	74 lm/W	/	n.a
FRUIT	11,8W	350mA	1224 lm	105 lm/W	/	F
	16,9W	500mA	1748 lm	105 lm/W	/	F

**ORDER REFERENCE**

> LUMINAIRE

**! ORDER REFERENCE** + (1) **W** (white) / **B** (black)

+ (2) **G** (gold reflector) option only for Gold 2700K

**STRETCH CEILING**

FISH		
14°	ZUMI732173117	Tubb Trimless Single SC Fish SLE G7 11,8/16,9W 350/500mA 1411/2015 lm 14° PC excl. driver
25°	ZUMI732171917	Tubb Trimless Single SC Fish SLE G7 11,8/16,9W 350/500mA 1411/2015 lm 25° PC excl. driver
39°	ZUMI732172017	Tubb Trimless Single SC Fish SLE G7 11,8/16,9W 350/500mA 1411/2015 lm 39° PC excl. driver
61°	ZUMI732172117	Tubb Trimless Single SC Fish SLE G7 11,8/16,9W 350/500mA 1411/2015 lm 61° PC excl. driver

**GOLD 2700K**

14°	ZUMI732183117	Tubb Trimless Single SC Gold SLE G7 11,8/16,9W 350/500mA 1308/1868 lm 2700K 14° PC excl. driver
25°	ZUMI732181917	Tubb Trimless Single SC Gold SLE G7 11,8/16,9W 350/500mA 1308/1868 lm 2700K 25° PC excl. driver
39°	ZUMI732182017	Tubb Trimless Single SC Gold SLE G7 11,8/16,9W 350/500mA 1308/1868 lm 2700K 39° PC excl. driver
61°	ZUMI732182117	Tubb Trimless Single SC Gold SLE G7 11,8/16,9W 350/500mA 1308/1868 lm 2700K 61° PC excl. driver

**GOLD+ 2400K**

14°	ZUMI732083117	Tubb Trimless Single SC Gold+ SLE G7 11,8/16,9W 350/500mA 826/1171 lm 2400K 14° PC excl. driver
25°	ZUMI732081917	Tubb Trimless Single SC Gold+ SLE G7 11,8/16,9W 350/500mA 826/1171 lm 2400K 25° PC excl. driver
39°	ZUMI732082017	Tubb Trimless Single SC Gold+ SLE G7 11,8/16,9W 350/500mA 826/1171 lm 2400K 39° PC excl. driver
61°	ZUMI732082117	Tubb Trimless Single SC Gold+ SLE G7 11,8/16,9W 350/500mA 826/1171 lm 2400K 61° PC excl. driver

**MEAT+**

14°	ZUMI732193117	Tubb Trimless Single SC Meat+ SLE G7 11,8/16,9W 350/500mA 879/1256 lm 14° PC excl. driver
25°	ZUMI732191917	Tubb Trimless Single SC Meat+ SLE G7 11,8/16,9W 350/500mA 879/1256 lm 25° PC excl. driver
39°	ZUMI732192017	Tubb Trimless Single SC Meat+ SLE G7 11,8/16,9W 350/500mA 879/1256 lm 39° PC excl. driver
61°	ZUMI732192117	Tubb Trimless Single SC Meat+ SLE G7 11,8/16,9W 350/500mA 879/1256 lm 61° PC excl. driver

**FRESH MEAT**

14°	ZUMI732203117	Tubb Trimless Single SC Fresh Meat SLE G7 11,8/16,9W 350/500mA 857/1224 lm 14° PC excl. driver
25°	ZUMI732201917	Tubb Trimless Single SC Fresh Meat SLE G7 11,8/16,9W 350/500mA 857/1224 lm 25° PC excl. driver
39°	ZUMI732202017	Tubb Trimless Single SC Fresh Meat SLE G7 11,8/16,9W 350/500mA 857/1224 lm 39° PC excl. driver
61°	ZUMI732202117	Tubb Trimless Single SC Fresh Meat SLE G7 11,8/16,9W 350/500mA 857/1224 lm 61° PC excl. driver

**FRUIT**

14°	ZUMI732213117	Tubb Trimless Single SC Fruit SLE G7 11,8/16,9W 350/500mA 1224/1748 lm 14° PC excl. driver
25°	ZUMI732211917	Tubb Trimless Single SC Fruit SLE G7 11,8/16,9W 350/500mA 1224/1748 lm 25° PC excl. driver
39°	ZUMI732212017	Tubb Trimless Single SC Fruit SLE G7 11,8/16,9W 350/500mA 1224/1748 lm 39° PC excl. driver
61°	ZUMI732212117	Tubb Trimless Single SC Fruit SLE G7 11,8/16,9W 350/500mA 1224/1748 lm 61° PC excl. driver

*FALSE CEILING -recessed kit to be ordered separately !*

**FISH**

14°	ZUMI742173117	Tubb Trimless Single FC Fish SLE G7 11,8/16,9W 350/500mA 1411/2015 lm 14° PC excl. driver
25°	ZUMI742171917	Tubb Trimless Single FC Fish SLE G7 11,8/16,9W 350/500mA 1411/2015 lm 25° PC excl. driver
39°	ZUMI742172017	Tubb Trimless Single FC Fish SLE G7 11,8/16,9W 350/500mA 1411/2015 lm 39° PC excl. driver
61°	ZUMI742172117	Tubb Trimless Single FC Fish SLE G7 11,8/16,9W 350/500mA 1411/2015 lm 61° PC excl. driver

**GOLD 2700K**

14°	ZUMI742183117	Tubb Trimless Single FC Gold SLE G7 11,8/16,9W 350/500mA 1308/1868 lm 2700K 14° PC excl. driver
25°	ZUMI742181917	Tubb Trimless Single FC Gold SLE G7 11,8/16,9W 350/500mA 1308/1868 lm 2700K 25° PC excl. driver
39°	ZUMI742182017	Tubb Trimless Single FC Gold SLE G7 11,8/16,9W 350/500mA 1308/1868 lm 2700K 39° PC excl. driver
61°	ZUMI742182117	Tubb Trimless Single FC Gold SLE G7 11,8/16,9W 350/500mA 1308/1868 lm 2700K 61° PC excl. driver

**GOLD+ 2400K**

14°	ZUMI742083117	Tubb Trimless Single FC Gold+ SLE G7 11,8/16,9W 350/500mA 826/1171 lm 2400K 14° PC excl. driver
25°	ZUMI742081917	Tubb Trimless Single FC Gold+ SLE G7 11,8/16,9W 350/500mA 826/1171 lm 2400K 25° PC excl. driver
39°	ZUMI742082017	Tubb Trimless Single FC Gold+ SLE G7 11,8/16,9W 350/500mA 826/1171 lm 2400K 39° PC excl. driver
61°	ZUMI742082117	Tubb Trimless Single FC Gold+ SLE G7 11,8/16,9W 350/500mA 826/1171 lm 2400K 61° PC excl. driver

**MEAT+**

14°	ZUMI742193117	Tubb Trimless Single FC Meat+ SLE G7 11,8/16,9W 350/500mA 879/1256 lm 14° PC excl. driver
25°	ZUMI742191917	Tubb Trimless Single FC Meat+ SLE G7 11,8/16,9W 350/500mA 879/1256 lm 25° PC excl. driver
39°	ZUMI742192017	Tubb Trimless Single FC Meat+ SLE G7 11,8/16,9W 350/500mA 879/1256 lm 39° PC excl. driver
61°	ZUMI742192117	Tubb Trimless Single FC Meat+ SLE G7 11,8/16,9W 350/500mA 879/1256 lm 61° PC excl. driver

**FRESH MEAT**

14°	ZUMI742203117	Tubb Trimless Single FC Fresh Meat SLE G7 11,8/16,9W 350/500mA 857/1224 lm 14° PC excl. driver
25°	ZUMI742201917	Tubb Trimless Single FC Fresh Meat SLE G7 11,8/16,9W 350/500mA 857/1224 lm 25° PC excl. driver
39°	ZUMI742202017	Tubb Trimless Single FC Fresh Meat SLE G7 11,8/16,9W 350/500mA 857/1224 lm 39° PC excl. driver
61°	ZUMI742202117	Tubb Trimless Single FC Fresh Meat SLE G7 11,8/16,9W 350/500mA 857/1224 lm 61° PC excl. driver

**FRUIT**

14°	ZUMI742213117	Tubb Trimless Single FC Fruit SLE G7 11,8/16,9W 350/500mA 1224/1748 lm 14° PC excl. driver
25°	ZUMI742211917	Tubb Trimless Single FC Fruit SLE G7 11,8/16,9W 350/500mA 1224/1748 lm 25° PC excl. driver
39°	ZUMI742212017	Tubb Trimless Single FC Fruit SLE G7 11,8/16,9W 350/500mA 1224/1748 lm 39° PC excl. driver
61°	ZUMI742212117	Tubb Trimless Single FC Fruit SLE G7 11,8/16,9W 350/500mA 1224/1748 lm 61° PC excl. driver

> REQUIREMENTS

ZUMIFB1

**False ceiling recessed kit**

Tubb Trimless Single FC recessed kit

> DRIVER**dimnable**

TRID28000671	LCA 25W 350-1050mA one4all SR PRE (DALI, DSI, switchDIM)
TRID28001110	PLUG 350mA
or	
TRID28001114	PLUG 500mA

**non dimnable**

TRID28000700	LC 25W 350-1050mA flexC SR EXC
TRID28001110	PLUG 350mA
or	
TRID28001114	PLUG 500mA

> OPTIONS**Honeycomb grid**

ZUMI25HC	Honeycomb grid
----------	----------------

**PRODUCT DESCRIPTION**


Trimless Single Downlighter for general or accent lighting. Available in a version for stretch ceiling and false ceiling.

Aluminium luminaire in several colors and color temperatures with several possible reflectors.

**TECHNICAL DATA**

Application	Recessed
Dimensions	visible dimensions: 154x154mm Tubb: ø80mm h80mm
IP rating	IP20
Power	350mA / 500mA
Lifetime L70/F10/65°C	>55000h
MacAdam ellipse	3
Guarantee	5 year

(\*on components, only if ordered luminaire **+driver**)



Color Temperature	Wattage excl. driver	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
3100K	11,8W	350mA	1210 lm	104 lm/W	98	F
	16,9W	500mA	1729 lm	104 lm/W	98	F

**ORDER REFERENCE**

> [LUMINAIRE](#)

**! ORDER REFERENCE** + (1) **W** (white) / **B** (black)  
+ (2) **G** (gold reflector)

**STRETCH CEILING**

<b>14°</b>	ZUMI732222317	Tubb Trimless Single SC Art CRI97 SLE G7 11,8/16,9W 350/500mA 1210/1729 lm 3100K 14° glass excl. driver
<b>25°</b>	ZUMI732222417	Tubb Trimless Single SC Art CRI97 SLE G7 11,8/16,9W 350/500mA 1210/1729 lm 3100K 25° glass excl. driver
<b>39°</b>	ZUMI732222517	Tubb Trimless Single SC Art CRI97 SLE G7 11,8/16,9W 350/500mA 1210/1729 lm 3100K 39° glass excl. driver
<b>61°</b>	ZUMI732222617	Tubb Trimless Single SC Art CRI97 SLE G7 11,8/16,9W 350/500mA 1210/1729 lm 3100K 61° glass excl. driver

**FALSE CEILING -recessed kit to be ordered separately !**

<b>14°</b>	ZUMI742222317	Tubb Trimless Single FC Art CRI97 SLE G7 11,8/16,9W 350/500mA 1210/1729 lm 3100K 14° glass excl. driver
<b>25°</b>	ZUMI742222417	Tubb Trimless Single FC Art CRI97 SLE G7 11,8/16,9W 350/500mA 1210/1729 lm 3100K 25° glass excl. driver
<b>39°</b>	ZUMI742222517	Tubb Trimless Single FC Art CRI97 SLE G7 11,8/16,9W 350/500mA 1210/1729 lm 3100K 39° glass excl. driver
<b>61°</b>	ZUMI742222617	Tubb Trimless Single FC Art CRI97 SLE G7 11,8/16,9W 350/500mA 1210/1729 lm 3100K 61° glass excl. driver

> [REQUIREMENTS](#)

ZUMIFB1

**False ceiling recessed kit**

Tubb Trimless Single FC recessed kit

> [DRIVER](#)

**dimmable**

TRID28000671	LCA 25W 350-1050mA one4all SR PRE (DALI, DSI, switchDIM)
TRID28001110	PLUG 350mA
or	
TRID28001114	PLUG 500mA

**non dimmable**

TRID28000700	LC 25W 350-1050mA flexC SR EXC
TRID28001110	PLUG 350mA
or	
TRID28001114	PLUG 500mA

> [OPTIONS](#)

**Honeycomb grid**

ZUMI25HC Honeycomb grid


**PRODUCT DESCRIPTION**

Trimless Single Downlighter for general or accent lighting. Available in a version for stretch ceiling and false ceiling.  
Aluminium luminaire in several colors and color temperatures with several possible reflectors.



**TECHNICAL DATA**

Application Recessed  
 Dimensions visible dimensions: 154x154mm  
 Tubb: ø80mm h80mm  
 IP rating IP20  
 Power 350mA / 500mA  
 Lifetime L70/F10/65°C >55000h  
 MacAdam ellipse 3  
 Guarantee 5 year  
 (\*on components, only if ordered luminaire **+driver**)



Color Temperature	Wattage excl. driver	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
3250K	11,8W	350mA	1313 lm	136 lm/W	95	F

**ORDER REFERENCE**

> LUMINAIRE

**! ORDER REFERENCE + (1) W (white) / B (black)**

*STRETCH CEILING*

14°	ZUMI732232317	Tubb Trimless Single SC Fashion CRI95 SLE G7 11,8/16,9W 350/500mA 1313/1876 lm 3250K 14° glass excl. driver
25°	ZUMI732232417	Tubb Trimless Single SC Fashion CRI95 SLE G7 11,8/16,9W 350/500mA 1313/1876 lm 3250K 25° glass excl. driver
39°	ZUMI732232517	Tubb Trimless Single SC Fashion CRI95 SLE G7 11,8/16,9W 350/500mA 1313/1876 lm 3250K 39° glass excl. driver
61°	ZUMI732232617	Tubb Trimless Single SC Fashion CRI95 SLE G7 11,8/16,9W 350/500mA 1313/1876 lm 3250K 61° glass excl. driver

*FALSE CEILING -recessed kit to be ordered separately !*

14°	ZUMI742232317	Tubb Trimless Single FC Fashion CRI95 SLE G7 11,8/16,9W 350/500mA 1313/1876 lm 3250K 14° glass excl. driver
25°	ZUMI742232417	Tubb Trimless Single FC Fashion CRI95 SLE G7 11,8/16,9W 350/500mA 1313/1876 lm 3250K 25° glass excl. driver
39°	ZUMI742232517	Tubb Trimless Single FC Fashion CRI95 SLE G7 11,8/16,9W 350/500mA 1313/1876 lm 3250K 39° glass excl. driver
61°	ZUMI742232617	Tubb Trimless Single FC Fashion CRI95 SLE G7 11,8/16,9W 350/500mA 1313/1876 lm 3250K 61° glass excl. driver

> REQUIREMENTS

**False ceiling recessed kit**

ZUMIFB1 Tubb Trimless Single FC recessed kit

> DRIVER

**dimmable**

TRID28000671 LCA 25W 350-1050mA one4all SR PRE (DALI, DSI, switchDIM)  
 TRID28001110 PLUG 350mA  
 or  
 TRID28001114 PLUG 500mA

**non dimmable**

TRID28000700 LC 25W 350-1050mA flexC SR EXC  
 TRID28001110 PLUG 350mA  
 or  
 TRID28001114 PLUG 500mA

> OPTIONS

**Honeycomb grid**

ZUMI25HC Honeycomb grid