

**PRODUCT DESCRIPTION**

Ukkie SLA is a downlighter for general or accent lighting. The cone has a diameter of about 90mm. Available in different colors and color temperatures with a lens of 12°, 24° or 36°.

Aluminium luminaire.

**TECHNICAL DATA**

Application	Recessed
Dimensions	cut out Ø 80mm - H 110mm
IP rating	IP20
Power	230V
Lifetime L90/B10/40°C	>54000h
MacAdam ellipse	3
Guarantee	5 year



Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2700K	9,4W	230V	800 lm	85 lm/W	90+	F
3000K	9,4W	230V	830 lm	88 lm/W	90+	F
4000K	9,4W	230V	865 lm	92 lm/W	90+	F

**ORDER REFERENCE**

> [LUMINAIRE](#)

**! ORDER REFERENCE + W (white) / B (black) / G (gold) / C (champagne) / T (titanium) / BR (bronze)**

<b>2700K 12°</b>	ZUMI2133102701	UKKIE SLA AC G3 2700K 800lm 9.4W 230V 12° CRI90+
<b>2700K 24°</b>	ZUMI2133112801	UKKIE SLA AC G3 2700K 800lm 9.4W 230V 24° CRI90+
<b>2700K 36°</b>	ZUMI2133122901	UKKIE SLA AC G3 2700K 800lm 9.4W 230V 36° CRI90+
<b>3000K 12°</b>	ZUMI2133132701	UKKIE SLA AC G3 3000K 830lm 9.4W 230V 12° CRI90+
<b>3000K 24°</b>	ZUMI2133142801	UKKIE SLA AC G3 3000K 830lm 9.4W 230V 24° CRI90+
<b>3000K 36°</b>	ZUMI2133152901	UKKIE SLA AC G3 3000K 830lm 9.4W 230V 36° CRI90+
<b>4000K 12°</b>	ZUMI2133162701	UKKIE SLA AC G3 4000K 865lm 9.4W 230V 12° CRI90+
<b>4000K 24°</b>	ZUMI2133172801	UKKIE SLA AC G3 4000K 865lm 9.4W 230V 24° CRI90+
<b>4000K 36°</b>	ZUMI2133182901	UKKIE SLA AC G3 4000K 865lm 9.4W 230V 36° CRI90+

> [no driver needed](#)

dimnable phase cut - see dimmerlist

**PRODUCT DESCRIPTION**

Ukkie SLA is a downlighter for general or accent lighting. The cone has a diameter of about 90mm. Available in different colors and color temperatures with a lens of 12°, 24° or 36°.

Aluminium luminaire.

**TECHNICAL DATA**

Application	Recessed
Dimensions	cut out Ø 80mm - H 110mm
IP rating	IP44
Power	230V
Lifetime L90/B10/40°C	>54000h
MacAdam ellipse	3
Guarantee	5 year



Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2700K	9,4W	230V	800 lm	85 lm/W	90+	F
3000K	9,4W	230V	830 lm	88 lm/W	90+	F
4000K	9,4W	230V	865 lm	92 lm/W	90+	F

**ORDER REFERENCE**

> [LUMINAIRE](#)

**! ORDER REFERENCE + W (white) / B (black) / G (gold) / C (champagne) / T (titanium) / BR (bronze)**

<b>2700K 12°</b>	ZUMI2343102701	UKKIE SLA AC G3 2700K 800lm 9.4W 230V 12° CRI90+
<b>2700K 24°</b>	ZUMI2343112801	UKKIE SLA AC G3 2700K 800lm 9.4W 230V 24° CRI90+
<b>2700K 36°</b>	ZUMI2343122901	UKKIE SLA AC G3 2700K 800lm 9.4W 230V 36° CRI90+
<b>3000K 12°</b>	ZUMI2343132701	UKKIE SLA AC G3 3000K 830lm 9.4W 230V 12° CRI90+
<b>3000K 24°</b>	ZUMI2343142801	UKKIE SLA AC G3 3000K 830lm 9.4W 230V 24° CRI90+
<b>3000K 36°</b>	ZUMI2343152901	UKKIE SLA AC G3 3000K 830lm 9.4W 230V 36° CRI90+
<b>4000K 12°</b>	ZUMI2343162701	UKKIE SLA AC G3 4000K 865lm 9.4W 230V 12° CRI90+
<b>4000K 24°</b>	ZUMI2343172801	UKKIE SLA AC G3 4000K 865lm 9.4W 230V 24° CRI90+
<b>4000K 36°</b>	ZUMI2343182901	UKKIE SLA AC G3 4000K 865lm 9.4W 230V 36° CRI90+

> [no driver needed](#)

dimnable phase cut - see dimmerlist

**PRODUCT DESCRIPTION**

Ukkie SLA is a downlighter for general or accent lighting. The cone has a diameter of about 90mm. Available in different colors and color temperatures with a lens of 12°, 24° or 36°.

Aluminium luminaire.



**TECHNICAL DATA**

Application	Recessed
Dimensions	cut out Ø 80mm - H 110mm
IP rating	IP20
Power	250/300/350mA
Lifetime L90/B10/40°C	>54000h
MacAdam ellipse	3
Guarantee	5 year

**LOW OUTPUT**

Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2700K	8.7/8.5W	250mA	935/1060 lm	105/123 lm/W	90+	F
3000K	8.7/8.5W	250mA	985/1100 lm	113/127 lm/W	90+	F
4000K	8.7/8.5W	250mA	1010/1130 lm	116/130 lm/W	90+	F

**HIGH OUTPUT**

Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2700K	10.8/12W	300/350mA	1037/1370 lm	96/114 lm/W	90+	F
3000K	10.8/12W	300/350mA	1097/1500 lm	102/123 lm/W	90+	F
4000K	10.8/12W	300/350mA	1140/1535 lm	106/125 lm/W	90+	F

**ORDER REFERENCE**

> [LUMINAIRE](#)

**! ORDER REFERENCE + W (white) / B (black / G (gold) / C (champagne) / T (titanium) / BR (bronze)**

**2700K**

LOW OUTPUT

12°	ZUMI2113012714	UKKIE SLA DC G3 2700K 935lm 8.7W 250mA 12° CRI90+
24°	ZUMI2113022814	UKKIE SLA DC G3 2700K 1060lm 8,5W 250mA 24° CRI90+
36°	ZUMI2113032914	UKKIE SLA DC G3 2700K 1060lm 8,5W 250mA 36° CRI90+

HIGH OUTPUT

12°	ZUMI2113012713	UKKIE SLA DC G3 2700K 1037lm 10,8W 300mA 12° CRI90+
24°	ZUMI2113022806	UKKIE SLA DC G3 2700K 1370lm 12W 350mA 24° CRI90+
36°	ZUMI2113032906	UKKIE SLA DC G3 2700K 1370lm 12W 350mA 36° CRI90+

## ZUMI

---

### 3000K

#### LOW OUTPUT

12°	ZUMI2113042714	UKKIE SLA DC G3 3000K 985lm 8,7W 250mA 12° CRI90+
24°	ZUMI2113052814	UKKIE SLA DC G3 3000K 1100lm 8,5W 250mA 24° CRI90+
36°	ZUMI2113062914	UKKIE SLA DC G3 3000K 1100lm 8,5W 250mA 36° CRI90+

#### HIGH OUTPUT

12°	ZUMI2113042713	UKKIE SLA DC G3 3000K 1097lm 10,8W 300mA 12° CRI90+
24°	ZUMI2113052806	UKKIE SLA DC G3 3000K 1500lm 12W 350mA 24° CRI90+
36°	ZUMI2113062906	UKKIE SLA DC G3 3000K 1500lm 12W 350mA 36° CRI90+

### 4000K

#### LOW OUTPUT

12°	ZUMI2113072714	UKKIE SLA DC G3 4000K 1010lm 8,7W 250mA 12° CRI90+
24°	ZUMI2113082814	UKKIE SLA DC G3 4000K 1130lm 8,5W 250mA 24° CRI90+
36°	ZUMI2113092914	UKKIE SLA DC G3 4000K 1130lm 8,5W 250mA 36° CRI90+

#### HIGH OUTPUT

12°	ZUMI2113072713	UKKIE SLA DC G3 4000K 1140lm 10,8W 300mA 12° CRI90+
24°	ZUMI2113082806	UKKIE SLA DC G3 4000K 1130lm 12W 350mA 24° CRI90+
36°	ZUMI2113092906	UKKIE SLA DC G3 4000K 1130lm 12W 350mA 36° CRI90+

> DRIVER (to be placed remote)

**PRODUCT DESCRIPTION**

Ukkie SLA is a downlighter for general or accent lighting. The cone has a diameter of about 90mm. Available in different colors and color temperatures with a lens of 12°, 24° or 36°.

Aluminium luminaire.



**TECHNICAL DATA**

Application	Recessed
Dimensions	cut out Ø 80mm - H 110mm
IP rating	IP44
Power	250/300/350mA
Lifetime L90/B10/40°C	>54000h
MacAdam ellipse	3
Guarantee	5 year

**LOW OUTPUT**

Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2700K	8.7/8.5W	250mA	935/1060 lm	105/123 lm/W	90+	F
3000K	8.7/8.5W	250mA	985/1100 lm	113/127 lm/W	90+	F
4000K	8.7/8.5W	250mA	1010/1130 lm	116/130 lm/W	90+	F

**HIGH OUTPUT**

Color Temperature	Wattage	Forward Current	Lumen (LED) (at tp = 65°C)	Lumen/Watt (LED) (at tp = 65°C)	CRI	Energy Label
2700K	10.8/12W	300/350mA	1037/1370 lm	96/114 lm/W	90+	F
3000K	10.8/12W	300/350mA	1097/1500 lm	102/123 lm/W	90+	F
4000K	10.8/12W	300/350mA	1140/1535 lm	106/125 lm/W	90+	F

**ORDER REFERENCE**

> [LUMINAIRE](#)

**! ORDER REFERENCE + W (white) / B (black / G (gold) / C (champagne) / T (titanium) / BR (bronze)**

**2700K**

LOW OUTPUT

<b>12°</b>	ZUMI 2123012714	UKKIE SLA DC IP G3 2700K 935lm 8.7W 250mA 12° CRI90+
<b>24°</b>	ZUMI 2123022814	UKKIE SLA DC IP G3 2700K 1060lm 8,5W 250mA 24° CRI90+
<b>36°</b>	ZUMI 2123032914	UKKIE SLA DC IP G3 2700K 1060lm 8,5W 250mA 36° CRI90+

HIGH OUTPUT

<b>12°</b>	ZUMI 2123012713	UKKIE SLA DC IP G3 2700K 1037lm 10,8W 300mA 12° CRI90+
<b>24°</b>	ZUMI 2123022806	UKKIE SLA DC IP G3 2700K 1370lm 12W 350mA 24° CRI90+
<b>36°</b>	ZUMI 2123032906	UKKIE SLA DC IP G3 2700K 1370lm 12W 350mA 36° CRI90+

## ZUMI

---

### 3000K

#### LOW OUTPUT

12°	ZUMI 2123042714	UKKIE SLA DC IP G3 3000K 985lm 8,7W 250mA 12° CRI90+
24°	ZUMI 2123052814	UKKIE SLA DC IP G3 3000K 1100lm 8,5W 250mA 24° CRI90+
36°	ZUMI 2123062914	UKKIE SLA DC IP G3 3000K 1100lm 8,5W 250mA 36° CRI90+

#### HIGH OUTPUT

12°	ZUMI 2123042713	UKKIE SLA DC IP G3 3000K 1097lm 10,8W 300mA 12° CRI90+
24°	ZUMI 2123052806	UKKIE SLA DC IP G3 3000K 1500lm 12W 350mA 24° CRI90+
36°	ZUMI 2123062906	UKKIE SLA DC IP G3 3000K 1500lm 12W 350mA 36° CRI90+

### 4000K

#### LOW OUTPUT

12°	ZUMI 2123072714	UKKIE SLA DC IP G3 4000K 1010lm 8,7W 250mA 12° CRI90+
24°	ZUMI 2123082814	UKKIE SLA DC IP G3 4000K 1130lm 8,5W 250mA 24° CRI90+
36°	ZUMI 2123092914	UKKIE SLA DC IP G3 4000K 1130lm 8,5W 250mA 36° CRI90+

#### HIGH OUTPUT

12°	ZUMI 2123072713	UKKIE SLA DC IP G3 4000K 1140lm 10,8W 300mA 12° CRI90+
24°	ZUMI 2123082806	UKKIE SLA DC IP G3 4000K 1130lm 12W 350mA 24° CRI90+
36°	ZUMI 2123092906	UKKIE SLA DC IP G3 4000K 1130lm 12W 350mA 36° CRI90+

> DRIVER (to be placed remote)